





4 109

Original

1

DETAILED STATEMENT OF SPECIFICATIONS FOR ALTERATIONS, ADDITIONS, OR REPAIRS TO BUILDINGS, ALREADY ERECTED.

1. State how many buildings to be altered, One

2. What is the Street or Avenue, and the number thereof, 217 1/2 Broadway

3. Ward, 458

2

PRESENT BUILDING.

Give the following information as to the present building:

1. Size of lot on which it is located, No. feet front, 26; feet rear, 26; feet deep, 50

2. Size of building, No. feet front, 26; feet rear, 26; feet deep, 60 No. of stories in height, 4; No. of feet in height, from curb level to highest point, 41 ft

3. Material of Building, Brick & stone; Material of Front, marble

4. Whether roof is Peak, Flat, or Mansard, Gambrel or Double Pitch

5. Material of Roofing, felt and gravel

6. Depth of foundation walls, 16 feet. Thickness of foundation walls, 24 inches. Material of foundation walls, Stone

7. Thickness of upper walls, 12 inches. Material of upper walls, Brick

8. Whether Independent or Party-walls, party walls

9. Whether there is any other building on the lot, none

10. How the building is occupied, as a tenement one family on each floor, 1st story occupied as a store.

HOW TO BE ALTERED.

IF RAISED OR BUILT UPON

Give the following information:

1. How many stories will the building be when raised, 4 at curb front & rear walls, the square on a level with top of main floor.

2. How many feet high will the building be when raised, 41 feet

3. Will the roof be Flat, Peak, or Mansard, Flat

4. What will be the material of roofing, lead & stone

5. What will be the material of cornices and gutter, galvanized iron

6. What will be the means of access to roof, ladders & stairs

7. Will a Fire-escape be provided, if required, yes

8. Will iron shutters be provided, if required, none required

9. How will the building be occupied, as a tenement one family on each floor

tenement with one family on each floor 4 2nd floor 12 1/2 12 1/2

## IF EXTENDED ON ANY SIDE,

Give the following information:

1. Size of extension, No. of feet front, 21 feet; feet rear, 10 feet; feet deep, 10 feet; No. of stories in height, 1; No. of feet in height, 10 feet
2. What will be the material of foundation walls of extension brick. What will be the depth 4 feet. What will be the thickness, 12 inches.
3. What will be the material of upper walls of extension brick. How thick will the upper walls be, 12 inches.
4. Will the roof of extension be Flat, Peak, or Mansard, Flat
5. What will be the material of roofing, Asphalt
6. What will be the material of cornice and gutter, Asphalt
7. Will iron shutters be provided, if required, No
8. How will the extension be occupied, As a living room
9. How will the extension be connected with present or main building, By a door

## IF ALTERED INTERNALLY,

Give definite particulars, and state how the building will be occupied, and if for a dwelling, state by how many families.

Not altered internally

## IF THE FRONT, REAR, OR SIDE WALLS, OR ANY PORTION THEREOF, ARE TO BE TAKEN OUT AND REBUILT,

Give definite particulars, and state in what manner.

The front & rear walls are to be removed and replaced with brickwork of the same thickness as the original walls.

## THE FOLLOWING INFORMATION IS ALSO REQUIRED:

1. If the building is to be occupied as a tenement building after the proposed alteration, will it be altered in every respect to conform with the provisions of Section 28 of the Building Law, Yes

2. How much will the Alteration cost, \$1,500 fifteen hundred Dollars

3. Will all materials and workmanship be in accordance with the provisions of the Law, Yes

Owner Charles J. Cooper Address 1234 Main St.

Architect William J. Cooper Address 1234 Main St.

Mason John J. Cooper Address 1234 Main St.

Carpenter John J. Cooper Address 1234 Main St.

1893

ALT: 1889

DEPT OF BUILDINGS

717

Original

FORM No. 2-1892.

2 1343

Plan No. 717

### APPLICATION TO ALTER, REPAIR, ETC.

Application is hereby made to alter as per subjoined detailed statement of specification for Alterations, Additions, or Repairs to buildings already erected, and herewith submit Plans and Drawings of such proposed alterations; and I do hereby agree that the provisions of the Building Law will be complied with, whether the same are specified herein or not.

(Sign here) *W. B. Smith*

NEW YORK, April 23 1893

- 1. State how many buildings to be altered. *One*
- 2. What is the street or avenue and the number thereof? Give diagram of property. *No 327*
- 3. How much will the alteration cost? \$ *about \$2000*

#### GIVE THE FOLLOWING INFORMATION AS TO THE PRESENT BUILDING:

- 1. Size of lot on which it is located, No. of feet front, *25*; feet rear, *25*; feet deep, *80*
- 2. Size of building, No. of feet front, *25*; feet rear, *25*; feet deep, *62*. No. of stories in height, *four*; No. of feet in height from curb level to highest point of beams, *56*
- 3. Material of building, *Brick & Stone*; material of front, *Granite*
- 4. Whether roof is peak, flat, or mansard, *flat*
- 5. Depth of foundation walls, *15* feet; thickness of foundation walls, *24*; materials of foundation walls, *Stone*
- 6. Thickness of upper walls, *12"* inches. Material of upper walls, *Brick*
- 7. Whether independent or party walls, *party walls*
- 8. How the building is or was occupied, *dwelling and store*

#### IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION:

- 1. How many stories will the building be when raised? \_\_\_\_\_
- 2. How high will the building be when raised? \_\_\_\_\_
- 3. Will the roof be flat, peak, or mansard? \_\_\_\_\_
- 4. What will be the thickness of wall of additional stories? \_\_\_\_\_ story, \_\_\_\_\_ inches; \_\_\_\_\_ story, \_\_\_\_\_ inches.
- 5. Give size and material of floor beams of additional stories; \_\_\_\_\_ 1st tier, \_\_\_\_\_ x \_\_\_\_\_ 2d tier, \_\_\_\_\_ x \_\_\_\_\_ Distance from centres on \_\_\_\_\_ tier, \_\_\_\_\_ inches; \_\_\_\_\_ tier \_\_\_\_\_ inches.
- 6. How will the building be occupied? *As a cabinet maker shop*

#### IF TO BE EXTENDED ON ANY SIDE, GIVE THE FOLLOWING INFORMATION.

- 1. Size of extension, No. feet front, \_\_\_\_\_; feet rear, \_\_\_\_\_; feet deep, \_\_\_\_\_; No. of stories in height, \_\_\_\_\_; No. of feet in height, \_\_\_\_\_
- 2. What will be the material of foundation walls of extension? \_\_\_\_\_ What will be the depth? \_\_\_\_\_ feet. What will be the thickness? \_\_\_\_\_ inches.
- 3. Will foundation be laid on earth, sand, rock, timber or piles? \_\_\_\_\_

*No top*



IF TO BE EXTENDED ON ANY SIDE GIVE THE FOLLOWING INFORMATION.

4. What will be the base, stone or concrete? ..... If base stones, give size and thickness and how laid, ..... If concrete, give thickness, .....
5. What will be the sizes of piers? ..... What will be the sizes of the base of piers? .....
6. What will be the thickness of upper walls? 1st story, ..... inches ; 2d story ..... inches ; 3d story, ..... inches ; 4th story, ..... inches ; 5th story, ..... inches ; 6th story, ..... inches ; 7th story, ..... inches ; from thence to top, ..... inches ; and of what materials to be constructed, .....
7. State whether independent or party-walls. .... If party-walls give thickness thereof. ....
8. With what material will walls be coped? .....
9. What will be the materials of front? ..... If of stone, what kind? ..... Give thickness of front ashlar. .... Give thickness of backing. ....
10. Will the roof be flat, peaked or mansard? .....
11. What will be the materials of roofing? .....
12. Give size and material of floor beams, 1st tier, ..... ; 2d tier, ..... ; 3d tier, ..... ; 4th tier, ..... ; 5th tier, ..... ; 6th tier, ..... ; 7th tier, ..... ; roof tier, ..... State distance from centres on 1st tier, ..... inches ; 2d tier, ..... inches ; 3d tier, ..... inches ; 4th tier, ..... inches ; 5th tier, ..... inches ; 6th tier, ..... inches ; 7th tier, ..... inches ; roof tier, ..... inches
13. If floors are to be supported by columns and girders, give the following information : Size and material of girders under 1st floor, ..... under each of the upper floors, ..... Size and material of columns under first floor, ..... under each of the upper floors, .....
14. If the front, rear or side walls are to be supported, in whole or in part, by iron girders or lintels, give definite particulars, .....
15. If girders are to be supported by brick piers and columns, state the size of piers and columns. ....
16. How will the extension be connected with present or main building? .....
17. How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. ....
18. State who will superintend the alterations. *W. H. Smith*
19. How many buildings are to be taken down? *6*

IF ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED :

*New transoms & headers inserted in 2<sup>d</sup> 3<sup>d</sup> & 4<sup>th</sup> floor, iron beams inserted to support the floors and the ground floor floor to be removed. The basement and first floor to have new supports.*

IF THE FRONT, REAR, OR SIDE WALLS, OR ANY PORTION THEREOF, ARE TO BE TAKEN OUT AND REBUILT, GIVE DEFINITE PARTICULARS, AND STATE IN WHAT MANNER :

.....  
.....  
.....  
.....

ALT 1893

Owner Estate Peter Cooper Address 17 Broadway  
Architect Bruce Address \_\_\_\_\_  
Mason \_\_\_\_\_ Address \_\_\_\_\_  
Carpenter J. B. Smith Address 18 Broadway

REPORT UPON APPLICATION.

NEW YORK, April 28 1893

To the Superintendent of Buildings:

I respectfully report that I have thoroughly examined and measured the building, walls, etc., named in the foregoing application, and found the foundation wall 3 to be built of Stone 24 inches thick, 15 feet below curb, the upper wall 3 built of Brick 12 inches thick, 62 feet deep. 51 feet in height, and that the mortar in said wall is hard and good, and that all the walls are \_\_\_\_\_ in good and safe condition.

What is the nature of the ground? \_\_\_\_\_

What kind of sand was used in the mortar? \_\_\_\_\_

How is or was the building occupied? Not occupied at present

(The Inspector must here state what defects, if any, are in the walls, beams or other part of the building.)  
The " " state the thickness of each wall in each and every story.)

Foundation Walls Stone 24"

Upper " Brick 12"

No Defects

J. G. Brown Inspector.

THE BUILDING LAW REQUIRES:

- 1st—All stone walls must be properly bonded.
- 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass.
- 3d—All buildings over two stories or above 25 feet in height, *except dwellings, school-houses, and churches*, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted.
- 4th—Outside fire escapes are required on all dwelling houses, occupied or built to be occupied by three or more families above the first story, and on hotels or lodging houses more than three stories in height, and on boarding houses, office buildings, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows:

BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE.

BRACKETS must not be less than 1 1/2 x 1 3/4 inches wrought iron, placed edgewise, or 1 3/4 inch angle iron 1/4 inch thick, well braced, and not more than three feet apart, and the braces to brackets must be not less than 3/4 inch square wrought iron, and must extend two-thirds of the width of the respective brackets or balconies. In all cases the brackets must go through the wall, and be turned down three inches.

BRACKETS ON NEW BUILDINGS must be set as the walls are being built. When brackets are to be put on old houses, the part going through the wall shall not be less than one inch diameter, with screw nuts and washers not less than five inches square and 1/2 inch thick.

TOP RAILS.—The top rail of balcony must be 1 3/4 inch x 1/2 inch wrought iron or 1 1/2 inch angle iron 1/4 inch thick, and in all cases must go through the walls, and be secured by nuts and 4 inch square washers, at least 3/8 inch thick, and no top rail shall be connected at angles by the use of cast iron.

BOTTOM RAILS.—Bottom rails must be 1 1/4 inch x 3/8 inch wrought iron or 1 1/2 inch angle iron 1/4 inch thick, well leaded into the wall. In frame buildings the top rails must go through the studding and be secured on the inside by washers and nuts as above.

FILLING-IN BARS.—The filling-in bars must be not less than 1/2 inch round or square wrought iron, placed not more than 6 inches from centres, and well riveted to the top and bottom rails.

STAIRS.—The stairs in all cases must be not less than 18 inches wide, and constructed of 1/2 x 3 1/2 inch wrought iron sides or strings. Steps may be of cast iron of the same width of strings, or 3/8 inch round iron, double rungs, and well riveted to the strings. The stairs must be secured to a bracket on top and rest on and be secured to a bracket or extra cross bar at the bottom. All stairs must have a 3/4 inch hand rail of wrought iron, well braced.

FLOORS.—The flooring of balconies must be of wrought iron 1 1/2 x 3/8 inch slats placed not over 1 3/4 inches apart, and secured to iron battens 1 1/2 x 3/8 inch, not over three feet apart and riveted at the intersection. The openings for stairways in all balconies shall not be less than 20 inches wide and 36 inches long, and have no covers.

DROP LADDERS.—Drop ladders from lower balconies where required shall not be less than 14 inches wide, and shall be made of 1 1/2 x 3/8 inch sides and 5/8 inch rungs of wrought iron. In no case shall a drop ladder be more than 12 feet in length. In no case shall the ends of balconies extend more than nine inches over the brackets.

SCUTTLE LADDERS.—Ladders to scuttles shall be constructed in all cases the same as the stairs or step-ladders from balconies of fire escapes.

THE HEIGHT OF RAILING around balconies shall not be less than two feet nine inches.

**No Fire Escape will be approved if not in accordance with above specifications.**

- 5th—All walls must be coped with stone or terra cotta. If coped with stone, the stone must not be less than 2 1/2 inches thick; and if with terra cotta, the terra cotta must be made with proper lap joints.
- 6th—Roofs must be covered with fire-proof material.
- 7th—All cornices must be fire-proof.
- 8th—All FLUES IN BUILDINGS hereafter erected must conform with the provisions of section 25, chapter 275, laws of 1892.
- 9th—No iron beam, lintel, or girder, intended to support a wall, shall be used for that purpose, *until tested and approved* as provided by law.



DEPARTMENT OF BUILDINGS.

Detailed Statement of Specification for Alterations to Buildings.

No. 717 Submitted April 25 1893

LOCATION. 327 Bowery

Owner Estate Peter Cooper

Architect Jas B. Smith

Builder J. G. Cronm April 28 1893

Returned by " " 19 1893

Report favorable.

FINAL REPORT. NEW YORK, Oct. 2 1893

To the Superintendent of Buildings: Work was commenced on the within described building on the 28 day of June 1893 and completed on the 30 day of Sept. 1893 and has been done in accordance with the foregoing detailed statement, except as noted below.

J. G. Cronm Inspector. REMARKS:

Referred to Inspector J. G. Cronm June 27 1893

Returned J. G. Cronm Oct 3 1893 Inspector.

NEW YORK, May 1 1893

This is to certify that I have examined the within detailed statement, together with the copy of the plans relating thereto, and find the same to be in accordance with the provisions of the laws relating to Buildings in the city of New York; that the same has been approved and entered in the records of this Department.

Approved: Enoch Wickens Superintendent of Buildings.

May 19 1893

Plans filed this date J. B. Smith

May 19 1893

See amendments attached to second page.

Dis-approved Enoch Wickens

May 25 1893 Key Dept of Bldg

See amendment attached June 13 1893

Incomplete J. B. Smith June 27 1893 Dis-approved Enoch Wickens

Approved June 22 1893

Approved Enoch Wickens Superintendent of Buildings

Approved Enoch Wickens Key Dept of Bldg

June 27 1893

Handwritten notes on the right side of the page, including dates and names.

ORIGINAL.

ALT. 1899

Applicant must indicate the Building Line or Lines, clearly and distinctly on the Drawings.

DEPARTMENT OF BUILDINGS  
CITY OF NEW YORK

RECEIVED

3

FORM No. 2.

Plan No. 1302

B 458

APPLICATION TO ALTER, REPAIR, Etc.

Application is hereby made to the Superintendent of Buildings of the City of New York, for the approval of the detailed statement of the specifications and plans herewith submitted, for the alteration or repair of the building herein described. All provisions of the Building Law shall be complied with in the alteration or repair of said building, whether specified herein or not.

(Sign here) *Esq. of Peter Cooper*  
*A. Salisbury*

NEW YORK, *Jan 6<sup>th</sup>* 1899

- 1. State how many buildings to be altered. *One*
- 2. What is the street or avenue and the number thereof? Give diagram of property. *327*  
*Bowery*
- 3. How much will the alteration cost? \$ *600<sup>00</sup>/<sub>100</sub>*

GIVE THE FOLLOWING INFORMATION AS TO THE PRESENT BUILDING :

- 1. Size of lot on which it is located, No. of feet front, *25'10"*; feet rear, *25'0"*; feet deep, *118 alt*
- 2. Size of building, No. of feet front, *25'10"*; feet rear, *25'0"*; feet deep, *65* No. of stories in height, *4*; No. of feet in height from curb level to highest point of beams, *49'0"*
- 3. Material of building, *Sand Stone, Brickwood*; material of front, *Sand Stone*
- 4. Whether roof is peak, flat, or mansard, *flat*
- 5. Depth of foundation walls, \_\_\_\_\_ feet; thickness of foundation walls, *12" + 30"*; materials of foundation walls, *Stone Rubble in mortar*
- 6. Thickness of upper walls, *12'* inches. Material of upper walls, *Sand Stone + Brick*
- 7. Whether independent or party walls, *Independent with all party South wall*
- 8. How the building is or was occupied, *as tenement now vacant*

IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION: *No.*

- 1. How many stories will the building be when raised? \_\_\_\_\_
- 2. How high will the building be when raised? \_\_\_\_\_
- 3. Will the roof be flat, peak, or mansard? \_\_\_\_\_
- 4. What will be the thickness of wall of additional stories? \_\_\_\_\_ story, \_\_\_\_\_ inches; \_\_\_\_\_ story, \_\_\_\_\_ inches.
- 5. Give size and material of floor beams of additional stories; \_\_\_\_\_ 1st tier, \_\_\_\_\_ x \_\_\_\_\_ 2d tier, \_\_\_\_\_ x \_\_\_\_\_ Distance from centres on \_\_\_\_\_ tier, \_\_\_\_\_ inches; \_\_\_\_\_ tier \_\_\_\_\_ inches.
- 6. How will the building be occupied? \_\_\_\_\_

IF TO BE EXTENDED ON ANY SIDE, GIVE THE FOLLOWING INFORMATION. *No.*

- 1. Size of extension, No. feet front, \_\_\_\_\_; feet rear, \_\_\_\_\_; feet deep, \_\_\_\_\_; No. of stories in height, \_\_\_\_\_; No. of feet in height, \_\_\_\_\_
- 2. What will be the material of foundation walls of extension? \_\_\_\_\_ What will be the depth? \_\_\_\_\_ feet. What will be the thickness? \_\_\_\_\_ inches.
- 3. Will foundation be laid on earth, sand, rock, timber or piles? \_\_\_\_\_



IF TO BE EXTENDED ON ANY SIDE GIVE THE FOLLOWING INFORMATION.

4. What will be the base, stone or concrete? ..... If base stones, give size and thickness and how laid, ..... If concrete, give thickness, .....
5. What will be the sizes of piers? ..... What will be the sizes of the base of piers? .....
6. What will be the thickness of upper walls? 1st story, ..... inches ; 2d story ..... inches ; 3d story, ..... inches ; 4th story, ..... inches ; 5th story, ..... inches ; 6th story, ..... inches ; 7th story, ..... inches ; from thence to top, ..... inches ; and of what materials to be constructed, .....
7. State whether independent or party-walls. .... If party-walls give thickness thereof. ....
8. With what material will walls be coped? .....
9. What will be the materials of front? ..... If of stone, what kind? ..... Give thickness of front ashlar. .... Give thickness of backing. ....
10. Will the roof be flat, peaked or mansard? .....
11. What will be the materials of roofing? .....
12. Give size and material of floor beams, 1st tier, ..... x ..... ; 2d tier, ..... x ..... ; 3d tier, ..... x ..... ; 4th tier, ..... x ..... ; 5th tier, ..... x ..... ; 6th tier, ..... x ..... ; 7th tier, ..... x ..... ; roof tier, ..... x ..... State distance from centres on 1st tier, ..... inches ; 2d tier, ..... inches ; 3d tier, ..... inches ; 4th tier, ..... inches ; 5th tier, ..... inches ; 6th tier, ..... inches ; 7th tier, ..... inches ; roof tier, ..... inches
13. If floors are to be supported by columns and girders, give the following information : Size and material of girders under 1st floor, ..... x ..... under each of the upper floors, ..... Size and material of columns under first floor, ..... under each of the upper floors, .....
14. If the front, rear or side walls are to be supported, in whole or in part, by iron girders or lintels, give definite particulars, .....
15. If girders are to be supported by brick piers and columns, state the size of piers and columns. ....
16. How will the extension be connected with present or main building? .....
17. How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. ....

18. State who will superintend the alterations. Atkinson 17-Busling Slip N.Y.C.

IF ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED :

As a store and lift.

IF THE FRONT, REAR, OR SIDE WALLS, OR ANY PORTION THEREOF, ARE TO BE TAKEN OUT AND REBUILT, GIVE DEFINITE PARTICULARS, AND STATE IN WHAT MANNER :

It is proposed to tear out the existing front wall, consisting of iron and sand stone, up to the elevation of the bottom of the second story floor beams, and to replace it with an iron construction; supporting the front wall, at the second floor level, with an iron beam girder supported at each end by cast iron columns, which in turn will bear on granite stones set in existing stone foundation walls. These walls will be strengthened as shown on accompanying plan. The lintel of the building adjacent to 327 on the north will be carried by the north column as shown.



# BUREAU OF BUILDINGS

## BOROUGH OF MANHATTAN, CITY OF NEW YORK

NOTICE—This Application must be TYPEWRITTEN and filed in TRIPLICATE. "SPECIFICATIONS—SHEET A" [Form 152] must be filed with EVERY Alteration Application.

"SPECIFICATIONS—SHEET B" [Form 158] must be filed, in addition, in case the building is to be raised in height or occupancy changed so as to increase floor loads, or if building is to be enlarged on one side.

**ALT.** APPLICATION No. 1996 192 4 BLOCK 438 LOT 2

LOCATION 327 Bowery

Examined 192 Examiner

### SPECIFICATIONS—SHEET B

If the building is to be raised in height or if the occupancy is changed so that the floor loads will be increased, the following information must be given as to the EXISTING BUILDING, and the thicknesses of existing walls and size of footings must be clearly shown on the plans:

(9) FOUNDATIONS: Character (whether stone, concrete, caisson, piles, grillage, etc.) Stone & Brick

Depth below curb 15' 0

Soil on which they rest (as per §231, Building Code.)

(10) UPPER WALLS: Material Brick & Sandstone

Kind of Mortar P.C. Mortar

Thickness of Ashlar (if any)

(11) PARTY WALLS: Any to be used?

If building is to be enlarged or extended, the following information as to the NEW WORK must be given:

(12) FOUNDATIONS: Character (whether stone, concrete, caisson, piles, grillage, etc.)

Depth below curb

Soil on which they rest (as per §231, Building Code)

(13) FOUNDATION WALLS: Material

(14) UPPER WALLS: Material

Kind of Mortar

Thickness of Ashlar (if any)

(15) PARTY WALLS: Any to be used?



In every case filed on SHEET B, the following information relative to existing and new construction must be given separately:

S

(16) FLOOR CONSTRUCTION:

Steel & wood

(17) SAFE CARRYING CAPACITY of floors per square foot:

180 lb. live load - first floor  
60 lb. - upper floors

State also whether floor capacities for existing construction have been previously filed, approved and posted, and, if possible, give date: No.

(18) PARTITIONS (Material and Thickness):

Interior

Stair Halls

Shafts

(19) ROOFING (Material):

(20) FIREPROOFING (Material and Thickness):

Columns

Girders

Beams

(21) INTERIOR FINISH (Material):

Floor Surface

Trim, Sash, Doors, etc.

(22) OUTSIDE WINDOW FRAME AND SASH (Material):



Graphair

ALT 1924

# BUREAU OF BUILDINGS

## BOROUGH OF MANHATTAN, CITY OF NEW YORK

**ALT.** APPLICATION No. 1996 1924

LOCATION 327 Bowery

REFERRED TO INSPECTOR Aug 14 1924, 1924, FOR IMMEDIATE REPORT AS TO OCCUPANCY: (If vacant, how last occupied?)

- sub use Basement  Storage 6th Floor.....
- 1st Floor  Floor + Storage 7th Floor.....
- 2d Floor  Storage 8th Floor.....
- 3d Floor  4 9th Floor.....
- 4th Floor  4 10th Floor.....
- 5th Floor.....

Is Building Fireproof, Non-fireproof or Frame? Non Fireproof  
What are the posted floor capacities? none posted.

Remarks: Gal 3455<sup>24</sup> + 3463<sup>24</sup> Pending

(Dated) August 16<sup>th</sup>, 1924  
(Signed) J. F. Mc Donnell Inspector.



5