

1057
B388
L28

Original

1057

Department for the Survey and Inspection of Buildings,

OFFICE, No. 2 FOURTH AVENUE.

New York, Sept 29th 1869

PLAN AND SPECIFICATION

For Alterations, Additions, or Repairs to Buildings already Erected.

The undersigned gives notice that David Jones owner ~~is~~ of premises Sixth St (opposite Brewery) proposes to alter or enlarge the building thereon, in the manner described below, and respectfully requests that said premises be examined, and a permit granted for such alteration or enlargement.

The present building is built of Brick, 3 stories, ^{about} 30 feet in height, 21 feet front 40 feet deep, with flat roof.

The foundation walls are built of Brick, 12 inches thick. The upper walls are built of Brick, 8 inches thick, and ^{about} 30 feet in height from curb level.

If independent walls, state the fact _____

If party-walls, state the fact Yes

If there is any other building on the lot, state the fact an old wooden building

Owner David Jones Residence _____

Architect Peter Tostevin Residence 25 South 4th St Brooklyn E D

Builder Rabold & Tostevin Residence _____

OWNER: DAVID JONES
ARCHITECT: PETER TOSTEVIN
BUILDER: RABOLD + TOSTEVIN

DESCRIPTION OF PROPOSED ALTERATIONS, ADDITIONS, OR REPAIRS.

- If raised or built upon, give The walls will be raised about 3 feet
- Number of stories The 1st & 2nd stories are to be made into 1 story
 - Number of feet in height about 33 feet in height
 - Style of roof Flat - Mansard roof front & rear
 - Materials of roofing Slate & tin
 - Materials of cornices Galvanized iron
 - Access to roof Scuttle & stairs
 - Fire escape, if required yes
 - Iron shutters, if required yes
 - How to be occupied Office 1st floor - 2nd floor for Janitor

If extended on the front, rear, or either side, give: 4 feet in front 24 feet in rear

1. Width and depth of extension 4 x 21 in front 24 x 21 in rear

2. Numbers of stories One

3. Number of feet in height about 20 feet

4. Depth, thickness, and materials of foundation walls. Brick - 6 feet below curb 12" thick

5. Height, thickness, and materials of upper walls about 20 ft high 12" thick

6. In what manner the extension is to be connected with the present building connected with anchors & blockings

If internal alterations are to be made, give definite particulars. The 1st floor is to be one large office - The 2nd floor will be arranged for Janitor & will be made satisfactory to the Department

If the front, rear, or side walls, or any portion of the same, are to be taken out and rebuilt, state in what manner,

The Brick front is to be taken out & a 1st class iron front put up - The rear wall is to be taken down & extended ^{set} back as depicted.

The party walls are to be made 8" thicker with hard brick & cement & well anchored with iron nails.

23. Make diagrams showing present building and main points of proposed alterations or additions.

Give the probable cost of the proposed alteration

about \$ 6,000

That all materials and construction will be in conformity to the provisions of the law.

Yes.

Original

Info

APPLICATION TO ALTER, REPAIR, ETC.

Application is hereby made to alter as per subjoined detailed statement of specification for Alterations, Additions or Repairs to buildings already erected, and herewith submit Plans and Drawings of such proposed alterations; and do hereby agree that the provisions of the Building Law will be complied with, whether the same are specified herein or not.

(Sign here) Louis F. Benisek

NEW YORK, May 28th 1891.

1. State how many buildings to be altered. one
2. What is the street or avenue and the number thereof? Give diagram of property. #638 E. 6th St.
3. How much will the alteration cost? \$ \$6000

GIVE THE FOLLOWING INFORMATION AS TO THE PRESENT BUILDING:

1. Size of lot on which it is located, No. of feet front, 21'0"; feet rear, 21'0"; feet deep, 97'0"
2. Size of building, No. of feet front, 21'0"; feet rear, 21'0"; feet deep, 70'0" No. of stories in height, 10^{stories}; No of feet in height from curb level to highest point of beams, 23'0"
3. Material of building, brick; material of front, _____
4. Whether roof is peak, flat, or mansard, mansard roof
5. Depth of foundation walls 10' below curb feet; thickness of foundation walls, _____; materials of foundation walls, brick
6. Thickness of upper walls, 12" inches. Material of upper walls, brick
7. Whether independent or party walls, independent, one part of westerly sidewall - party wall
8. How the building is or was occupied? It was used as store with one family in mansard roof

IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION:

1. How many stories will the building be when raised? _____
2. How high will the building be when raised? _____
3. Will the roof be flat, peak, or mansard? _____
4. What will be the thickness of wall of additional stories? _____ story, _____ inches; _____ story, _____ inches.
5. Give size and material of floor beams of additional stories; _____ 1st tier, _____ x _____ 2d tier, _____ x _____ Distance from centres on _____ tier, _____ inches; _____ tier _____ inches.
6. How will the building be occupied? _____

IF TO BE EXTENDED ON ANY SIDE, GIVE THE FOLLOWING INFORMATION.

1. Size of extension, No. feet front, 21'0"; feet rear, 21'0"; feet deep, 22'0"; No. of stories in height, one story; No. of feet in height, 23'0"
2. What will be the material of foundation walls of extension? H. R. brick. What will be the depth? 10' below curb feet. What will be the thickness? 16 inches.
3. Will foundation be laid on earth, sand, rock, timber or piles? on earth

IF TO BE EXTENDED ON ANY SIDE GIVE THE FOLLOWING INFORMATION.

4. What will be the base, stone or concrete? *concrete* If base stones, give size and thickness and how laid, _____ If concrete, give thickness, *3' x 18"*
5. What will be the sizes of piers? _____ What will be the sizes of the base of piers? _____
6. What will be the thickness of upper walls? 1st story, *12"* inches; 2d story _____ inches; 3d story, _____ inches; 4th story, _____ inches; 5th story, _____ inches; 6th story, _____ inches; 7th story, _____ inches; from thence to top, *8* inches; and of what materials to be constructed, *of best A B brick*
7. State whether independent or party-walls, *Independent* If party-walls give thickness thereof _____
8. With what material will walls be coped? *with blue stone coping*
9. What will be the materials of front? _____ If of stone, what kind? _____
Give thickness of front ashlar _____ Give thickness of backing _____
10. Will the roof be flat, peaked or mansard? *flat roof*
11. What will be the materials of roofing? *tin*
12. Give size and material of floor beams, 1st tier, *of yellow pine 4" x 10"*; 2d tier, _____; 3d tier, _____; 4th tier, _____; 5th tier, _____; 6th tier, _____; 7th tier, _____; roof tier, *of spruce, 3" x 10"* State distance from centres on 1st tier *14" from center* inches; 2d tier, _____ inches; 3d tier, _____ inches; 4th tier, _____ inches; 5th tier, _____ inches; 6th tier, _____ inches; 7th tier, _____ inches; roof tier, *20" from centers* inches
13. If floors are to be supported by columns and girders, give the following information: Size and material of girders under 1st floor, *of yellow pine, 12" x 10"* under each of the upper floors, _____ Size and material of columns under first floor, *4" cast iron columns of metal* under each of the upper floors, _____
14. If the front, rear or side walls are to be supported, in whole or in part, by iron girders or lintels, give definite particulars, *small extension in rear to be supported by two (7") wrought iron beams 55 lbs per yd. and wrought iron cross beam, 40 lbs per yd.*
15. If girders are to be supported by brick piers and columns, state the size of piers and columns. _____
16. How will the extension be connected with present or main building? *Extension to be checked to old building.*
17. How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. *Present building & extension to be used as Synagogue*
18. State who will superintend the alterations. *Louis F. Heinicke*

IF ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED:

Present stairs marked dotted on plans to be taken out, in front to be put a new stairs leading from cellar vestibule to gallery & mansard floor, all as shown. Also have in front a gallery as marked on plans. Floor beams for same to be 4" x 10" of yellow pine 7' 14" from centers. Present iron front not to be disturbed. Present 1st story floor beams in front to be supported by yellow pine girders 12"

IF THE FRONT, REAR, OR SIDE WALLS, OR ANY PORTION THEREOF, ARE TO BE TAKEN OUT AND REBUILT, GIVE DEFINITE PARTICULARS, AND STATE IN WHAT MANNER:

OWNER: HERMAN GEOTTECK
ARCHITECT: LOUIS F. HEINECKE

Owner Herman Geottek, Architect Address # 313 E 34th St. City
Architect Louis F. Heinecke Address 62 Boverly
Mason _____ Address _____
Carpenter _____ Address _____

REPORT UPON APPLICATION.

BUREAU OF INSPECTION OF BUILDINGS,

NEW YORK, June 9 1891

To the Superintendent of Buildings:

I respectfully report that I have thoroughly examined and measured the building, walls, etc., named in the foregoing application, and found the foundation wall to be built of Brick 16 inches thick, 10 feet below curb, the upper wall built of Brick 12.8 inches thick, 7.0 feet deep, 7.5 feet in height, and that the mortar in said wall is hard and good, and that all the walls are in good and safe condition.

What is the nature of the ground? Good

What kind of sand was used in the mortar? Sharp

How is or was the building occupied? _____

(The Inspector must here state what defects, if any, are in the walls, beams or other part of the building.)

The " " state the thickness of each wall in each and every story.)

7.5' of rear portion of west wall is 12" brick foundation
8" 1 + 2 story

Amos Duffey Inspector.
THE BUILDING LAW REQUIRES:

- 1—All stone walls must be properly bonded.
- 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass.
- 3d—All buildings over two stories or above 25 feet in height, except dwellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted.
- 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first, and on dwellings more than four stories in height, occupied by three or more families above the first floor, and on office buildings, hotels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows:

BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE.

BRACKETS must not be less than $\frac{1}{2}$ x $1\frac{1}{2}$ inches wrought iron, placed edgewise, or $1\frac{1}{2}$ inch angle iron $\frac{1}{4}$ inch thick, well braced, and not more than three feet apart, and the braces to brackets must be not less than $\frac{3}{4}$ inch square wrought iron, and must extend two-thirds of the width of the respective brackets or balconies. In all cases the brackets must go through the wall, and be turned down three inches.

BRACKETS ON NEW BUILDINGS must be set as the walls are being built. When brackets are to be put on old houses, the part going through the wall shall not be less than one inch diameter, with screw nuts and washers not less than five inches square and $\frac{1}{2}$ inch thick.

TOP RAILS.—The top rail of balcony must be $1\frac{1}{4}$ inch x $\frac{1}{2}$ inch wrought iron or $1\frac{1}{2}$ inch angle iron $\frac{1}{4}$ inch thick, and in all cases must go through the walls, and be secured by nuts and 4 inch square washers, at least $\frac{3}{8}$ inch thick, and no top rail shall be connected at angles by the use of cast iron.

BOTTOM RAILS.—Bottom rails must be $1\frac{1}{4}$ inch x $\frac{3}{8}$ inch wrought iron or $1\frac{1}{2}$ inch angle iron $\frac{1}{4}$ inch thick, well leaded into the wall. In frame buildings the top rails must go through the studding and be secured on the inside by washers and nuts as above.

FILLING-IN BARS.—The filling-in bars must be not less than $\frac{1}{2}$ inch round or square wrought iron, placed not more than 6 inches from centres, and well riveted to the top and bottom rails.

STAIRS.—The stairs in all cases must be not less than 18 inches wide, and constructed of $\frac{1}{4}$ x $3\frac{1}{2}$ inch wrought iron sides or strings. Steps may be of cast iron of the same width of strings, or $\frac{3}{4}$ inch round iron, double rungs, and well riveted to the strings. The stairs must be secured to a bracket on top and rest on and be secured to a bracket or extra cross bar at the bottom. All stairs must have a $\frac{3}{4}$ inch hand rail of wrought iron, well braced.

FLOORS.—The flooring of balconies must be of wrought iron $1\frac{1}{2}$ x $\frac{3}{8}$ inch slats placed not over $1\frac{1}{4}$ inches apart, and secured to iron battens $1\frac{1}{2}$ x $\frac{3}{4}$ inch, not over three feet apart and riveted at the intersection. The openings for stairways in all balconies shall not be less than 20 inches wide and 30 inches long, and have no covers.

DROP LADDERS.—Drop ladders from lower balconies where required shall not be less than 11 inches wide, and shall be made of $1\frac{1}{2}$ x $\frac{3}{4}$ inch sides and $\frac{5}{8}$ inch rungs of wrought iron. In no case shall a drop ladder be more than 12 feet in length. In no case shall the ends of balconies extend more than nine inches over the brackets.

SCUTTLE LADDERS.—Ladders to scuttles shall be constructed in all cases the same as the stairs or step-ladders from balconies of fire escapes.

THE HEIGHT OF RAILING around balconies shall not be less than two feet nine inches.

No Fire Escape will be approved by this Bureau if not in accordance with above specifications.

- 5th—All walls must be coped with stone or terra cotta. If coped with stone, the stone must not be less than $2\frac{1}{2}$ inches thick; and if with terra cotta, the terra cotta must be made with proper lap joints.
- 6th—Roofs must be covered with fire-proof material.
- 7th—All cornices must be fire-proof.
- 8th—All FURNACE FLUES OF DWELLING HOUSES shall have at least eight inch walls on each side. No furnace flues shall be of less size than eight inches square, or four inches wide and sixteen inches long, inside measure. If preferred, the furnace flues may be made of cast iron or fire-clay pipe of proper size built in the walls, with an air space of not less than one inch between said pipes, and four inches of brick wall on the outside.
All flues not built for furnace or boiler flues must be altered to conform to the above requirements before they are used as such.
- 9th—No iron beam, lintel, or girder, intended to span an opening over eight feet, intended to support a wall, shall be used for that purpose, until tested and approved as provided by law.

Department of Buildings of The City of New York.

3

B 288
THOMAS J. BRADY,
 President of the Board of Buildings and
 Commissioner of Buildings for the Bor-
 oughs of Manhattan and The Bronx.
 Office, No. 220 Fourth Avenue, S. W. cor. 18th Street,
 Borough of Manhattan.

JOHN GUILFOYLE,
 Commissioner of Buildings for
 the Borough of Brooklyn.
 Office, Borough Hall, Borough of Brooklyn.

DANIEL CAMPBELL,
 Commissioner of Buildings for the Bor-
 oughs of Queens and Richmond.
 Office, Richmond Building, New Brighton, Staten Island,
 Borough of Richmond.
 Branch Office, Town Hall, Jamaica, Long Island,
 Borough of Queens.

Plan No. 2562

RECEIVED DEC 11 1900

APPLICATION TO ALTER, REPAIR, ETC.

Application is hereby made to the Commissioner of Buildings of The City of New York, for the Borough of Manhattan & The Bronx for the approval of the detailed statement of the specifications and plans herewith submitted, for the alteration or repair of the building herein described. All provisions of the Building Code shall be complied with in the alteration or repair of said building, whether specified herein or not.

(Sign here) Fred. Gehling

THE CITY OF NEW YORK,
 BOROUGH OF Manhattan December 11th 1900

LOCATION AND DESCRIPTION OF PRESENT BUILDING.

- State how many buildings to be altered 1
- What is the exact location thereof? (State on what street or avenue; the side thereof, the number of feet from the nearest street or avenue, and the name thereof) 638-6th Street, south side 200 feet west of Ave C.
- How was the building occupied? Synagogue
How is the building to be occupied? Synagogue and Baths in Basement
- Is the building on front or rear of lot? front Is there any other building on the lot? no
If so, state size: _____ feet front; _____ feet rear; _____ feet deep; _____ stories high. How occupied? _____
- Size of lot? 22 feet front; 22 feet rear; 95 feet deep.
- Size of building which it is proposed to alter or repair? 22 feet front; 22 feet rear; 90 feet deep. Number of stories in height? 3 & 2 Height from curb level to highest point? 35 ft on front and 26 ft on rear.
- Depth of foundation walls below curb level? 10 Material of foundation walls? Brick
Thickness of foundation walls? front 16 inches; rear 16 inches; side 16 inches; party 16 inches.
- Material of upper walls? Brick & Iron If ashlar, give kind and thickness _____
- Thickness of upper walls:
Basement: front _____ inches; rear _____ inches; side _____ inches; party _____ inches.
1st story: " Iron " " 12 " " 12 " " 12 "
2d story: " Iron " " 12 " " 12 " " 12 "
3d story: " Mansard " " 12 " " 12 " " 12 "
4th story: " _____ " " _____ " " _____ "
5th story: " _____ " " _____ " " _____ "
6th story: " _____ " " _____ " " _____ "
- Is roof flat, peak or mansard? Mansard on front, flat on rear

12/11

If the Front, Rear or Side Walls, or any portion thereof, are to be taken out and rebuilt, give definite particulars, and state in what manner :

45. _____

If altered Internally, give definite particulars, and state how the building will be occupied :

46. *The Gallery on 2nd Story will be extended, 5' 4" wide on each side, supported by 4-10" steel beams 76 lbs per yard, with wrought iron hanger 1 1/4 diameter. C.I. Templates 12" x 16" x 1". The floor beams will be of spruce 3" x 10" x 16" bits. Centres. Header double. Bathrooms & Plunge will be erected in Basement and a new Entrance will be made leading from Sidewalk to Basement and no further alterations will be made.*

47. How much will the alteration cost? *\$ 15.00⁰⁰*

If the Building is to be occupied as a Flat, Apartment, Tenement or Lodging House, give the following particulars :

- 48. State what per centum of lot is to be occupied?
- 49. How many feet open space will remain between building and rear line of lot?
- 50. Is any part of building to be used as a store or for any other business purpose, if so, state for what?

	Cellar	Basement	1st Floor	2d Floor	3d Floor	4th Floor	5th Floor	6th Floor
51. How many families will occupy each? - -								
52. Height of ceilings? - - - -								
53. Number of living rooms opening on shafts and courts?								
54. Number of living rooms opening on street and yard?								

- 55. How basement to be occupied? Height of basement ceiling above sidewalk?
- How lighted and ventilated?
- How made water-tight?
- 56. Will cellar or basement ceiling be plastered? How?

- 57. How will cellar stairs be enclosed?
- 58. How cellar to be occupied? Height of cellar ceiling above sidewalk?
- How lighted and ventilated?
- How made water-tight?
- 59. Give number of light and vent shafts
- State materials to be used in their construction
- 60. Will shafts be open or covered with louvre skylights full size of shafts?
- Size of each shaft?
- 61. Dimensions of windows for living rooms?
- 62. What doors will have fan lights?
- Dimensions of same?
- 63. Of what materials will hall partitions be constructed?
- 64. Of what materials will hall floors be constructed?
- 65. How will hall ceilings and soffits of stairs be plastered?
- 66. How will halls be lighted and ventilated?
- 67. Of what material will stairways be constructed?
- 68. If any other building on lot, give size: front; rear; deep; stories high; how occupied; on front or rear of lot; material
- How much space between it and proposed building?
- 69. How will floors and sides of water closets to the height of 16 inches be made waterproof?
- 70. Number and location of water closets: Cellar; 1st floor; 2d floor; 3d floor; 4th floor; 5th floor; 6th floor
- 71. Total area of shafts over 25 square feet? Of courts?

Owner, *Congregation Ahawath Yeshurun* address, *Premises*
President Marcus Weiss — *179 Ave B.*
 Architect, *Fred. Ebeling* " *97-7th Street.*
 Superintendent, *The President* " _____
 Mason, _____ " _____
 Carpenter, _____ " _____

OWNER: CONGREGATION AHAWATH YESHW'RUN
ARCHITECT: FREDERICK EBELING

Department of Buildings of The City of New York.

THOMAS J. BRADY,
 President of the Board of Buildings and
 Commissioner of Buildings for the Bor-
 oughs of Manhattan and The Bronx.
 Office, No. 220 Fourth Avenue, S. W. cor. 18th Street,
 Borough of Manhattan.

JOHN GUILFOYLE,
 Commissioner of Buildings for
 the Borough of Brooklyn.
 Office, Borough Hall, Borough of Brooklyn.

DANIEL CAMPBELL,
 Commissioner of Buildings for the Bor-
 oughs of Queens and Richmond.
 Office, Richmond Building, New Brighton, Staten Island,
 Borough of Richmond.
 Branch Office, Town Hall, Jamaica, Long Island,
 Borough of Queens.

Borough of *Manhattan*

The City of New York, *March 12th* 190*1*

Amendment to Application No. 2562 *Alt. B, 1900*

Location *638 - 6th Street (Synagogue)*

*We intend to built 2 new Stairs leading
 from 1st Story to 2nd Story. Headers and
 Trimmers will be double and hung
 in Bridle Irons according to law. The
 proposed plumbing in Basement,
 Plunge and Bath tubs, we herewith
 withdraw and amended plans are filed
 within. There will be no Stairs put
 up leading from Side walk to Basement
 as shown on approved plans.*

*Window Openings will be cut in Sidewalls, one in
 first Story on easterly side and one on each side of 2nd
 Story (gallery) three all together, size 3' 0" x 5' 6" in iron
 daylight. Plank partitions will be built around
 new Water closets in 3rd Story up to ceiling and a galv.
 Iron Vent Shaft will be put on roof with Louvers
 complete all as shown on plans.*

No further Alterations will be made.

Fred. Ebeling

3/18-01

3/16 1901

*to
 construction
 March 16th 1901
 (McBurt)*

OK. Mar. 15-01

Markus Haerdt

Applicant must indicate the Building Line or Lines clearly and distinctly on the Drawings.

B388
L28

Office of the Borough President of the Borough of Manhattan,
In The City of New York.

4

THE BUREAU OF BUILDINGS FOR THE BOROUGH OF MANHATTAN,
Office, No. 220 FOURTH AVENUE
S. W. Corner 18th Street.

OFFICE OF THE SUPERINTENDENT OF BUILDINGS
BUREAU OF BUILDINGS
OFFICE OF THE BOROUGH OF MANHATTAN
AUG 28 1906

Plan No. 2371

APPLICATION TO ALTER, REPAIR, ETC.

Application is hereby made to the Superintendent of Buildings of The City of New York, for the Borough of Manhattan, for the approval of the detailed statement of the specifications and plans herewith submitted, for the alteration or repairs of the building herein described. All provisions of the Law shall be complied with in the alteration or repair of said building, whether specified herein or not.

(Sign here) Fred Ebeling

The City of New York, Borough of Manhattan, August 27th 1906.

LOCATION AND DESCRIPTION OF PRESENT BUILDING.

1. State how many buildings to be altered 1
2. What is the exact location thereof? (State on what street or avenue, the side thereof, the number of feet from the nearest street or avenue, and the name thereof) 638 Sixth St, South Side, 200 ft. West of Ave C.
3. How was the building occupied? Synagogue
How is the building to be occupied? same, synagogue
4. Is the building on front or rear of lot? front Is there any other building erected on lot or permit granted for one? no Size _____ x _____ ; height _____ How occupied? _____ Give distance between same and proposed building _____ feet.
5. Size of lot? 21 feet front; 21 feet rear; 97 feet deep.
6. Size of building which it is proposed to alter or repair? _____ feet front; _____ feet rear; 92 feet deep. Number of stories in height? 3+2 Height from curb level to highest point? 31'6" x 22'0"
7. Depth of foundation walls below curb level? 10 ft Material of foundation walls? brick Thickness of foundation walls? front 16 inches rear 16 inches; side 16 inches; party 16 inches.
8. Material of upper walls? brick If ashlar, give kind and thickness _____
9. Thickness of upper walls:
Basement: front _____ inches; rear _____ inches; side _____ inches; party _____ inches.
1st story: " iron " " 12 " " 12 " " 12 "
2d story: " iron " " 12 " " 12 " " 12 "
3d story: " mansard " " 12 " " 12 " " 12 "
4th story: " _____ " " _____ " " _____ " " _____ "
5th story: " _____ " " _____ " " _____ " " _____ "
6th story: " _____ " " _____ " " _____ " " _____ "
10. Is roof flat, peak or mansard? mansard on front, flat on rear.

No Plumbing

If the Front, Rear or Side Walls, or any portion thereof, are to be taken out and rebuilt, give definite particulars, and state in what manner :

47. Present mansard roof will be removed & a flat roof substituted. Iron front wall will be taken down, to the top of cellar wall, and a new 12" brick wall resting on 2-6" steel beams 12 lbs. per ft., set on c. l. templates 16" x 12" x 1" thick, as shown on section. New 12" brick wall on rear of 3rd story will be built, & rest on 2-12" steel beams 25 lbs. per ft. C. l. templates 16" x 12" x 1" thick. Present windows in rear part shall be made about 3 ft. higher. Skylight will be enlarged as shown, made of Galv. iron & wire glass. Headers & trimmers will be double. All parts of raised brick walls will be laid in cement mortar.

If altered Internally, give definite particulars, and state how the building will be occupied :

48. New stairs will be built in front part of building leading from 2nd to 3rd story, connecting to present stairs leading to street. Present steel beams and hangers will be raised and hangers will be made longer. Seating capacity will not be more than 200 people. Some plank partitions in 3rd story will be removed, as shown by dotted lines. Scuttle & scuttle ladder will be put back again.

49. How much will the alteration cost? \$7,000.00

If the Building is to be occupied as a Flat, Apartment or Lodging House, give the following particulars :

50. Is any part of building to be used as a store or for any other business purpose, if so, state for what?

	Cellar	Base-ment	1st Floor	2d Floor	3d Floor	4th Floor	5th Floor	6th Floor
51. How many families will occupy each?								
52. Height of ceilings?								

53. How basement to be occupied? _____
 How made water-tight? _____
54. Will cellar or basement ceiling be plastered? _____ How? _____
55. How will cellar stairs be enclosed? _____
56. How will cellar be occupied? _____
 How made water-tight? _____
57. Will shafts be opened or covered with louvre skylights full size of shafts? _____

Size of each shaft? _____

Dimensions of windows for living rooms? _____

59. Of what materials will hall partitions be constructed? _____

60. Of what materials will hall floors be constructed? _____

61. How will hall ceilings and soffits of stairs be plastered? _____

62. Of what material will stairways be constructed? _____

Give sizes of stair well holes? _____

63. If any other building on lot, give size; front _____; rear _____; deep _____; stories high _____; how occupied _____; on front or rear of lot _____; material _____

How much space between it and proposed building? _____

64. How will floors and sides of water closets to the height of 16 inches be made waterproof? _____

65. Number and location of water closets: Cellar _____; 1st floor _____; 2d floor _____; 3d floor _____; 4th floor _____; 5th floor _____; 6th floor _____;

66. This building will safely sustain per superficial foot upon the first floor 120 lbs.; upon 2d floor 120 lbs.; upon 3d floor 120 lbs.; upon 4th floor _____ lbs.; upon 5th floor _____ lbs.; upon 6th floor _____ lbs.; upon 7th floor _____ lbs.; upon 8th floor _____ lbs.

CONGREGATION AHAWATH TESCHUREM

Owner, Cong. Ahawath Teschurem. Address, 638 Sixth St.

Architect, Fred Ebeling. " 420 East Ninth St.

Superintendent, M. Weiss, President. " 358-60 East Eighth St.

Mason, _____ " _____

Carpenter, _____ " _____

President of the Borough of Manhattan,
In The City of New York.

THE BUREAU OF BUILDINGS FOR THE BOROUGH OF MANHATTAN

Office, No. 220 FOURTH AVENUE,
S. W. Corner 18th Street.

RECEIVED
FOR THE BUREAU OF BUILDINGS
1906

The City of New York, Sept. 6th 1906. 190

Amendment to Plan No. 2371 Alt. 1906.

Location:-638 Sixth Street.

1. Means of egress: Two windows in rear of first story will be formed into sash doors, and two doors will be cut in fence. Doors leading to an open yard. All doors will be opened to the outside. All as shown on corrected first story plan.

2:- Hangers will be properly secured to supports, as shown on corrected section.

Respectfully submitted

Fred. Ebeling.

I have thoroughly examined the drawings and also the law as to construction
Dated Sept. 12, 1906

A. Schwartz.
C.H. Sept 14, 1906
J. P. Smith

The City of New York
Sept 6 1906
I hereby certify that the within specified specifications and copy of the plans submitted to the Bureau of Buildings for the Borough of Manhattan are in accordance with the laws of the City of New York.

Edw. J. Connelley.
Superintendent of Buildings

9/14/06

Office of the Borough President, The Borough of Manhattan
In The City of New York.

THE BUREAU OF BUILDINGS FOR THE BOROUGH OF MANHATTAN,
Office, No. 220 FOURTH AVENUE,
S. W. Corner 18th Street.

(Rep. No. 4217/06.) The City of New York, Nov. 30th 1906. 190

Amendment to plan No. 2371 Alt. 1906.

Location: 638 Sixth St., south side, 200 ft. west of Ave. C.

Recesses are put in 12" brick wall of upper story on easterly side, 8" deep with 6" steel beam on top of each. One window opening is cut in rear part of 2nd story westerly wall. Two windows in 2nd story, one on easterly wall and one on westerly wall will be shifted as shown on corrected plans.

Respectfully submitted

Fred. Ebeling.

construction
Dec 1-1906
A. Schwartz.
H. Lee 3. 11
J. Roth

12/3 6

Edw. S. Murphy

12/7 1906