

B374

Original

Department of Buildings,

IN THE CITY OF NEW YORK.

L1

OFFICE OF THE SUPERINTENDENT, No. 2 FOURTH AVENUE.

2

DETAILED STATEMENT OF SPECIFICATIONS FOR THE ERECTION OF BUILDINGS.

3

11th Ward

621

June 17/92

1

1. State how many buildings to be erected, four
2. How many of them for dwelling, state the number of families, one for dwelling three for other use on first story and dwellings above eight families in each and ten in the other first name
3. What is the Street or Avenue, and the number thereof, three crossing at the N.E.C. on Avenue
4. On which side, North, South, East, or West, of 4th Street and Avenue C and
5. How many feet from the nearest street, one to be situated 65 feet from the
6. Whether North, South, East, or West of said street, N.E.C. of 4th Street & Avenue C on 4th Street
7. What is the nearest street, _____
8. Size of lot, No. of feet front, 24 ; No. of feet rear, 24 ; No. of feet deep, 65 feet on Avenue 72 - 4th Street
9. Size of building, No. of feet front, 24 ; No. of feet rear, 24 ; No. of feet deep, 52 feet on Avenue 60'0" on others
 No. of stories in height, five ; No. of feet in height, from curb level to highest point, 55 feet
10. What will each building cost (exclusive of the lot), \$ 12,000
11. What will be the depth of foundation walls, from curb level or surface of ground, 10 feet.
12. Will foundation be laid on earth, rock, timber, or piles, solid ground
13. What will be the base, stone or concrete, stone ; if base stones, give size, and how laid, 3x4 feet across & in cement ; if concrete, give thickness, _____
14. What will be the sizes of piers, under iron columns 7x7 feet 20x24"
15. What will be the sizes of the base of piers, _____ 4x4 feet
16. What will be the thickness of foundation walls, 24 inches and of what materials constructed, stone laid in cement
17. What will be the thickness of upper walls in 1st story, 12 inches ; 2d story, 12 inches ; 3d story, 12 inches ; from thence to top, 12 inches ; and of what materials to be constructed, hard brick laid in mortar of cheap sand & lime
18. Whether Independent or Party walls ; if Party walls, give thickness thereof, in part independent inches.
19. With what material walls to be coped, 3x11" blue stone to be cut out under line of beams to form 16" thickness between beams
20. What will be the materials of front, stone ; if of stone, what kind, brown ; give thickness of front ashlar, 4 , and thickness of backing thereof, 12"
21. Will the roof be Flat, Peak, or Mansard, flat
22. What will be the materials of roofing, tin
23. What will be the means of access to roof, Bulkheads & Stairs
24. What will be the materials of cornices, galvanized iron

25. If there are to be skylights in roof, give size of same, and of what materials constructed, 3 x 3 feet
of wood

26. Is the building to be provided with iron shutters or blinds, _____

27. Give size and material of floorbeams, 1st tier, spruce 3 x 10; 2d tier, spruce

3 x 9; 3d tier, spruce 3 x 9; 4th tier, spruce 3 x 9; 5th tier,

spruce 3 x 9; 6th tier, _____; roof tier, spruce

3 x 8. State distance from centres on 1st tier, 16 inches; 2d tier, 16 inches; 3d tier,

16 inches; 4th tier, 16 inches; 5th tier, 16 inches; 6th tier, _____ inches;

roof tier, 22 inches.

28. If floors are to be supported by columns and girders, give the following information: Size and material of

6 x 8 girders under first tier of beams & second tier on corner house
girders on 1st floor, _____; 2d floor, _____; 3d floor,

supported by 6 x 6 chestnut posts & iron columns
_____; 4th floor, _____; 5th floor,

_____; 6th or roof girders, _____ Size and material of columns on 1st floor,

_____; 2d floor, _____; 3d floor,

_____; 4th floor, _____; 5th floor, _____; 6th or roof

columns, _____.

29. What will be the distance of wooden girders, beams, or timbers, from all flues, _____

30. If any hoistways, state how protected, _____

31. Will headers and trimmers be hung in stirrup-irons, _____

32. State if any hot air, steam, or other furnaces, _____

33. If the front, rear, or side walls are to be supported in whole or in part, by iron girders or lintels, give de-

finite particulars, front of Mason house to be supported on first

story by 12 x 16" on party loads 8 x 16" on door opening 8" round

at corner & two 6" round iron columns between and

iron lintel course all in strict accord with the law

34. If girders are to be supported by brick piers and columns, state the size of piers and columns, _____

35. Will a Fire-Escape be provided, yes

IF THE BUILDING IS TO BE OCCUPIED AS A TENEMENT HOUSE, GIVE THE FOLLOWING PARTICULARS:

36. State how many families are to occupy each floor, and the whole number in the house; also, if any part is to

be used as a Store or for other business purposes, state the fact, Stores on Mason

two families on each floor above, eight in all and

two families on Street house

37. What will be the heights of ceilings on 1st story, 11' 6" feet; 2d story, 9' 6" feet; 3d story,

9' 6" feet; 4th story, 9' 0" feet; 5th story, 9' 0" feet; 6th story, _____ feet.

38. State if a fire-escape is to be provided, and what kind, Balkony fire escapes and

step ladders on each story of iron according to law

39. If any wood houses, state where located, and of what materials, in Cellars of wood
40. How is the building to be ventilated, through ventilation holes, four lights head lights & C. masonry chimneys in skylight
41. How are the hall partitions to be constructed and of what materials? of wood, to be set out with brick up to ceiling on first story on Ocean houses.
42. How are the stairways to be constructed and of what materials? of wood. Cellar stairs to be inclosed with 3" brickwork to ceiling & iron doors.
43. How are the floors and ceilings of the cellar and first story to be constructed? first and second tier of beams bedcapped on Ocean houses & first tier on Street houses
44. If there is any building already erected on the front or rear of the lot, give size of the same, state how occupied, (if for a tenement, state by how many families,) and how many feet of space there will be between the building proposed to be erected, and the one already erected, no

45. Will all materials and workmanship be in accordance with the requirements of the law, yes
46. If any walls already built are to be used as party-walls, fill up the application below. no

APPLICATION TO USE PARTY-WALLS.

The undersigned gives notice that _____ intends to use the _____ wall of building _____ as party-wall in the erection of the building described above, and respectfully requests that the same be examined and a permit granted therefor. The foundation wall _____ built of _____, _____ inches thick; the upper wall _____ built of _____, _____ inches thick, _____ feet in height, _____ feet deep, _____

(SIGN HERE,)

Owner E. Y. Low Address _____

Architect W. S. Barnes Address No. 919 Third Avenue

Mason Mr. Deenos Address _____

Carpenter Breen & Mason Address _____

39. If any wood houses, state where located, and of what materials, in cellars of wood
40. How is the building to be ventilated, through ventilation holes, fourlights head lights & c. masonry chimneys in Registry
41. How are the hall partitions to be constructed and of what materials? of wood, to be set out with brick up to ceiling on first story on Ocean houses
42. How are the stairways to be constructed and of what materials? of wood. Cellar stairs to be inclosed with 3" brickwork to ceiling & iron doors
43. How are the floors and ceilings of the cellar and first story to be constructed? first and second tier of beams to be capped on Ocean houses & first tier on Street houses
44. If there is any building already erected on the front or rear of the lot, give size of the same, state how occupied, (if for a tenement, state by how many families,) and how many feet of space there will be between the building proposed to be erected, and the one already erected, no
45. Will all materials and workmanship be in accordance with the requirements of the law, yes
46. If any walls already built are to be used as party-walls, fill up the application below. no

APPLICATION TO USE PARTY-WALLS.

The undersigned gives notice that.....intends to use the.....wall of building
as party-wall in the erection of the building described
 above, and respectfully requests that the same be examined and a permit granted therefor. The foundation wall
built of.....,.....inches thick; the upper wall.....built of.....,
 inches thick,..... feet in height,..... feet deep,.....

(SIGN HERE,)

Owner E. V. Low Address

Architect Fr. J. Barnes Address No 919 Third Ocean

Mason Mr. Deane Address

Carpenter Breen & Mason Address

Original

B374
L2

APPLICATION TO ALTER, REPAIR, ETC.

2

Application is hereby made to alter as per subjoined detailed statement of specification for Alterations, Additions or Repairs to buildings already erected, and I herewith submit Plans and Drawings of such proposed alterations; and I do hereby agree that the provisions of the Building Law will be complied with, whether the same are specified herein or not.

(Sign here) Rosa Hirschman
Per H. Baylis archt.

NEW YORK, Aug. 12 1890

- 1. State how many buildings to be altered. One
- 2. What is the street or avenue and the number thereof? Give diagram of property. 56 Ave. C. East side of Street 25.0' W. of Hk. St.
- 3. How much will the alteration cost? \$ 3000.

GIVE THE FOLLOWING INFORMATION AS TO THE PRESENT BUILDING:

- 1. Size of lot on which it is located, No. of feet front, 24; feet rear, 24; feet deep, 65
- 2. Size of building, No. of feet front, 24; feet rear, 24; feet deep, 57 No. of stories in height, 5; No of feet in height from curb level to highest point of beams, 56
- 3. Material of building, Brick; material of front, Brick & Stone
- 4. Whether roof is peak, flat, or mansard, Flat
- 5. Depth of foundation walls 8.0 feet; thickness of foundation walls, 20; materials of foundation walls, Stone
- 6. Thickness of upper walls, 12 inches. Material of upper walls, Brick
- 7. Whether independent or party walls, Party
- 8. How the building is or was occupied, Stores on 1st Story. Dwelling above

IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION:

- 1. How many stories will the building be when raised?
- 2. How high will the building be when raised?
- 3. Will the roof be flat, peak, or mansard?
- 4. What will be the thickness of wall of additional stories? story, inches; story, inches.
- 5. Give size and material of floor beams of additional stories; 1st tier, x; 2d tier, x. Distance from centres on tier, inches; tier, inches.
- 6. How will the building be occupied?

IF TO BE EXTENDED ON ANY SIDE, GIVE THE FOLLOWING INFORMATION.

- ... inches, from sill to top, inches:
 and of what materials to be constructed,
7. State whether independent or party-walls. If party-walls give thickness thereof.....
 8. With what material will walls be coped?
 9. What will be the materials of front?..... If of stone, what kind?
 Give thickness of front ashlar..... (Give thickness of backing.....)
 10. Will the roof be flat, peaked or mansard?.....
 11. What will be the materials of roofing?.....
 12. Give size and material of floor beams, 1st tier, x; 2d tier,
 x; 3d tier, x; 4th tier, x
 5th tier, x; 6th tier, x; 7th tier,
 x; roof tier, x State distance from centres on 1st tier,
 inches; 2d tier, inches; 3d tier, inches; 4th tier, inches; 5th tier,
 inches; 6th tier, inches; 7th tier, inches; roof tier, inches
 13. If floors are to be supported by columns and girders, give the following information: Size and material
 of girders under 1st floor, x under each of the upper floors,
 Size and material of columns under first floor,
 under each of the upper floors,
 14. If the front, rear or side walls are to be supported, in whole or in part, by iron girders or lintels, give
 definite particulars,
 15. If girders are to be supported by brick piers and columns, state the size of piers and columns.

 16. How will the extension be connected with present or main building?.....
 17. How will the extension be occupied? If for dwelling purposes, state how many families are to occupy
 each floor.
 18. State who will superintend the alterations.....

IF ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED:

It is proposed to set a new girder under 1st tier of beams 8" x 10" of Yellow Pine supported by 7 locust Posts also to cut an opening in side wall of Basement, wall above opening to be supported by two 18" thick 200 lb. rolled iron beams. Door of opening made of wrought iron - or used for storage.

IF THE FRONT, REAR, OR SIDE WALLS, OR ANY PORTION THEREOF, ARE TO BE TAKEN OUT AND REBUILT, GIVE DEFINITE PARTICULARS, AND STATE IN WHAT MANNER:

It is proposed to build new area walls at front and rear 20" thick of Stone, and set new steps from sidewalk to Basement. Area to be covered with perforated iron. Also to cut new window openings in rear wall of Basement with new brick jambs

Owner Rosa Herschman Address 163 East 63rd St.
 Architect Hauklin Baylies Address 51 & 52 Bible House
 Mason Address
 Carpenter Address

REPORT UPON APPLICATION.

BUREAU OF INSPECTION OF BUILDINGS,
 NEW YORK, August 15th 1890

To the Superintendent of Buildings:

I respectfully report that I have thoroughly examined and measured the building, walls, etc., named in the foregoing application, and found the foundation wall to be built of Stone 20 inches thick, 8 feet below curb, the upper wall built of Brick 12 inches thick, 50 feet deep. 55 feet in height, and that the mortar in said wall is hard and good, and that all the walls are Good in good and safe condition.

What is the nature of the ground? Good

What kind of sand was used in the mortar? Sharp

How is or was the building occupied? Store + Dwelling

(The Inspector must here state what defects, if any, are in the walls, beams or other part of the building.)
 The " " state the thickness of each wall in each and every story.)

James H. Kelly Inspector.

THE BUILDING LAW REQUIRES:

- 1st—All stone walls must be properly bonded.
- 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass.
- 3d—All buildings over two stories or above 25 feet in height, *except dwellings, school houses, and churches,* on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted.
- 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first, and on dwellings more than four stories in height, occupied by three or more families above the first floor, and on office buildings, hotels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows:

BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE.

BRACKETS must not be less than $\frac{1}{2} \times 1\frac{1}{2}$ inches wrought iron, placed edgewise, or $1\frac{1}{2}$ inch angle iron $\frac{1}{2}$ inch thick, well braced, and not more than three feet apart, and the braces or brackets must be not less than $\frac{3}{4}$ inch square wrought iron, and must extend two-thirds of the width of the respective brackets or balconies. In all cases the brackets must go through the wall, and be turned down three inches.

BRACKETS ON NEW BUILDINGS must be set as the walls are being built. When brackets are to be put on old houses, the part going through the wall shall not be less than one inch diameter, with screw nuts and washers not less than five inches square and $\frac{1}{2}$ inch thick.

TOP RAILS.—The top rail of balcony must be $1\frac{1}{2}$ inch \times $\frac{1}{2}$ inch wrought iron or $1\frac{1}{2}$ inch angle iron $\frac{1}{2}$ inch thick, and in all cases must go through the walls, and be secured by nuts and 4 inch square washers, at least $\frac{3}{8}$ inch thick, and no top rail shall be connected at angles by the use of cast iron.

BOTTOM RAILS.—Bottom rails must be $1\frac{1}{2}$ inch \times $\frac{3}{8}$ inch wrought iron or $1\frac{1}{2}$ inch angle iron $\frac{1}{2}$ inch thick, well leaded into the wall. In frame buildings the top rails must go through the studding and be secured on the inside by washers and nuts as above.

FILLING-IN BARS.—The filling-in bars must be not less than $\frac{1}{2}$ inch round or square wrought iron, placed not more than 6 inches from centres, and well riveted to the top and bottom rails.

STAIRS.—The stairs in all cases must be not less than 18 inches wide, and constructed of $\frac{1}{2} \times 3\frac{1}{2}$ inch wrought iron sides or strings. Steps may be of cast iron of the same width of strings, or $\frac{5}{8}$ inch round iron, double rungs, and well riveted to the strings. The stairs must be secured to a bracket on top and rest on and be secured to a bracket or extra cross bar at the bottom. All stairs must have a $\frac{3}{4}$ inch hand rail of wrought iron, well braced.

FLOORS.—The flooring of balconies must be of wrought iron $1\frac{1}{2} \times \frac{3}{4}$ inch slats placed not over $1\frac{1}{2}$ inches apart, and secured to iron battens $1\frac{1}{2} \times \frac{3}{4}$ inch, not over three feet apart and riveted at the intersection. The openings for stairways in all balconies shall not be less than 20 inches wide and 35 inches long, and have no covers.

DROP LADDERS.—Drop ladders from lower balconies where required shall not be less than 14 inches wide, and shall be made of $1\frac{1}{2} \times \frac{3}{8}$ inch sides and $\frac{5}{8}$ inch rungs of wrought iron. In no case shall a drop ladder be more than 12 feet in length. In no case shall the ends of balconies extend more than nine inches over the brackets.

SCUTTLE LADDERS.—Ladders to scuttles shall be constructed in all cases the same as the stairs or step-ladders from balconies of fire escapes.

THE HEIGHT OF RAILING around balconies shall not be less than two feet nine inches.

No Fire Escape will be approved by this Bureau if not in accordance with above specifications.

- 5th—All walls must be coped with stone or terra cotta. If coped with stone, the stone must not be less than $2\frac{1}{2}$ inches thick; and if with terra cotta, the terra cotta must be made with proper lap joints.
- 6th—Roofs must be covered with fire-proof material.
- 7th—All cornices must be fire-proof.
- 8th—All FURNACE FLUES OF DWELLING HOUSES shall have at least eight inch walls on each side. No furnace flues shall be of less size than eight inches square, or four inches wide and sixteen inches long, inside measure. If preferred, the furnace flues may be made of cast iron or fire-clay pipe of proper size built in the walls, with an air space of not less than one inch between said pipes, and four inches of brick wall on the outside.
 All flues not built for furnace or boiler flues must be altered to conform to the above requirements before they are used as such.
- 9th—No iron beam, lintel, or girder, intended to span an opening over eight feet, intended to support a wall, shall be used for that purpose, *until tested and approved* as provided by law.

For. of. in. is. n. e.

B374
L 2

Applicant must indicate the Building Line or Lines clearly and distinctly on the Drawings.

Office of the Borough President of the Borough of Manhattan,
In The City of New York.

3

THE BUREAU OF BUILDINGS FOR THE BOROUGH OF MANHATTAN,
Office, No. 220 FOURTH AVENUE,
S. W. Corner 18th Street.

Plan No. 2060

APPLICATION TO ALTER, REPAIR, ETC.

Application is hereby made to the Superintendent of Buildings of The City of New York, for the Borough of Manhattan, for the approval of the detailed statement of the specifications and plans herewith submitted for the alteration or repairs of the building herein described. All provisions of the Law shall be complied with in the alteration or repair of said building, whether specified herein or not.

(Sign here) Ignatz J. Rosenberg

THE CITY OF NEW YORK, BOROUGH OF MANHATTAN, Oct. 1909

LOCATION AND DESCRIPTION OF PRESENT BUILDING.

1. State how many buildings to be altered. One
2. What is the exact location thereof? (State on what street or avenue, the side thereof, the number of feet from the nearest street or avenue, and the name thereof) #56 Ave. C. on the East Side of the Ave. 24'-0" North of East 4th St.
3. How was the building occupied? Tenement
How is the building to be occupied? Tenement
4. Is the building on front or rear of lot? front Is there any other building erected on lot or permit granted for one? — Size — x —; height — How occupied? — Give distance between same and proposed building — feet.
5. Size of lot? 24'-0" feet front; 24'-0" feet rear; 64'-3" feet deep.
6. Size of building which it is proposed to alter or repair? 24'-0" feet front; 24'-0" feet rear; 48'-0" feet deep. Number of stories in height? 5 Height from curb level to highest point? 49'-0"
7. Depth of foundation walls below curb level? 4'-0" Material of foundation walls? Stone Thickness of foundation walls? front 20 inches; rear 20 inches; side 20 inches; party — inches.
8. Material of upper walls? Brick If ashlar, give kind and thickness —
9. Thickness of upper walls:
cellar
~~Basement~~: front 16 inches; rear 16 inches; side 16 inches; party — inches.
1st story: " 12 " " 12 " " 12 "

floors as per plans.

If altered internally, give definite particulars, and state how the building will be occupied :

48. *Present Water Closets in yard removed and new W. Cl. compartments installed in Bld. as per plans. New 3'-0" x 5'-0" Partition Windows set. New Skylight, also present Fire Escapes reconstructed.*
The building to be occupied as a Tenement as at present.

49. How much will the alteration cost? *\$ 1200.⁰⁰*

If the Building is to be occupied as a Flat, Apartment or Lodging House, give the following particulars :

50. Is any part of building to be used as a store or for any other business purpose, if so, state for what?

	Cellar	Basement	1st Floor	2d Floor	3d Floor	4th Floor	5th Floor	6th Floor
51. How many families will occupy each?								
52. Height of ceilings?								

53. How basement to be occupied?
 How made water-tight?
54. Will cellar or basement ceiling be plastered? _____ How? _____
55. How will cellar stairs be enclosed? _____
56. How will cellar be occupied? _____
 How made water-tight? _____
57. Will shafts be opened or covered with louvre skylights full size of shafts? _____
 Size of each shaft? _____

58. Dimensions of water closet windows? _____
 Dimensions of windows for living rooms? _____
59. Of what materials will hall partitions be constructed? _____

60. Of what materials will hall floors be constructed? _____

61. How will hall ceilings and soffits of stairs be plastered? _____
62. Of what material will stairways be constructed? _____
 Give sizes of stair well holes? _____
63. If any other building on lot, give size; front _____; rear _____; deep _____;
 stories high _____; how occupied _____; on front or rear
 of lot _____; material _____.
 How much space between it and proposed building? _____
64. How will floors and sides of water closets to the height of 16 inches be made waterproof? _____

65. Number and location of water closets: Cellar _____; 1st floor _____; 2d floor _____;
 3d floor _____; 4th floor _____; 5th floor _____; 6th floor _____;
66. This building will safely sustain per superficial foot upon the 1st floor _____ lbs.; upon 2d floor
 _____ lbs.; upon 3d floor _____ lbs.; upon 4th floor _____ lbs.; upon 5th floor
 _____ lbs.; upon 6th floor _____ lbs.; upon 7th floor _____ lbs.; upon 8th floor
 _____ lbs.

Owner, Gussie A. Engel Address, 218-270 E. 11th Street

Architect, Synatz J. Rosenberg " 320 B'way

Superintendent, The Architect " _____

Mason, _____ " _____

Carpenter, _____ " _____

ORIGINAL

RECEIVED
MAR 2 1956

DEPARTMENT OF HOUSING AND BUILDINGS

BOROUGH OF MANHATTAN, CITY OF NEW YORK

NOTICE—This application must be typewritten and filed in quadruplicate. All proposed work under this application must be shown on plans and section. All vertical lines of soil, waste, leader and refrigerator pipes should be designated by numbers or letters. A soil or waste line and its attendant vent line may be considered as one stack, and so numbered or lettered. In alterations, NEW WORK ONLY should be specified. When new fixtures are to be connected to present lines, the location and diameter of said lines must be shown on the plan. Minor alterations in connection with work described may be included in this form.

PLUMBING, MECHANICAL EQUIPMENT AND TANK INSTALLATION

B.N. 657 APPLICATION No. 19 56 BLOCK 374 LOT 2

Street No. and LOCATION 56 Ave. C, East side 24'-0 1/2" North of East 4th Street

FEEs REQUIRED FOR B.N. No. 19

Owner Gustav Rosenberg Address 110 East 18th Street, N.Y.

Pres. Vice Pres.

Lessee Address

Pres. Vice Pres.

Architect Sydne Schleman Address 156 East 34th Street, N.Y.

Contractor Address

COMPENSATION INSURANCE has been secured in accordance with the requirements of the Workmen's Compensation Law as follows:

To The Borough Superintendent: City of New York, March 1st, 1956

Application is hereby made on behalf of the owner-lessee for approval of the plans and specifications herewith submitted, and made a part hereof for the erection, alteration or installation of the building therein described,—with the understanding that if no work is performed hereunder within one year from the time of issuance, this approval shall expire by limitation as provided by law, and the applicant agrees to comply with the Building Code and all rules and regulations applicable thereto in effect at this date.

Applicant (Sign Here) Address 156 East 34th St. N. Y.

Examined and Recommended for Approval on 19 56 Examiner

APPROVED 19 Borough Superintendent

Work Included Herein: Plumbing? Yes Sprinkler? Standpipe? Fuel Oil? Gasoline Tank Installation or Fuel Oil (Bulk)?

1. State in detail the work proposed To install one additional toilet on 2nd, 3rd, 4th and 5th floors.

Is this a new or old building? Old

Give character of construction Brick Class: 3

Dimensions: Stories High 5 Feet High 52'-0" Feet Front 24'-0 1/2" Feet Deep 51'-3"

How occupied Stores & Class A Mult. Dwell No. of Families 8

Is application made to remove a violation or order of any Dept.? Yes Give No. Housing Div.

How to be occupied Same

Estimated Cost \$1,500.00

(Any variation in estimated cost shall be filed and recorded as an amendment.)

If fuel burning equipment is to be installed Smoke Control Equipment Form must accompany this application.

Exemptions If exemption from payment of fee is claimed, state clearly the basis of claim

PLUMBING SPECIFICATIONS

Describe special equipment or features: