

ORIGINAL

Plan No. 220

APPLICATION FOR ERECTION OF BUILDINGS.

1

B390
L57

Application is hereby made to the Superintendent of Buildings of the City of New York, for the approval of the detailed statement of the specifications and plans herewith submitted, for the erection of the building herein described. All provisions of the Building Law shall be complied with in the erection of said building, whether specified herein or not.

NEW YORK, March 15th 1898. (Sign here) Charles King

1. State how many buildings to be erected. one
2. How occupied? If for dwelling, state the number of families. 2 families on a floor
3. What is the street or avenue and the number thereof? Give diagram of property. No 197- 4th St.
4. Size of lot. No. of feet front, 20.0; No. of feet rear, 20.0; No. of feet deep, 72.8 x 80.3
5. Size of building. No. of feet front, 20.0; No. of feet rear, 20.0; No. of feet deep, 62.4 x 65.6; No. of stories in height, 5; No. of feet in height from curb level to highest point of roof beams, 59.10
6. What will each building cost exclusive of the lot? \$ 12,000.00
7. What will be the depth of foundation walls from curb level or surface of ground? 10 ft
8. Will foundation be laid on earth, sand, rock, timber or piles? Natural soil
9. What will be the base, stone or concrete? stone If base stones, give size and thickness and how laid. 36 x 36 x 10" thick If concrete, give thickness. —
10. What will be the sizes of piers? 20" x 24"
11. What will be the sizes of the base of piers? stone 10" thick or concrete 18" thick
12. What will be the thickness of foundation walls? 8-12-20 + 24 Of what material constructed? Hard burnt brick + blue stone laid in cement mortar
13. What will be the thickness of upper walls? Basement, — inches; 1st story 8-12 + 16 inches; 2d story, 8 + 12 inches; 3d story, 8 + 12 inches; 4th story, 8 + 12 inches; 5th story, 8 + 12 inches; 6th story, — inches; 7th story, — inches, and from thence to top, 8 inches. Of what materials to be constructed? Hard burnt brick in lime mortar
14. State whether independent or party walls. Independent + party walls
15. With what material will walls be coped? Blue stone
16. What will be the materials of front? Brick If of stone, what kind? Brown stone trim Give thickness of ashler. — Give thickness of backing in each story. —
17. Will the roof be flat, peaked or mansard? Flat
18. What will be the materials of roofing? Tin
19. Give size and materials of floor beams. 1st tier, 8-54 lb beams; 2d tier, 3x10 spruce; 3d tier, 3x10 spruce; 4th tier, 3x10 spruce; 5th tier, 3x10 spruce; 6th tier, —; 7th tier, —; 8th tier, —; roof tier, 3x9 spruce. State distances from centres. 1st tier, 4.10 inches; 2d tier, 16 inches; 3d tier, 16 inches; 4th tier, 16 inches; 5th tier, 16 inches; 6th tier, — inches; 7th tier, — inches; 8th tier, — inches; roof tier, 30 inches.
20. If floors are to be supported by columns and girders, give the following information: Size and material of girders under 1st floor, 8" partition wall under each of the upper floors, — Size and materials of columns under 1st floor, — under each of the upper floors, —
21. This building will safely sustain per superficial foot upon 1st floor 150 lbs.; upon 2d floor 70 lbs.; upon 3d floor 70 lbs.; upon 4th floor 70 lbs.; upon 5th floor 70 lbs.
22. If the front, rear or side walls are to be supported, in whole or in part, by iron girders or lintels, give definite particulars. The front wall in basement to be spanned by 3x10-35 lb. per ft. steel beams and 12" granite blocks.
→ all floors to be lined with fire clay lining blocks.
23. If girders are to be supported by brick piers and columns, state the sizes of piers and columns. → The iron floor beams to have hollow fire clay arch blocks between spans
24. State by whom the construction of the building is to be superintended. owner
Sto A. Apr 17/98

If the Building is to be occupied as an Apartment or Tenement House, give the following particulars.

1. State how many families are to occupy each floor, and the whole number in the house; also, if any part is to be used as a store or for any other business purposes, state the fact, *There will be janitor in basement and 2 families on each floor. The studd partition in main 1st story hall also around all stair halls to be of in with brick and wire lath & plastered 9.6*
2. What will be the heights of ceilings? 1st story, *10.6* feet; 2d story, *9.6* feet; 3d story, *9.6* feet; 4th story, *9.6* feet; 5th story, *9.6* feet; 6th story, _____ feet; 7th story, _____ feet.
3. How are the hall partitions to be constructed and of what materials? _____
4. How many buildings are to be taken down? *one*

Owner *Co. Magidel* Address *58 Suffolk St*
 Architect *Charles D. ...* Address *153 - 4th Ave*
 Mason _____ Address _____
 Carpenter _____ Address _____

If a Wall or part of a Wall already built is to be used, fill up the following.

The undersigned gives notice that *he* intend to use the *easterly* wall of building *195-7th St. and westerly wall of 199-7th St.* as party wall in the erection of the building hereinbefore described, and respectfully requests that the same be examined and a permit granted therefor. The foundation wall *is* built of *stone* *20-18* inches thick, *10.0* feet below curb; the upper wall *are* built of *Brick*, *8-16 + 16* inches thick, *26.0 + 39.6* feet deep, *40.0* feet in height.

(Sign here) *Charles D. ...*

NOTE—In making application for the erection of buildings, the following drawings must be furnished: Plans of each and every story, front, rear and side elevations, and longitudinal and transverse sections. All plans must be drawn to a uniform scale, and must be on tracing cloth, properly designated and colored.

THE BUILDING LAW REQUIRES:

- 1st—That all stone walls shall be properly bonded and laid in cement mortar.
- 2d—That all skylights having a superficial area of more than nine square feet, placed in any building, shall have the sashes and frames thereof constructed of iron and glass.
- 3d—That every building which is more than two stories in height above the curb level, except dwelling-houses, hotels, school-houses and churches, shall have doors, blinds or shutters made of iron, hung to iron hanging frames or to iron eyes built into the wall, on every window and opening above the first story thereof, excepting on the front openings of buildings fronting on streets which are more than thirty feet in width. Or the said doors, blinds or shutters may be constructed of pine or other soft wood of two thicknesses of matched boards at right angles with each other, and securely covered with tin, on both sides and edges, with folded lapped joints, the nails for fastening the same being driven inside the lap; the hinges and bolt, or latches shall be secured or fastened to the door or shutter after the same has been covered with the tin, and such doors or shutters shall be hung upon an iron frame, independent of the woodwork of the windows and doors, or two iron hinges securely fastened in the masonry; or such frames, if of wood, shall be covered with tin in the same manner as the doors and shutters.
- 4th—That outside fire escapes shall be placed on every dwelling-house occupied by or built to be occupied by three or more families above the first story, and every building already erected, or that may hereafter be erected, more than three stories in height, occupied and used as a hotel or lodging-house, and every boarding-house, having more than fifteen sleeping-rooms above the basement story, and every factory, mill, manufactory or workshop, hospital, asylum or institution for the care or treatment of individuals, and every building in whole or in part occupied or used as a school or place of instruction or assembly, and every office building five stories or more in height, all to be constructed as follows:

BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE.


BRACKETS must not be less than $\frac{1}{2} \times 1\frac{3}{4}$ inches wrought iron, placed edgewise, or $1\frac{3}{4}$ inch angle iron $\frac{1}{2}$ inch thick, well braced, and not more than three feet apart, and the braces to brackets must be not less than $\frac{3}{4}$ inch square wrought iron, and must extend two-thirds of the width of the respective brackets or balconies. In all cases the brackets must go through the wall, and be turned down three inches.
BRACKETS ON NEW BUILDINGS must be set as the walls are being built. When brackets are to be put on old houses, the part going through the wall shall not be less than one inch diameter, with screw nuts and washers not less than five inches square and $\frac{1}{2}$ inch thick.
TOP RAILS.—The top rail of balcony must be $1\frac{3}{4}$ inch \times $\frac{1}{2}$ inch wrought iron or $1\frac{1}{2}$ inch angle iron $\frac{1}{2}$ inch thick, and in all cases must go through the walls, and be secured by nuts and 4 inch square washers, at least $\frac{3}{8}$ inch thick, and no top rail shall be connected at angles by the use of cast iron.
BOTTOM RAILS.—Bottom rails must be $1\frac{1}{2}$ inch \times $\frac{3}{8}$ inch wrought iron or $1\frac{1}{2}$ inch angle iron $\frac{1}{2}$ inch thick, well leaded into the wall. In frame buildings the top rails must go through the studding and be secured on the inside by washers and nuts as above.
FILLING-IN BARS.—The filling-in bars must be not less than $\frac{1}{2}$ inch round or square wrought iron, placed not more than 6 inches from centres, and well riveted to the top and bottom rails.
STAIRS.—The stairs in all cases must be not less than 18 inches wide, and constructed of $\frac{1}{2} \times 3\frac{1}{2}$ inch wrought iron sides or strings. Steps may be of cast iron of the same width of strings, or $\frac{3}{8}$ inch round iron, double rungs, and well riveted to the strings. The stairs must be secured to a bracket on top and rest on and be secured to a bracket or extra cross bar at the bottom. All stairs must have a $\frac{3}{4}$ inch hand rail of wrought iron, well braced.
FLOORS.—The flooring of balconies must be of wrought iron $1\frac{1}{2} \times \frac{3}{8}$ inch slats placed not over $1\frac{1}{4}$ inches apart, and secured to iron battens $1\frac{1}{2} \times \frac{3}{8}$ inch, not over three feet apart and riveted at the intersection. The openings for stairways in all balconies shall not be less than 20 inches wide and 36 inches long, and have no covers.
DROP LADDERS.—Drop ladders from lower balconies where required shall not be less than 14 inches wide, and shall be made of $1\frac{1}{2} \times \frac{3}{8}$ inch sides and $\frac{3}{8}$ inch rungs of wrought iron. In no case shall a drop ladder be more than 12 feet in length. In no case shall the ends of balconies extend more than nine inches over the brackets.
SCUTTLE LADDERS.—Ladders to scuttles shall be constructed in all cases the same as the stairs or step-ladders from balconies of fire escapes.
THE HEIGHT OF RAILING around balconies shall not be less than two feet nine inches.

No Fire Escape will be approved by the Superintendent of Buildings if not in accordance with above specifications.

In constructing all balcony fire-escapes, the manufacturer thereof shall securely fasten thereto, in a conspicuous place, a cast-iron plate having suitable raised letters on the same, to read as follows: Notice! Any person placing any incumbrance on this balcony is liable to a penalty of ten dollars and imprisonment for ten days.

- 5th—That all exterior and division or party walls over fifteen feet high, excepting where such walls are to be finished with cornices, gutters or crown mouldings, shall have parapet walls carried two feet above the roof, and shall be coped with stone, well-burnt terra-cotta or cast iron.
- 6th—That every building and the tops and sides of every dormer-window thereon shall be covered and roofed with slate, tin, copper or iron, or such other quality of fire-proof roofing as the superintendent of buildings, under his certificate, may authorize.
- 7th—That all exterior cornices shall be fire proof.
- 8th—That the stone or brick work of all smoke flues, and the chimney shafts of all furnaces, boilers, bakers' ovens, large cooking ranges and laundry stoves, and all flues used for a similar purpose, shall be at least eight inches in thickness. If there is a cast-iron or burnt clay pipe built inside of the same, with one-inch air space all around it, then the stone or brick work inclosing such pipes shall not be less than four inches in thickness.
- 9th—That before any iron or steel beam, lintel or girder intended to span an opening over ten feet in length in any building, shall be used for supporting a wall, it shall be inspected, tested and approved as provided by law.

Avenue B.



7TH ST.

8TH ST.

NB 2-20/98

Avenue C.

BUREAU OF BUILDINGS
BOROUGH OF MANHATTAN, CITY OF NEW YORK

960

NOTICE—This Application must be TYPEWRITTEN and filed in TRIPPLICATE, and ONE copy sworn to by Applicant. If Elevator or Plumbing Applications are filed herewith, ONE AFFIDAVIT is sufficient for all. Plans must be filed on tracing Linen or Cloth.

Permitted

ALT. APPLICATION No. 960 192

LOCATION N.S. of .7th St. 274'2" E. of Ave. B. BLOCK 390 LOT 57
No. 197-7th St.

New York City, May 5, 1926. 192

To THE SUPERINTENDENT OF BUILDINGS:

Application is hereby made for approval of the plans and specifications herewith submitted, and made a part hereof, for the ALTERATION of the building therein described,—with the understanding that if no work is performed hereunder within one year from the time of issuance, this approval shall expire by limitation as provided by law; and the applicant agrees to comply with all provisions of the Building Code of the City of New York, and with the provisions of all other laws and rules relating to the alteration of said building in effect at this date.

Work under this approval will not be commenced until a permit has been secured, application for which will be filed with the Superintendent of Buildings, accompanied by satisfactory evidence that compensation insurance has been obtained in accordance with the provisions of the Workmen's Compensation Law.

MAY 25 1926

EXAMINED AND RECOMMENDED FOR APPROVAL ON _____ 192

[Signature]

Examiner

APPROVED MAY 25 1926 192

Superintendent of Buildings, Borough of Manhattan.

STATE, COUNTY AND }
CITY OF NEW YORK } ss. Philip Bardes
Typewrite Name of Applicant

being duly sworn, deposes and says: That he resides at Number 230 Grand St.
, in the Borough of Manhattan
in the City of New York , in the County of New York
in the State of New York , that he is the architect for the

owner in fee of all that certain lot, piece or parcel of land, shown on the diagram annexed hereto and made a part hereof, situate, lying and being in the Borough of Manhattan, City of New York aforesaid, and known and designated as Number 197 .7th St. N.S. of .7th St. 274'2" E. of Avenue B. and hereinafter more particularly described; that the work proposed to be done upon the said premises, in accordance with the accompanying detailed statement in writing of the specifications and plans of such proposed work, including all amendments to the same which may be filed hereafter—and also all Elevator and Plumbing work

(if any) proposed to be done upon the same premises and specified in separate applications filed herewith, and all subsequent amendments thereto—is duly authorized by

Reiskin
[Name of Owner or Lessee]

and that

Philip Bardes is

duly authorized by the aforesaid **owner** to make application for the approval of such detailed statement of specifications and plans (and amendments thereto) in **his** behalf.

Deponent further says that the full names and residences, street and number, of the owner or owners of the said land, and also of every person interested in said building or proposed building, structure or proposed structure, premises, wall, platform, staging or flooring, either as owner, lessee, or in any representative capacity, are as follows:

NAMES AND ADDRESSES

Owner **ISAAC Reiskin** 79 7th St. N.Y.C.

Lessee

Architect **Philip Bardes** 230 Grand St. N.Y.C.

Superintendent **Owner**

The said land and premises above referred to are situate at, bounded and described as follows, viz.: BEGINNING

at a point on the **North** side of **7th St.**
distant **274'2"** feet **East** from the corner formed by the intersection of
Avenue B. and **7th St.**
running thence **North 89°10"** feet; thence **East 20'0"** feet;
thence **South 89°10"** feet; thence **West 20'0"** feet

to the point or place of beginning, being designated on the map as Block No. **390** Lot No. **57**

(SIGN HERE) *Philip Bardes* Applicant

Dimensions and Lot and Block numbers agree with Land Map.

Sworn to before me this **5th** day of **May** 19**24**

(Signature) _____
Date _____ Tax Dept. (Title)

**ALTERATION
APPLICATION**

**BUREAU OF BUILDINGS
BOROUGH OF MANHATTAN
CITY OF NEW YORK**

NOTE: ALL elevations and grades for curbs and sidewalks must be obtained from the Commissioner of Public Works, Municipal Building, New York City

BUREAU OF BUILDINGS

BOROUGH OF MANHATTAN, CITY OF NEW YORK

NOTICE—This Application must be TYPEWRITTEN and filed in TRIPLICATE.
 "SPECIFICATIONS—SHEET A" (Form 152) must be filed with EVERY Alteration Application.
 "SPECIFICATIONS—SHEET B" (Form 158) must be filed, in addition, in case the building is to be raised in height or occupancy changed so as to increase floor loads, or if building is to be enlarged on one side.

ALT. APPLICATION No. 960 192 BLOCK 390 LOT 57

LOCATION N.S. of E. 7th St. 274'2" E. of Avenue B.
No. 197 E. 7th St.

DISTRICT (under building zone resolution) Use Business Height 1 1/2 Area B

Examined MAY 20 1928 192 Examiner _____

SPECIFICATIONS—SHEET A

(1) NUMBER OF BUILDINGS TO BE ALTERED One
 Any other building on lot or permit granted for one? No

(2) ESTIMATED COST OF ALTERATION: \$ 10,000.

(3) OCCUPANCY (in detail):
 Of present building Store & Tenement

Of building as altered Tenement

(4) SIZE OF EXISTING BUILDING:
 At street level 20'0" feet front 70'0" feet deep
 At typical floor level 20'0" feet front 70'0" feet deep
 Height 5 & basement stories 55'0" feet

(5) SIZE OF BUILDING AS ALTERED:
 At street level 20'0" feet front 70'0" feet deep
 At typical floor level 20'0" feet front 70'0" feet deep
 Height 5 & basement stories 55'0" feet

(6) CHARACTER OF CONSTRUCTION OF PRESENT BUILDING: Ordinary
 [Frame, Ordinary or Fireproof]

(7) NUMBER OF OCCUPANTS (in each story of building as altered, giving males and females separately in the case of factories):

No factory

(8) STATE GENERALLY IN WHAT MANNER THE BUILDING WILL BE ALTERED:

It is hereby proposed to raise the first tier of floor beams and to rearrange all interior partitions on all floors.
To install new bathrooms, all as shown on plans.