

Plan No. _____

APPLICATION FOR ERECTION OF BUILDINGS.

Application is hereby made to the Superintendent of Buildings of the City of New York, for the approval of the drawings, statement of the specifications and plans herewith submitted, for the erection of the building hereinafter described. All provisions of the Building Law shall be complied with in the erection of said building, whether specified herein or not.

NEW YORK, May 6 1897 (Sign here) Jos. L. Bittman owner
Geo. West Architect

1. State how many buildings to be erected. Two
2. How occupied? If for dwelling, state the number of families. Tenement 22 fam. + 2 stores
3. What is the street or avenue and the number thereof? Give diagram of property. Nos 65-67 East 4th Street
4. Size of lot. No. of feet front, 25.0; No. of feet rear, 25.0; No. of feet deep, 100.0
5. Size of building. No. of feet front, 25.0; No. of feet rear, 25.0; No. of feet deep, 87.0; No. of stories in height, 6; No. of feet in height from curb level to highest point of roof beams, 66.6
6. What will each building cost exclusive of the lot? \$ 27,000.00
7. What will be the depth of foundation walls from curb level or surface of ground? 10 feet
8. Will foundation be laid on earth, sand, rock, timber or piles? Earth
9. What will be the base, stone or concrete? stone If base stones, give size and thickness and how laid. 9x36" laid in Cement If concrete, give thickness.
10. What will be the sizes of piers? 28x28" 24x28" 32x28"
11. What will be the sizes of the base of piers? one foot larger on all sides
12. What will be the thickness of foundation walls? 16", 24", 28" Of what material constructed? Hard brick + rubble stone laid in Cement mortar
13. What will be the thickness of upper walls? Basement 16", 24", 28" inches; 1st story 16 inches; 2d story, 16 inches; 3d story, 12 inches; 4th story, 12 inches; 5th story, 12 inches; 6th story, 12 inches; 7th story, ✓ inches, and from thence to top, 8 inches. Of what materials to be constructed? Hard burnt brick
14. State whether independent or party walls. Independent + Party Party
15. With what material will walls be coped? Blue stone or Earthware
16. What will be the materials of front? Brick If of stone, what kind? ✓ Give thickness of ashler. ✓ Give thickness of backing in each story. ✓
17. Will the roof be flat, peaked or mansard? Flat
18. What will be the materials of roofing? Tin + 4" bk. Arches
19. Give size and materials of floor beams, 1st tier, 8" 54 lbs p.f. steel; 2d tier, 3x10" Spruce; 3d tier, 3x10" Spruce; 4th tier, 3x10" Spruce; 5th tier, 3x10" Spruce; 6th tier, 3x10" Spruce; 7th tier, ✓; 8th tier, ✓; roof tier, 3x9" Spruce
State distances from centres. 1st tier, 4 ft inches; 2d tier, 16 inches; 3d tier, 16 inches; 4th tier, 16 inches; 5th tier, 16 inches; 6th tier, 16 inches; 7th tier, ✓ inches; 8th tier, ✓ inches; roof tier, 20 inches.
20. If floors are to be supported by columns and girders, give the following information: Size and material of girders under 1st floor, 8" brick wall under each of the upper floors, 8" brick wall under each of the upper floors. Size and materials of columns under 1st floor, 8" brick wall under each of the upper floors.
21. This building will safely sustain per superficial foot upon 1st floor 150 lbs.; upon 2d floor 75 lbs.; upon 3d floor 75 lbs.; upon 4th floor 75 lbs.; upon 5th floor 75 lbs. 6th floor 75 lbs
22. If the front, rear or side walls are to be supported, in whole or in part, by iron girders or lintels, give definite particulars. Front wall above 1st floor carried on 3x9" 63 lbs. p.f. steel beams - Front light shafts carried on 6-8" 54 lbs. p.f. steel beams + two 16" Channels
23. If girders are to be supported by brick piers and columns, state the sizes of piers and columns. Front Sider carrying Front wall carried on 11x16" 78x16" + 116x16" Cast Iron Col. 3/4" metal with cap + sole plates complete
24. State by whom the construction of the building is to be superintended. Contractor

If the Building is to be occupied as an Apartment or Tenement House, give the following particulars.

1. State how many families are to occupy each floor, and the whole number in the house; also, if any part is to be used as a store or for any other business purposes, state the fact.

Tenements, four families on upper stories 2 on 1st floor total 22 in all 4th 2 stores

2. What will be the heights of ceilings? 1st story, *11'8"* feet; 2d story, *10'0"* feet; 3d story, *9'8"* feet; 4th story, *9'8"* feet; 5th story, *9'8"* feet; 6th story, *9'8"* feet; 7th story, *✓* feet.

3. How are the hall partitions to be constructed and of what materials? *upper floor 8x12" brick walls 1st story entrance hallway 4" T. b. blocks*

4. How many buildings are to be taken down? *two*

Owner *Jacob Kunguetein* Address *237 East 60th St.*
 Architect *G. F. Pelham* Address *503 Fifth Ave*
 Mason _____ Address _____
 Carpenter _____ Address _____

If a Wall or part of a Wall already built is to be used, fill up the following.

The undersigned gives notice that *he* intends to use the *present party* wall of building *No. 63 East 4th Street*

as party wall in the erection of the building hereinbefore described, and respectfully requests that the same be examined and a permit granted therefor. The foundation wall *is* built of *stone* *20* inches thick, *10'0"* feet below curb; the upper wall *is* built of *brick*, *12* inches thick, *23'0"* feet deep, *alt 35'0"* feet in height. *wall now lined on West side*

(Sign here) *G. F. Pelham Archt*

NOTE--In making application for the erection of buildings, the following drawings must be furnished: Plans of each and every story, front, rear and side elevations, and longitudinal and transverse sections. All plans must be drawn to a uniform scale, and must be on tracing cloth, properly designated and colored.

THE BUILDING LAW REQUIRES:

- 1st--That all stone walls shall be properly bonded and laid in cement mortar.
- 2d--That all skylights having a superficial area of more than nine square feet, placed in any building, shall have the sashes and frames thereof constructed of iron and glass.
- 3d--That every building which is more than two stories in height above the curb level, except dwelling-houses, hotels, school-houses and churches, shall have doors, blinds or shutters made of iron, hung to iron hanging frames or to iron eyes built into the wall, on every window and opening above the first story thereof, excepting on the front openings of buildings fronting on streets which are more than thirty feet in width. Or the said doors, blinds or shutters may be constructed of pine or other soft wood of two thicknesses of matched boards at right angles with each other, and securely covered with tin, on both sides and edges, with folded lapped joints, the nails for fastening the same being driven inside the lap; the hinges and bolt, or latches shall be secured or fastened to the door or shutter after the same has been covered with the tin, and such doors or shutters shall be hung upon an iron frame, independent of the woodwork of the windows and doors, or two iron hinges securely fastened in the masonry; or such frames, if of wood, shall be covered with tin in the same manner as the doors and shutters.
- 4th--That outside fire escapes shall be placed on every dwelling-house occupied by or built to be occupied by three or more families above the first story, and every building already erected, or that may hereafter be erected, more than three stories in height, occupied and used as a hotel or lodging-house, and every boarding-house, having more than fifteen sleeping-rooms above the basement story, and every factory, mill, manufacturing or workshop, hospital, asylum or institution for the care or treatment of individuals, and every building in whole or in part occupied or used as a school or place of instruction or assembly, and every office building five stories or more in height, all to be constructed as follows:

BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE.

BRACKETS must not be less than $\frac{3}{4}$ x $1\frac{3}{4}$ inches wrought iron, placed edgewise, or $1\frac{3}{4}$ inch angle iron $\frac{1}{4}$ inch thick, well braced, and not more than three feet apart, and the braces to brackets must be not less than $\frac{3}{4}$ inch square wrought iron, and must extend two-thirds of the width of the respective brackets or balconies. In all cases the brackets must go through the wall, and be turned down three inches.

BRACKETS ON NEW BUILDINGS must be set as the walls are being built. When brackets are to be put on old houses, the part going through the wall shall not be less than one inch diameter, with screw nuts and washers not less than five inches square and $\frac{1}{2}$ inch thick.

TOP RAILS.--The top rail of balcony must be $1\frac{3}{4}$ inch x $\frac{1}{2}$ inch wrought iron or $1\frac{1}{4}$ inch angle iron $\frac{1}{4}$ inch thick, and in all cases must go through the walls, and be secured by nuts and 4 inch square washers, at least $\frac{3}{8}$ inch thick, and no top rail shall be connected at angles by the use of cast iron.

BOTTOM RAILS.--Bottom rails must be $1\frac{1}{4}$ inch x $\frac{3}{4}$ inch wrought iron or $1\frac{1}{4}$ inch angle iron $\frac{1}{4}$ inch thick, well leaded into the wall. In frame buildings the top rails must go through the studding and be secured on the inside by washers and nuts as above.

FILLING-IN BARS.--The filling-in bars must be not less than $\frac{1}{2}$ inch round or square wrought iron, placed not more than 6 inches from centres, and well riveted to the top and bottom rails.

STAIRS.--The stairs in all cases must be not less than 18 inches wide, and constructed of $\frac{3}{4}$ x $3\frac{1}{2}$ inch wrought iron sides or strings. Steps may be of cast iron of the same width of strings, or $\frac{5}{8}$ inch round iron, double rungs, and well riveted to the strings. The stairs must be secured to a bracket on top and rest on and be secured to a bracket or extra cross bar at the bottom. All stairs must have a $\frac{3}{4}$ inch hand rail of wrought iron, well braced.

FLOORS.--The flooring of balconies must be of wrought iron $1\frac{3}{8}$ x $\frac{3}{8}$ inch slats placed not over $1\frac{1}{4}$ inches apart, and secured to iron battens $1\frac{1}{2}$ x $\frac{3}{8}$ inch, not over three feet apart and riveted at the intersection. The openings for stairways in all balconies shall not be less than 20 inches wide and 36 inches long, and have no covers.

DROP LADDERS.--Drop ladders from lower balconies where required shall not be less than 14 inches wide, and shall be made of $1\frac{1}{2}$ x $\frac{3}{8}$ inch sides and $\frac{5}{8}$ inch rungs of wrought iron. In no case shall a drop ladder be more than 12 feet in length. In no case shall the ends of balconies extend more than nine inches over the brackets.

SCUTTLE LADDERS.--Ladders to scuttles shall be constructed in all cases the same as the stairs or stop-ladders from balconies of fire escapes.

THE HEIGHT OF RAILING around balconies shall not be less than two feet nine inches.

No Fire Escape will be approved by the Superintendent of Buildings if not in accordance with above specifications.

In constructing all balcony fire-escapes, the manufacturer thereof shall securely fasten thereto, in a conspicuous place, a cast-iron plate having suitable raised letters on the same, to read as follows: Notice! Any person placing any incumbrance on this balcony is liable to a penalty of ten dollars and imprisonment for ten days.

- 5th--That all exterior and division or party walls over fifteen feet high, excepting where such walls are to be finished with cornices, gutters or crown mouldings, shall have parapet walls carried two feet above the roof, and shall be coped with stone, well-burnt terra-cotta or cast iron.
- 6th--That every building and the tops and sides of every dormer-window thereon shall be covered and roofed with slate, tin, copper or iron, or such other quality of fire-proof roofing as the superintendent of buildings, under his certificate, may authorize.
- 7th--That all exterior cornices shall be fire proof.
- 8th--That the stone or brick work of all smoke flues, and the chimney shafts of all furnaces, boilers, bakers' ovens, large cooking ranges and laundry stoves, and all flues used for a similar purpose, shall be at least eight inches in thickness. If there is a cast-iron or burnt clay pipe built inside of the same, with one-inch air space all around it, then the stone or brick work inclosing such pipes shall not be less than four inches in thickness.
- 9th--That before any iron or steel beam, lintel or girder intended to span an opening over ten feet in length in any building, shall be used for supporting a wall, it shall be inspected, tested and approved as provided by law.

Cellar—How to be occupied? *Storage*

Basement—How to be occupied? *✓*

Cellar ceiling—Height above sidewalk *✓*

Basement ceiling—Height above sidewalk *✓*

	Cellar.	Basement.	1st floor.	2d floor.	3d floor.	4th floor.	5th floor.	6th floor.	7th floor.
How many families will occupy each floor?	<i>✓</i>	<i>✓</i>	<i>2</i>	<i>4</i>	<i>4</i>	<i>4</i>	<i>4</i>	<i>4</i>	
Height of ceilings	<i>7.8</i>	<i>✓</i>	<i>11.8</i>	<i>10.0</i>	<i>9.8</i>	<i>9.8</i>	<i>9.8</i>	<i>9.8</i>	
Number of living rooms opening on shafts and courts	<i>✓</i>	<i>✓</i>	<i>4</i>	<i>10</i>	<i>10</i>	<i>10</i>	<i>10</i>	<i>10</i>	
Number of living rooms opening on street and yard	<i>✓</i>	<i>✓</i>	<i>2</i>	<i>4</i>	<i>4</i>	<i>4</i>	<i>4</i>	<i>4</i>	

Halls—How lighted and ventilated? *Windows on Open Court & skylight* ^{vent.}

State dimensions of ventilating skylight over main hall *3.0 x 4.0*

Dimensions of windows for living rooms *not less than 12 sq. ft.*

Dimensions of windows for water-closet apartments *not less than 3 sq. ft.*

Dimensions of fanlights over doors of living rooms where marked on plans *1.2 x 2.6*

Basement—How lighted and ventilated? *✓*

“ How made water-tight? *✓*

Cellar—How lighted and ventilated? *Windows on Open Courts*

“ How made water-tight? *cement floor*

Will cellar or basement ceiling be plastered? *yes*

What additional structure, if any, will be on lot? *none*

Distance from extreme rear of main building to rear line of lot *13.0*

Distance from extreme rear of extension to rear line of lot *✓*

	Cellar.	Basement.	1st floor.	2d floor.	3d floor.	4th floor.	5th floor.	6th floor.	7th floor.
Number and location of water-closets ..	<i>✓</i>	<i>✓</i>	<i>2</i>	<i>2</i>	<i>2</i>	<i>2</i>	<i>2</i>	<i>2</i>	

How will the floor and sides of water-closet apartments be made water-tight? *Slates*
back & sides extended to height of W. C. seat

How will water-closet apartments be ventilated? *Windows on Open Courts*

RECEIVED JUL 24 1899
DEPT. OF BUILDINGS OF MANHATTAN & THE

Applicant must indicate the Building Line or Lines clearly and distinctly on the drawings.

2

Plan No. 1766

APPLICATION TO ALTER, REPAIR, Etc.

Application is hereby made to the Commissioner of Buildings of The City of New York, for the Boroughs of Manhattan and The Bronx, for the approval of the detailed statement of the specifications and plans with submitted, for the alteration or repair of the building herein described. All provisions of the Building Law shall be complied with in the alteration or repair of said building, whether specified therein or not.

NEW YORK, July 25th 1899 (Sign here) *Chryers, plans only*

- 1. State how many buildings to be altered. *One*
- 2. What is the street or avenue and the number thereof? Give diagram of property. *67 East 4th Street*
- 3. How much will the alteration cost? \$ *700.00*

GIVE THE FOLLOWING INFORMATION AS TO THE PRESENT BUILDING:

- 1. Size of lot on which it is located, No. of feet front, *25'0"*; feet rear, *25'0"*; feet deep, *100'0"*
- 2. Size of building, No. of feet front, *25'0"*; feet rear, *25'0"*; feet deep, *87'0"* No. of stories in height, *6*; No. of feet in height from curb level to highest point of beams, *66'6"*
- 3. Material of building, *brick*; material of front, *brick terra cotta*
- 4. Whether roof is peak, flat, or mansard, *flat*
- 5. Depth of foundation walls *10'0"* feet; thickness of foundation walls, *24*; materials of foundation walls, *stone*
- 6. Thickness of upper walls, *16 + 12* inches. Material of upper walls, *brick*
- 7. Whether independent or party walls, *party + independent walls*
- 8. How the building is or was occupied, *tenement + stores*

IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION:

- 1. How many stories will the building be when raised?
- 2. How high will the building be when raised?
- 3. Will the roof be flat, peak, or mansard?
- 4. What will be the thickness of wall of additional stories? *story, inches;*
story, inches.
- 5. Give size and material of floor beams of additional stories; *1st tier, x*
2d tier, x Distance from centres on *tier,*
inches; tier inches.
- 6. How will the building be occupied?

IF TO BE EXTENDED ON ANY SIDE, GIVE THE FOLLOWING INFORMATION.

- 1. Size of extension, No. feet front, ; feet rear, ; feet deep, ; No. of stories in height, ; No. of feet in height, .
- 2. What will be the material of foundation walls of extension? . What will be the depth? .feet. What will be the thickness? .inches.
- 3. Will foundation be laid on earth, sand, rock, timber or piles?

IF TO BE EXTENDED ON ANY SIDE GIVE THE FOLLOWING INFORMATION.

4. What will be the base, stone or concrete? If base stones, give size and thickness and how laid, If concrete, give thickness,
5. What will be the sizes of piers? What will be the sizes of the base of piers?
6. What will be the thickness of upper walls? 1st story, inches ; 2d story inches ; 3d story, inches ; 4th story, inches ; 5th story, inches ; 6th story, inches ; 7th story, inches ; from thence to top, inches ; and of what materials to be constructed,
7. State whether independent or party-walls. If party-walls give thickness thereof.
8. With what material will walls be coped?
9. What will be the materials of front? If of stone, what kind? Give thickness of front ashlar. Give thickness of backing.
10. Will the roof be flat, peaked or mansard?
11. What will be the materials of roofing?
12. Give size and material of floor beams, 1st tier, x ; 2d tier, x ; 3d tier, x ; 4th tier, x ; 5th tier, x ; 6th tier, x ; 7th tier, x ; roof tier, x State distance from centres on 1st tier, inches ; 2d tier, inches ; 3d tier, inches ; 4th tier, inches ; 5th tier, inches ; 6th tier, inches ; 7th tier, inches ; roof tier, inches
13. If floors are to be supported by columns and girders, give the following information : Size and material of girders under 1st floor, x under each of the upper floors, Size and material of columns under first floor, under each of the upper floors,
14. If the front, rear or side walls are to be supported, in whole or in part, by iron girders or lintels, give definite particulars,
15. If girders are to be supported by brick piers and columns, state the size of piers and columns.
16. How will the extension be connected with present or main building?
17. How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor.
18. State who will superintend the alterations. *Owner*

IF ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED :

.....
.....
.....
.....

IF THE FRONT, REAR, OR SIDE WALLS, OR ANY PORTION THEREOF, ARE TO BE TAKEN OUT AND REBUILT, GIVE DEFINITE PARTICULARS, AND STATE IN WHAT MANNER :

New windows of size shown will be cut through the present walls on the first floor and in cellar; these window openings will be cut beside the present piers that will not be disturbed in any way. Granite blocks, piers, beams, etc, will not be affected by new openings. A new door of size marked on plans will be cut through wall in cellar where shown

DEPARTMENT OF HOUSING AND BUILDINGS
BOROUGH OF MANHATTAN, CITY OF NEW YORK

MANHATTAN
Municipal Bldg.,
Manhattan

BROOKLYN
Municipal Bldg.,
Brooklyn

BRONX
Bronx County Bldg.,
Grand Conc. & E. 161st St.

QUEENS
21-10 49th Avenue,
L. I. City

RICHMOND
Boro Hall,
St. George, S. I.

NOTICE—This Application must be TYPEWRITTEN and filed in QUADRUPPLICATE

ALTERED BUILDING

PERMIT NO. 19 BLOCK 460 LOT 53

Application No. **1187** 1939 SEC. OR WARD VOL.
 N.B. ALT.

LOCATION 67 East 4th Street - U.S. 217'-6" East of Bowery

DISTRICT (under building zone resolution) Use Business Height 13 Area B

EXAMINED AND RECOMMENDED

FOR APPROVAL ON May 9 1959

Examiner

APPROVED MAY 8 1959 19

Borough Superintendent

SPECIFICATIONS

- (1) NUMBER OF BUILDINGS TO BE ALTERED One
 Any other building on lot or permit granted for one? NO
 Is building on front or rear of lot? Front
- (2) ESTIMATED COST OF ALTERATION: \$ 2,500.00
- (3) PROPOSED OCCUPANCY: Class "A" Multiple Dwelling-Old Law Tenement

STORY (include Cellar and basement)	BEFORE ALTERATION			AFTER ALTERATION						
	APTS.	ROOMS	USE	LIVE LOAD	NO. OF PERSONS			APTS.	ROOMS	USE
					MALE	FEMALE	TOTAL			
Cellar	0	0	Storage and Boiler Room							No change
1st fl	2	6	2 stores & B.O.	120	3	2	5	2	6	No change
2nd fl	4	14	Multiple Dwell.	40				4	14	No change
3rd fl	4	14	Multiple Dwell.	40				4	14	No change
4th fl	4	14	Multiple Dwell.	40				4	14	No change
5th fl	4	14	Multiple Dwell.	40				4	14	No change
6th fl	4	14	Multiple Dwell.	40				4	14	No change
NOTE: NO CHANGE OF OCCUPANCY.										

ORIGINAL

(4) SIZE OF EXISTING BUILDING:
 At typical floor level 25'-0" feet front 88'-0" feet deep 25'-0" feet rear
 At street level 25'-0" feet front 88'-0" feet deep 25'-0" feet rear
 Height¹ 6 stories 70'-0" feet

(5) SIZE OF BUILDING AS ALTERED:
 At street level feet front feet deep feet rear
 At typical floor level NO CHANGE feet front NO CHANGE feet deep NO CHANGE feet rear
 Height¹ stories feet

If volume of building is to be increased, give the following information: NO INCREASE.

(6) AREA² OF BUILDING AS ALTERED: At street level Total floor area² sq. ft.

(7) TOTAL HEIGHT³ Cubic Contents⁴ cu. ft.

1. The term "height" of a structure shall mean the vertical distance from the curb level to the highest point of the roof beams in the case of flat roofs or to a point at the average height of the gable in the case of roofs having a pitch of more than one foot in four and one-half, except that in the case of structure where the grade of the street has not been legally established or where the structure does not adjoin the street, the average level of all the ground adjoining such structures shall be used instead of the curb level.

2. In computing this area, measurement shall be taken to the outside surfaces of exterior walls at each floor. Courts, yards, etc., shall be excluded. The areas of cellars and basements shall not be included.

3. Total height shall be measured from 6 inches below the lowest finished floor to the outside of the roof, and in case of sloping roofs, to the average height.

4. The cubical contents is the actual space enclosed within the outer surfaces of the outside walls and between the outer surface of the roof and six inches below the surface of the lowest floors. This includes the cube of dormers, penthouses, vaults, pits, enclosed porches, and other enclosed appendages. Outside steps, terraces, footings, courts, yards, light shafts and buildings detached from the main structure are not to be included. (Detached structures are to be separately computed.)

(8) CHARACTER OF PRESENT BUILDING:

Frame—	Fire-Protected—
Non-fireproof— non-fireproof	Metal—
Fireproof—	Heavy Timber—

(9) STATE GENERALLY IN WHAT MANNER THE BUILDING WILL BE ALTERED:

It is proposed to do all required fire-retarding work throughout; to remove existing hall toilets and install new bath rooms as well as new combination sinks and tubs for each apartment, and finally to remove existing store fronts and stoop and replace same with new modern store fronts and building entrance, all as shown on the accompanying plan.

If the building is to be raised in height or if the occupancy is changed so that the floor loads will be increased, the following information must be given as to the EXISTING BUILDING and the thickness of existing walls and size of footings must be clearly shown on the plans.

(10) NATURE OF SOIL UPON WHICH FOOTINGS WILL REST IN TERMS OF SECTION 7.5.2, BUILDING CODE:

(11) FOOTINGS: Material

(12) FOUNDATION WALLS: Material

(13) UPPER WALLS: Material

Kind of Mortar

Any Ashlar

Thickness of Walls

(14) PARTY WALLS: Any to be used?

Thickness of Walls

If building is to be enlarged or extended, the following information as to NEW WORK must be given:

(15) NATURE OF SOIL UPON WHICH FOOTINGS WILL REST IN TERMS OF SECTION 7.5.2, BUILDING CODE:

(16) FOOTINGS: Material

(17) FOUNDATION WALLS: Material

(18) UPPER WALLS: Material

Kind of Mortar

Any Ashlar

Thickness of Walls

(19) PARTY WALLS: Any to be used?

Thickness of Walls

(20) FIREPROOFING: Material and Thickness

For Columns

For Girders

For Beams

(21) INTERIOR FINISH: Material

Floor Surface

Trim, Sash, Doors, etc.

Plaster

(22) OUTSIDE WINDOW FRAMES AND SASH: Material

(23) ANY ELECTRICAL WORK TO BE DONE?

REMARKS

Inspector