

ORIGINAL

1

1408

Applicant must indicate the Building Line or Lines clearly and distinctly on the Drawings.

B402  
L 52

Office of the Borough President of the Borough of Manhattan,  
In The City of New York.

THE BUREAU OF BUILDINGS FOR THE BOROUGH OF MANHATTAN,  
Office, No. 220 FOURTH AVENUE  
S. W. Corner 18th Street.

Plan No. 1408

APPLICATION TO ALTER, REPAIR, ETC.

Application is hereby made to the Superintendent of Buildings of The City of New York for the Borough of Manhattan for the approval of the detailed statement of the specifications and plans herewith submitted for the alteration or repair of the building herein described. All provisions of the law shall be complied with in the alteration or repair of said building, whether specified herein or not.

(Sign here) *Henry J. Regelman Archt.*

THE CITY OF NEW YORK,  
BOROUGH OF MANHATTAN, July 27 1904

LOCATION AND DESCRIPTION OF PRESENT BUILDING.

- State how many buildings to be altered. One
- What is the exact location thereof? (State on what street or avenue; the side thereof, the number of feet from the nearest street or avenue, and the name thereof).  
# 527 E. 6th St.
- How was the building occupied? 1 tenement  
How is the building to be occupied? 1 tenement
- Is the building on front or rear of lot? \_\_\_\_\_ Is there any other building erected on lot or permit granted for one? \_\_\_\_\_ Size \_\_\_\_\_ x \_\_\_\_\_; height \_\_\_\_\_ How occupied? \_\_\_\_\_ Give distance between same and proposed building \_\_\_\_\_ feet.
- Size of lot? 35' 0" feet front; 25' 0" feet rear; 91' 4" feet deep.
- Size of building which it is proposed to alter or repair? 25' 0" feet front; 25' 0" feet rear; 54' 2" feet deep. Number of stories in height? 5 stories Height from curb level to highest point? 55' 0"  
*Cellar, Basement and*
- Depth of foundation walls below curb level? 12' 0" Material of foundation walls? Blue Stone  
Thickness of foundation walls? front 20" inches; rear 20" inches; side 20" inches; party 20" inches.
- Material of upper walls? Brick If ashlar, give kind and thickness. no
- Thickness of upper walls:  
Basement: front 12 inches; rear 12 inches; side 12 inches; party 12 inches.  
1st story: " 12 " " 12 " " 12 " " 12 "  
2d story: " 12 " " 12 " " 12 " " 12 "  
3d story: " 12 " " 12 " " 12 " " 12 "  
4th story: " 12 " " 12 " " 12 " " 12 "  
5th story: " 12 " " 12 " " 12 " " 12 "  
6th story: " \_\_\_\_\_ " \_\_\_\_\_ " \_\_\_\_\_ " \_\_\_\_\_ " \_\_\_\_\_ " \_\_\_\_\_ "
- Is roof flat, peak or mansard? Flat

If the Front, Rear or Side Walls, or any portion thereof, are to be taken out and rebuilt, give definite particulars, and state in what manner :

47. I propose to take out partitions shown on plans in dotted lines & reset new stud partitions, to be plastered 3 coats.  
Cut new openings for close compartment windows on all upper stories, set into openings cast iron frames with lugs cast on outside as per detail on plans.  
Frames to be full thickness of walls, and to be built solid into same.

If altered Internally, give definite particulars, and state how the building will be occupied :

48. Should present piers become defective during construction of work same will then be rebuilt in cement.

66. This building will safely sustain per superficial foot upon the first floor \_\_\_\_\_ lbs.; upon 2d floor \_\_\_\_\_ lbs.; upon 3d floor \_\_\_\_\_ lbs.; upon 4th floor \_\_\_\_\_ lbs.; upon 5th floor \_\_\_\_\_ lbs.; upon 6th floor \_\_\_\_\_ lbs.; upon 7th floor \_\_\_\_\_ lbs.; upon 8th floor \_\_\_\_\_ lbs.

Owner, Ignatz Bauer Esq. Address, # 527 E. 6th St.

Architect, Henry G. Schumann " # 133-7th St.

Superintendent, \_\_\_\_\_

Mason, \_\_\_\_\_

Carpenter, \_\_\_\_\_