

Plan No. 1870

*Original*

442  
20

APPLICATION TO ALTER, REPAIR, ETC.

Application is hereby made to alter as per subjoined detailed statement of specification for Alterations, Additions or Repairs to buildings already erected, and 2 herewith submit Plans and Drawings of such proposed alterations; and 2 do hereby agree that the provisions of the Building Law will be complied with, whether the same are specified herein or not.

(Sign here) Fred. Gehring

NEW YORK, October 27, 1891

1. State how many buildings to be altered. One
2. What is the street or avenue and the number thereof? Give diagram of property. No 47 1/2 First Str.
3. How much will the alteration cost? \$ 500.00

GIVE THE FOLLOWING INFORMATION AS TO THE PRESENT BUILDING :

1. Size of lot on which it is located, No. of feet front, 20'9"; feet rear, 20'9"; feet deep, 69'4"
2. Size of building, No. of feet front, 20'9"; feet rear, 20'9"; feet deep, 52'2" No. of stories in height, 5; No of feet in height from curb level to highest point of beams, 54
3. Material of building, Brick; material of front, Brick
4. Whether roof is peak, flat, or mansard, Flat
5. Depth of foundation walls 10'0" feet; thickness of foundation walls, 16; materials of foundation walls, Brick laid in cement
6. Thickness of upper walls, 12 inches. Material of upper walls, Brick
7. Whether independent or party walls, Independent & Party
8. How the building is or was occupied, Tenement and Store

IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION :

1. How many stories will the building be when raised? .....
2. How high will the building be when raised? .....
3. Will the roof be flat, peak, or mansard? .....
4. What will be the thickness of wall of additional stories? ..... story, ..... inches; ..... story, ..... inches.
5. Give size and material of floor beams of additional stories; ..... 1st tier, ..... x ..... 2d tier, ..... x ..... Distance from centres on ..... tier, ..... inches; ..... tier ..... inches.
6. How will the building be occupied? .....

IF TO BE EXTENDED ON ANY SIDE, GIVE THE FOLLOWING INFORMATION.

1. Size of extension, No. feet front, .....; feet rear, .....; feet deep, .....; No. of stories in height, .....; No. of feet in height, .....
2. What will be the material of foundation walls of extension? ..... What will be the depth? ..... feet. What will be the thickness? ..... inches.
3. Will foundation be laid on earth, sand, rock, timber or piles? .....

IF TO BE EXTENDED ON ANY SIDE GIVE THE FOLLOWING INFORMATION.

4. What will be the base, stone or concrete?..... If base stones, give size and thickness and how laid,..... If concrete, give thickness,.....
5. What will be the sizes of piers?..... What will be the sizes of the base of piers?.....
6. What will be the thickness of upper walls? 1st story,..... inches ; 2d story..... inches ; 3d story,..... inches ; 4th story,..... inches ; 5th story,..... inches ; 6th story,..... inches ; 7th story,..... inches ; from thence to top,..... inches ; and of what materials to be constructed,.....
7. State whether independent or party-walls..... If party-walls give thickness thereof.....
8. With what material will walls be coped?.....
9. What will be the materials of front?..... If of stone, what kind?..... Give thickness of front ashlar..... Give thickness of backing.....
10. Will the roof be flat, peaked or mansard?.....
11. What will be the materials of roofing?.....
12. Give size and material of floor beams, 1st tier,..... x..... ; 2d tier,..... x..... ; 3d tier,..... x..... ; 4th tier,..... x..... ; 5th tier,..... x..... ; 6th tier,..... x..... ; 7th tier,..... x..... ; roof tier,..... x..... State distance from centres on 1st tier,..... inches ; 2d tier,..... inches ; 3d tier,..... inches ; 4th tier,..... inches ; 5th tier,..... inches ; 6th tier,..... inches ; 7th tier,..... inches ; roof tier,..... inches
13. If floors are to be supported by columns and girders, give the following information : Size and material of girders under 1st floor,.....,..... x..... under each of the upper floors,..... Size and material of columns under first floor,..... under each of the upper floors,.....
14. If the front, rear or side walls are to be supported, in whole or in part, by iron girders or lintels, give definite particulars,.....
15. If girders are to be supported by brick piers and columns, state the size of piers and columns. ....
16. How will the extension be connected with present or main building?.....
17. How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor.....
18. State who will superintend the alterations.....

IF ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED :

IF THE FRONT, REAR, OR SIDE WALLS, OR ANY PORTION THEREOF, ARE TO BE TAKEN OUT AND REBUILT, GIVE DEFINITE PARTICULARS, AND STATE IN WHAT MANNER :

The present store front is to be removed and a new one put in in 1st story, to project 12" the sill of show window to be 18" from sidewalk.  
The masonry & ironwork are not to be touched.  
The building will be occupied same as it is at present with Store & Tenement

Owner Rudolph Marten Address 47 1/2 First Str.  
 Architect Fred Behning Address 40 3 First Ave.  
 Mason Address  
 Carpenter Address

REPORT UPON APPLICATION.

BUREAU OF INSPECTION OF BUILDINGS,  
 NEW YORK, Oct 29 1891

To the Superintendent of Buildings:

I respectfully report that I have thoroughly examined and measured the building, walls, etc., named in the foregoing application, and found the foundation wall to be built of Brick 16 inches thick, 10 feet below curb, the upper wall built of Brick 12 inches thick, 52 feet deep, 54 feet in height, and that the mortar in said wall is good hard and good, and that all the walls are in good and safe condition.

What is the nature of the ground? Sandy

What kind of sand was used in the mortar? Good

How is or was the building occupied? Residence

(The Inspector must here state what defects, if any, are in the walls, beams or other part of the building.)

The " " state the thickness of each wall in each and every story.)

Foundation	16"
1st story	12
2 "	12
3 "	12
4 "	12
5 "	12

THE BUILDING LAW REQUIRES:

- 1st—All stone walls must be properly bonded.
- 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass.
- 3d—All buildings over two stories or above 25 feet in height, except dwellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted.
- 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first, and on dwellings more than four stories in height, occupied by three or more families above the first floor, and on office buildings, hotels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows:

BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE.

BRACKETS must not be less than 1/4 x 1 3/4 inches wrought iron, placed edgewise, or 1 3/4 inch angle iron 1/4 inch thick, well braced, and not more than three feet apart, and the braces to brackets must be not less than 3/4 inch square wrought iron, and must extend two-thirds of the width of the respective brackets or balconies. In all cases the brackets must go through the wall, and be turned down three inches.

BRACKETS ON NEW BUILDINGS must be set as the walls are being built. When brackets are to be put on old houses, the part going through the wall shall not be less than one inch diameter, with screw nuts and washers not less than five inches square and 1/2 inch thick.

TOP RAILS.—The top rail of balcony must be 1 3/4 inch x 3/4 inch wrought iron or 1 1/2 inch angle iron 1/4 inch thick, and in all cases must go through the walls, and be secured by nuts and 4 inch square washers, at least 3/8 inch thick, and no top rail shall be connected at angles by the use of cast iron.

BOTTOM RAILS.—Bottom rails must be 1 1/4 inch x 3/4 inch wrought iron or 1 1/2 inch angle iron 1/4 inch thick, well led into the wall. In frame buildings the top rails must go through the studding and be secured on the inside by washers and nuts as above.

FILLING-IN BARS.—The filling-in bars must be not less than 1/2 inch round or square wrought iron, placed not more than 6 inches from centres, and well riveted to the top and bottom rails.

STAIRS.—The stairs in all cases must be not less than 18 inches wide, and constructed of 1/4 x 3 1/4 inch wrought iron sides or strings. Steps may be of cast iron of the same width of strings, or 3/8 inch round iron, double rungs, and well riveted to the strings. The stairs must be secured to a bracket on top and rest on and be secured to a bracket or extra cross bar at the bottom. All stairs must have a 3/4 inch hand rail of wrought iron, well braced.

FLOORS.—The flooring of balconies must be of wrought iron 1 3/4 x 3/4 inch slats placed not over 1 1/4 inches apart, and secured to iron battens 1 1/2 x 3/4 inch, not over three feet apart and riveted at the intersection. The openings for stairways in all balconies shall not be less than 20 inches wide and 30 inches long, and have no covers.

DROP LADDERS.—Drop ladders from lower balconies where required shall not be less than 14 inches wide, and shall be made of 1 1/2 x 3/4 inch sides and 5/8 inch rungs of wrought iron. In no case shall a drop ladder be more than 12 feet in length. In no case shall the ends of balconies extend more than nine inches over the brackets.

SCUTTLE LADDERS.—Ladders to scuttles shall be constructed in all cases the same as the stairs or step-ladders from balconies of fire escapes.

THE HEIGHT OF RAILING around balconies shall not be less than two feet nine inches.

No Fire Escape will be approved by this Bureau if not in accordance with above specifications.

- 5th—All walls must be coped with stone or terra cotta. If coped with stone, the stone must not be less than 2 1/2 inches thick; and if with terra cotta, the terra cotta must be made with proper lap joints.
- 6th—Roofs must be covered with fire-proof material.
- 7th—All cornices must be fire-proof.
- 8th—All FURNACE FLUES OF DWELLING HOUSES shall have at least eight inch walls on each side. No furnace flues shall be of less size than eight inches square, or four inches wide and sixteen inches long, inside measure. If preferred, the furnace flues may be made of cast iron or fire-clay pipe of proper size built in the walls, with an air space of not less than one inch between said pipes, and four inches of brick wall on the outside.  
 All flues not built for furnace or boiler flues must be altered to conform to the above requirements before they are used as such.
- 9th—No iron beam, lintel, or girder, intended to span an opening over eight feet, intended to support a wall, shall be used for that purpose, until tested and approved as provided by law.

Applicant must indicate the Building Line or Lines clearly and distinctly on the Drawings.

B 442

Office of the Borough President of the Borough of Manhattan, 2

In The City of New York.

L 19

THE BUREAU OF BUILDINGS FOR THE BOROUGH OF MANHATTAN,

Office, No. 220 FOURTH AVENUE,

S. W. Corner 18th Street.

20

Plan No.

APPLICATION TO ALTER, REPAIR, ETC.

Application is hereby made to the Superintendent of Buildings of The City of New York for the Borough of Manhattan for the approval of the detailed statement of the specifications and plans herewith submitted for the alteration or repair of the building herein described. All provisions of the law shall be complied with in the alteration or repair of said building, whether specified herein or not.

(Sign here) O. Rusemann

THE CITY OF NEW YORK,

BOROUGH OF MANHATTAN, May 19, 1906.

LOCATION AND DESCRIPTION OF PRESENT BUILDING.

- State how many buildings to be altered two
- What is the exact location thereof? (State on what street or avenue; the side thereof, the number of feet from the nearest street or avenue, and the name thereof) South side of First St. 250' east of Second Ave. #47847912
- How was the building occupied? tenements  
How is the building to be occupied? tenements
- Is the building on front or rear of lot? front Is there any other building erected on lot or permit granted for one? no Size \_\_\_\_\_ x \_\_\_\_\_; height \_\_\_\_\_ How occupied? \_\_\_\_\_ Give distance between same and proposed building \_\_\_\_\_ feet.
- Size of lot? 42 feet front; 42 feet rear; 66'6" feet deep.
- Size of building which it is proposed to alter or repair? 42 feet front; 42 feet rear; 46'6" feet deep. Number of stories in height? 5 Height from curb level to highest point? 55 ft.
- Depth of foundation walls below curb level? 8 ft. Material of foundation walls? stone Thickness of foundation walls? front 24 inches; rear 24 inches; side 24 inches; party \_\_\_\_\_ inches.
- Material of upper walls? brick If ashlar, give kind and thickness \_\_\_\_\_
- Thickness of upper walls:  
Basement: front \_\_\_\_\_ inches; rear \_\_\_\_\_ inches; side \_\_\_\_\_ inches; party \_\_\_\_\_ inches.  
1st story: " 16 " " 16 " " 16 " " " "  
2d story: " 12 " " 12 " " 12 " " " "  
3d story: " 12 " " 12 " " 12 " " " "  
4th story: " 12 " " 12 " " 12 " " " "  
5th story: " 12 " " 12 " " 12 " " " "  
6th story: " \_\_\_\_\_ " " \_\_\_\_\_ " " \_\_\_\_\_ " " \_\_\_\_\_
- Is roof flat, peak or mansard? flat

If the Front, Rear or Side Walls, or any portion thereof, are to be taken out and rebuilt, give definite particulars, and state in what manner :

47. *but window openings in front + rear wall.*  
*Same to have 2-4" 6 lbs. per ft. steel beams.*  
*cast iron window boxes with 10" channel on top.*

If altered Internally, give definite particulars, and state how the building will be occupied :

48. *Blk. M. b. comp. as shown.*  
*Lath + plaster partitions.*  
*Windows in cross partitions*

*Occupied as before.*

49. How much will the alteration cost? *\$ 4000*

If the Building is to be occupied as a Flat, Apartment or Lodging House, give the following particulars :

50. Is any part of building to be used as a store or for any other business purpose, if so, state for what?

	Cellar	Basement	1st Floor	2d Floor	3d Floor	4th Floor	5th Floor	6th Floor
51. How many families will occupy each?								
52. Height of ceilings?								

53. How basement to be occupied? .....  
 How made water-tight? .....
54. Will cellar or basement ceiling be plastered? ..... How? .....
55. How will cellar stairs be enclosed? .....
56. How cellar to be occupied? .....  
 How made water-tight? .....
57. Will shafts be open or covered with louvre skylights full size of shafts? .....
- Size of each shaft? .....

58.

Dim \_\_\_\_\_

59. Of what materials will hall partitions be constructed? \_\_\_\_\_

60. Of what materials will hall floors be constructed? \_\_\_\_\_

61. How will hall ceilings and soffits of stairs be plastered? \_\_\_\_\_

62. Of what material will stairways be constructed? \_\_\_\_\_

Give sizes of stair well holes? \_\_\_\_\_

63. If any other building on lot, give size; front \_\_\_\_\_; rear \_\_\_\_\_; deep \_\_\_\_\_; stories high \_\_\_\_\_; how occupied \_\_\_\_\_; on front or rear of lot \_\_\_\_\_; material \_\_\_\_\_

How much space between it and proposed building? \_\_\_\_\_

64. How will floors and sides of water closets to the height of 16 inches be made waterproof? \_\_\_\_\_

65. Number and location of water closets: Cellar \_\_\_\_\_; 1st floor \_\_\_\_\_; 2d floor \_\_\_\_\_; 3d floor \_\_\_\_\_; 4th floor \_\_\_\_\_; 5th floor \_\_\_\_\_; 6th floor \_\_\_\_\_

66. This building will safely sustain per superficial foot upon the first floor \_\_\_\_\_ lbs.; upon 2d floor \_\_\_\_\_ lbs.; upon 3d floor \_\_\_\_\_ lbs.; upon 4th floor \_\_\_\_\_ lbs.; upon 5th floor \_\_\_\_\_ lbs.; upon 6th floor \_\_\_\_\_ lbs.; upon 7th floor \_\_\_\_\_ lbs.; upon 8th floor \_\_\_\_\_ lbs.

Owner, Morris Soffer Address, 171 Canal St

Architect, O. Reissmann " 30 First St

Superintendent, owner " \_\_\_\_\_

Mason, 2 " \_\_\_\_\_

Carpenter, \_\_\_\_\_ " \_\_\_\_\_

DEPARTMENT OF HOUSING AND BUILDINGS  
BOROUGH OF Manhattan, CITY OF NEW YORK

MANHATTAN Municipal Bldg., Manhattan  
BROOKLYN Municipal Bldg., Brooklyn  
BRONX Bronx County Bldg., Grand Concourse & E. 161st St.,  
QUEENS 21-10 49th Avenue, L. I. City  
RICHMOND Boro Hall St. George, S. I.

NOTICE—This Application must be TYPEWRITTEN and filed in TRIPLICATE, and ONE copy sworn to by Applicant. A copy must be kept in plain view on the work at all times until completion.

PERMIT

PERMIT No. 4599 19 39 } N. B. ALT. P. & D. ELEV. D. W. SIGN } Application No. 3146 19 39

LOCATION 47 1/2 East 1st Street

BLOCK 442 LOT 20

FEE PAID FOR

New York City Nov 10, 1939 19

To the Borough Superintendent:

Application is hereby made for a PERMIT to perform the entire

work described in the above numbered application and the accompanying plans. If no work is performed within one year from the time of issuance, this permit shall expire by limitation as provided by law; and the applicant agrees to comply with all provisions of the Building Code of the City of New York and with the provisions of all other laws and rules relating to this subject. Compensation insurance has been secured in accordance with the requirements of the Workmen's Compensation Law as follows:

Standard Surety & Cas Co WC OS 59907 exp. Sept. 25, 1940

When the policy of a general contractor does not fully cover the work of any sub-contractor, such sub-contractor must file a certificate of workmen's compensation covering his particular work. No work is to be commenced by this sub-contractor until his certificate has been submitted and approved by this department.

The construction work covered by this permit will be supervised by a Licensed Architect, or a Professional Engineer, or by a Superintendent of Construction, having at least ten years' experience, acceptable to the Borough Superintendent.

STATE AND CITY OF NEW YORK } ss. Abraham Fisher for S.S. Jackson  
COUNTY OF New York } Typewrite Name of Applicant

being duly sworn, deposes and says: That he resides at Number 135 Edgecombe Ave in the Borough of Manhattan in the City of N.Y., in the County of N.Y. in the State of N.Y. that he is agent for contractor for lessees and owner in fee of all that certain lot, piece or parcel of land, shown on the diagram annexed to the approved application and made a part thereof, situate, lying and being in the Borough of Manhattan, City of New York aforesaid, and known and designated as Number 47 1/2 E. 1st St

and therein more particularly described; that the work proposed to be done upon the said premises, in accordance with the approved application and accompanying plans is duly authorized by Borough Provision Co, Inc

and that S.S. Jackson lessee is duly authorized by the aforesaid to make application for a permit to perform said work set forth in the approved application and accompanying plans, and all the statements herein contained are true to deponent's own knowledge.

(SIGN HERE) Abraham Fisher

Sworn to before me, this 10 day of Nov 1939  
Notary Public or Commissioner of Deeds

Satisfactory evidence having been submitted as indicated above that compensation insurance has been secured in accordance with the Workmen's Compensation Law, a permit is hereby issued for the performance of the entire work described in the above numbered application and the accompanying plans.

EXAMINED AND RECOMMENDED FOR APPROVAL ON NOV 10 1939, 19

proved 19 7  
Examiner  
Borough Superintendent

DEPARTMENT OF HOUSING AND BUILDINGS

BOROUGH OF Manhattan, CITY OF NEW YORK

MANHATTAN  
Municipal Bldg.,  
Manhattan

BROOKLYN  
Municipal Bldg.,  
Brooklyn

BRONX  
Bronx County Bldg.,  
Grand Concourse & E. 161st St.

QUEENS  
21-10 49th Avenue,  
L. I. City

RICHMOND  
Boro Hall,  
St. George, S. I.

NOTICE—This Application must be TYPEWRITTEN and filed in QUADRUPPLICATE.

ALTERED BUILDING

PERMIT No. 19 BLOCK 442 LOT 20

APPLICATION No. 19 SEC. OR WARD VOL.  
N.B. ALT.

LOCATION 47 1/2 East 1st Street

DISTRICT (under building zone resolution) USE Bus. HEIGHT 1 1/2 AREA B

EXAMINED AND RECOMMENDED

FOR APPROVAL ON Nov 9 1939

*John J. Daniels*  
Examiner.

11-9-39

APPROVED 10-10-39 19

Borough Superintendent

SPECIFICATIONS

- (1) NUMBER OF BUILDINGS TO BE ALTERED one  
Any other building on lot or permit granted for one? no  
Is building on front or rear of lot? front
- (2) ESTIMATED COST OF ALTERATION: \$ 2000.00
- (3) PROPOSED OCCUPANCY: Factory & Old Law Tenement Multiple Dwelling Class A

STORY (include cellar and basement)	BEFORE ALTERATION			AFTER ALTERATION						
	APTS.	ROOMS	USE	LIVE LOAD	NO. OF PERSONS			APTS.	ROOMS	USE
					MALE	FEMALE	TOTAL			
Cellar			Storage							Storage
1st Fl	1	2	Apartment and Store	120	5		5	0	0	Factory
2nd Fl	2	8	Apartments					2	8	Apartments
3rd Fl	2	8	"					2	8	"
4th Fl	2	8	"					2	8	"
5th Fl	2	8	"					2	8	"

(4) SIZE OF EXISTING BUILDING:  
At typical floor level 20-7 feet front 52 feet deep 20-7 feet rear  
At street level 20-7 feet front 52 feet deep 20-7 feet rear  
Height<sup>1</sup> 5 stories 53 feet

(5) SIZE OF BUILDING AS ALTERED:  
At street level feet front feet deep feet rear  
At typical floor level same feet front same feet deep same feet rear  
Height<sup>1</sup> stories feet

If volume of building is to be increased, give the following information:

(6) AREA<sup>2</sup> OF BUILDING AS ALTERED: At street level Total floor area<sup>2</sup> sq. ft.  
(7) TOTAL HEIGHT<sup>3</sup> Cubic Contents<sup>4</sup> cu. ft.

1. The term "height" of a structure shall mean the vertical distance from the curb level to the highest point of the roof beams in the case of flat roofs or to a point at the average height of the gable in the case of roofs having a pitch of more than one foot in four and one-half, except that in the case of structure where the grade of the street has not been legally established or where the structure does not adjoin the street, the average level of all the ground adjoining such structures shall be used instead of the curb level.  
2. In computing this area, measurement shall be taken to the outside surfaces of exterior walls at each floor. Courts, yards, etc., shall be excluded. The areas of cellars and basements shall not be included.  
3. Total height shall be measured from 6 inches below the lowest finished floor to the outside of the roof, and in case of sloping roofs, to the average height.  
4. The cubical contents is the actual space enclosed within the outer surfaces of the outside walls and between the outer surface of the roof and six inches below the surface of the lowest floors. This includes the cube of dormers, penthouses, vaults, pits, enclosed porches, and other enclosed appendages. Outside steps, terraces, footings, courts, yards, light shafts and buildings detached from the main structure are not to be included. (Detached structures are to be separately computed.)



(8) CHARACTER OF PRESENT BUILDING:

Frame—	Fire-Protected—
Non-fireproof— yes	Metal—
Fireproof—	Heavy Timber—

(9) STATE GENERALLY IN WHAT MANNER THE BUILDING WILL BE ALTERED:

Remove partitions, cut new opening in brick party wall to adjoining building and erect new terra cotta block and brick walls for smoke house enclosure, set new columns and girders in cellar and fire retard walls and ceiling of first floor as shown on plans.

If the building is to be raised in height or if the occupancy is changed so that the floor loads will be increased, the following information must be given as to the EXISTING BUILDING and the thickness of existing walls and size of footings must be clearly shown on the plans.

(10) NATURE OF SOIL UPON WHICH FOOTINGS WILL REST IN TERMS OF SECTION 7.5.2, BUILDING CODE:

course sand

(11) FOOTINGS: Material concrete

(12) FOUNDATION WALLS: Material stone

(13) UPPER WALLS: Material brick  
Kind of Mortar cement  
Any Ashlar  
Thickness of Walls

(14) PARTY WALLS: Any to be used? yes  
Thickness of Walls see plan

If building is to be enlarged or extended, the following information as to NEW WORK must be given:

(15) NATURE OF SOIL UPON WHICH FOOTINGS WILL REST IN TERMS OF SECTION 7.5.2, BUILDING CODE:

(16) FOOTINGS: Material

(17) FOUNDATION WALLS: Material

(18) UPPER WALLS: Material  
Kind of Mortar  
Any Ashlar  
Thickness of Walls

(19) PARTY WALLS: Any to be used?  
Thickness of Walls

(20) FIREPROOFING: Material and Thickness  
For Columns  
For Girders  
For Beams

(21) INTERIOR FINISH: Material  
Floor Surface cement  
Trim, Sash, Doors, etc. kalamein  
Plaster cement

(22) OUTSIDE WINDOW FRAMES AND SASH: Material

(23) ANY ELECTRICAL WORK TO BE DONE? yes

REMARKS

Inspector.