570

Detailed Statement of Specification for Alterations, Additions, or Repairs to Buildings already Erected,

and herewith submit a full set of Plans and Drawings of proposed Alterations.

	and herewith submit a full set of Flans and Drawings of proposed Afterations.
1.	State how many buildings to be altered, One
2.	What is the Street or Avenue and the number thereof, an North sick of 9 st bet 33
3.	How much will the alteration cost, \$ 425,00
	PRESENT BUILDING.
	Give the following information as to the present building:
1.	Size of lot on which it is located, No. feet front, 29 ; feet rear, 29 ; feet deep, 24
	Size of building, No. of feet front, 28; feet rear, 24; feet deep, 24; No. of stories
	in height,
3.	Material of building, Brick & Story Material of front, Story front, Wood
4.	Whether roof is peak, flat, or mansard, Flat
5.	Depth of foundation walls, feet; thickness of foundation walls, feet; thickness of foundation walls,
	foundation walls, Stone
6.	Thickness of upper walls, 12 inches. Material of upper walls, 12 inches.
7.	Whether independent or party-walls,
8.	How the building is occupied, Stores & Jenement
	HOW TO BE ALTERED.
	IF RAISED OR BUILT UPON, Give the following information:
1.	
	How many stories will the building be when raised,
	How many feet high will the building be when raised,
	Will the roof be flat, peak, or mansard,
	story, inches.
5	Give size and material of floor beams of additional stories; story, ;
	story, x Distance from centres on tier, inches;
	tion in the
6.	How will the building be occupied, Storen & Jenement
***	so surface,
	IF EXTENDED ON ANY SIDE,
	Give the following information:
1.	Size of extension, No. feet front, ; feet rear, ; feet deep, ; No. of stories
	in height,; No. of feet in height,
2.	What will be the material of foundation walls of extension,
	feet. What will be the thickness, inches.
3.	Will foundation be laid on earth, rock, timber or piles,

IF THE FRONT, REAR, OR SIDE WALLS, OR ANY PORTION THERES. ARE TO BE TAKEN OUT AND REBUILT,

Give definite particulars, and state in what manner,

Brevent Store Windower to be removed Wing Store William
Brevert Store Windows To be removed. New Store Windows to be Mer To be put in 12: from face of Building Propert Clums into to be Mer (The nailing that to be for the land of free seal to remove the now of 22 in in midthe which will be a substitute for the plant of the second over consider of 22 in in midthe which will be a substitute for the plant of the second over consideration of 22 in in midthe which will be a substitute for the plant of the second of the s
(The nailing the lattom of the lover stong of present fire recape to to received, the non
of 22 per in wealth which will be a substitute for the platfordences
Owner, Seeing Johnston Address, 697 Leepington are
Architect, Long Sturtyhover Address, 226 & 41 of
Mason, Address, Address, 147 & 22 A
(The following must be signed by the party authorized to submit this detailed statement and the
necompanying plans and drawings:) New York. Unil /6 4 188.3
I do hereby agree that the provisions of the Building Law will be complied with in the alterations
of the building herein described, whether the same are specified herein or not. (SIGN HERE.) A. Wilkinson
(SIGN HERE.) CO. WELKINSON
NOTICE TO OWNERS, ARCHITECTS AND BUILDERS.
THE BUILDING LAW REQUIRES
1st.—All stone walls must be properly bonded. 2d.—All skylights, over 3 feet square, must be of iron and glass.
3d.—All buildings over 2 stories or above 25 feet in height, except dwellings and churches, must have iron shutters on every window and opening above the 1st story.
4th.—Fire escapes are required on all tenement, flat and apartment houses, office buildings, lodging houses and factories, and the balconies of such fire escapes must take in one window of each suite of apartments,
and as may be approved by the Inspector of Buildings. 5th.—All walls must be coped with stone or iron. If coped with stone, the stone must not be less than
2½ inches thick, and if with iron, the iron must not be less than ½ inch thick, and turned down at least 1½ inches at edges.
6th.—Roofs must be covered with fire-proof material. 7th.—All cornices must be fire proof.
8th.—All furnace and boiler flues must be constructed as directed by the Inspector of Buildings.
REPORT UPON APPLICATION.
Hire Acpartment, City of Aew York,
BUREAU OF INSPECTION OF BUILDINGS.
o the Inspector of Buildings: New York, April 17 1883
I respectfully report that I have thoroughly examined the foregoing described building and find the
ame to be built of but 5 stor es, 5 feet in height, 2 g feet front, 2 feet deep, feet deep, roof. I have thoroughly examined and measured the walls, and find the foundation walls to
e built of 20 inches thick; the upper walls are built of 12 inches thick,
nd J-J- feet in height, and that the mortar in said walls is hard and good, and that all
he walls arein a good and safe condition.
(The Examiner must here state what defects, if any, are in the walls, beams or other part of the building.)
There are no defect, in well or flow-
<i>y</i>
Frank Schaaf. Examiner
FINAL REPORT OF EXAMINER.
NEW YORK, June 1 188 3
Work was commenced on the within described building on the 27 day of April 188 3
and completed on the day of May 1883, and has been done in accordance with
he foregoing detailed statement, except as noted below.
Will Marrard Examiner.
REMARKS.

BUREAU OF INSPECTION OF BUILDINGS.

City and County	Plan No. 5/6, Building.
of Shirtorh ss.	1873
Levis Johnston	Residing at W. 796 Leverghin areum
	State of Shorton
do hereby depose and say that I am the	owner
of the premises known and designated as	. 109 East Smith Clint,
	2
in the City of New York; and that the work	proposed to be done, in accordance with the accom-
	premises is authorized by me, and that
Alfred & nich	ieon
	permit for the proposed work in huy behalf.
And I further depose and say, that no o	ther person or persons than myself, or those herein-
after named, with their several addresses, are in	n any manner interested in the said work, as owners,
executors, administrators or other legal represe	entatives
i	74 112
	6 1 . 131 1
	Commin
1 Section 1 Sect	
Subscribed and sworn to before me, this	
day of A.D., 188	and
Police	24 200
may cy con	of the same



BUREAU INS. OF BUILDINGS,

Received FEB 16 1892



APPLICATION TO ALTER, REPAIR, ETC.

Application is hereby made to alter as per subjoined detailed statement of specification for Alter-
ations, Additions or Repairs to buildings already erected, and herewith submit Plans and Drawings
of such proposed alterations; and do hereby agree that the provisions of the Building Law will be complied with, whether the same are specified herein or not.
(Sign here) Bruno H. Berger architect
NEW YORK, Febry 15th 1892
1. State how many buildings to be altered, One
2. What is the street or avenue and the number thereof? Give diagram of property.
109 East 9 Street 3. How much will the alteration cost? \$ 1500.00
GIVE THE FOLLOWING INFORMATION AS TO THE PRESENT BUILDING:
1. Size of lot on which it is located, No. of feet front, 30; feet rear, 30; feet deep, 24
2. Size of building, No. of feet front, 30; feet rear, 30; feet deep, 24. No. of stories
in height,
3. Material of building, Buck ; material of front, Buck
4. Whether roof is peak, flat, or mansard, Flat
5. Depth of foundation walls 8 feet; thickness of foundation walls, 20; materials
of foundation walls, Blue Stone
6. Thickness of upper walls,inches. Material of upper walls,
7. Whether independent or party walls, Independent
8. How the building is or was occupied, Stones in first story, Jenements above
No. Service Co.
IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION:
IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION:
IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION: 1. How many stories will the building be when raised?
IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION: 1. How many stories will the building be when raised? 2. How high will the building be when raised?
IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION: 1. How many stories will the building be when raised? 2. How high will the building be when raised? 3. Will the roof be flat, peak, or mansard? 4. What will be the thickness of wall of additional stories? 5. story, inches;
IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION: 1. How many stories will the building be when raised? 2. How high will the building be when raised? 3. Will the roof be flat, peak, or mansard?
IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION: 1. How many stories will the building be when raised? 2. How high will the building be when raised? 3. Will the roof be flat, peak, or mansard? 4. What will be the thickness of wall of additional stories? story, inches.
IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION: 1. How many stories will the building be when raised? 2. How high will the building be when raised? 3. Will the roof be flat, peak, or mansard? 4. What will be the thickness of wall of additional stories? story, inches; 5. Give size and material of floor beams of additional stories; 2d tier, Distance from centres on tier,
IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION: 1. How many stories will the building be when raised? 2. How high will the building be when raised? 3. Will the roof be flat, peak, or mansard? 4. What will be the thickness of wall of additional stories? 5. Give size and material of floor beams of additional stories; 2d tier, 2d tier, Distance from centres on inches;
IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION: 1. How many stories will the building be when raised? 2. How high will the building be when raised? 3. Will the roof be flat, peak, or mansard? 4. What will be the thickness of wall of additional stories? 5. Give size and material of floor beams of additional stories; 1. Ist tier, 2. Distance from centres on tier, inches; 6. How will the building be occupied?
IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION: 1. How many stories will the building be when raised? 2. How high will the building be when raised? 3. Will the roof be flat, peak, or mansard? 4. What will be the thickness of wall of additional stories? 5. Give size and material of floor beams of additional stories; 2d tier, 2d tier, Distance from centres on inches;
IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION: 1. How many stories will the building be when raised? 2. How high will the building be when raised? 3. Will the roof be flat, peak, or mansard? 4. What will be the thickness of wall of additional stories? 5. Give size and material of floor beams of additional stories; 1. Ist tier, 2. Distance from centres on tier, inches; 6. How will the building be occupied?
IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION: 1. How many stories will the building be when raised? 2. How high will the building be when raised? 3. Will the roof be flat, peak, or mansard? 4. What will be the thickness of wall of additional stories? story, inches; 5. Give size and material of floor beams of additional stories; 1st tier, x 2d tier, x Distance from centres on tier, inches; 6. How will the building be occupied?
IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION: 1. How many stories will the building be when raised? 2. How high will the building be when raised? 3. Will the roof be flat, peak, or mansard? 4. What will be the thickness of wall of additional stories? 5. Give size and material of floor beams of additional stories; 1. Size of extension, No. feet front, 1. Size of extension, No. feet front, 1. Size of extension, No. feet front, 1. No. of feet in height, 1. Size of extension, No. of feet in height,
IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION: 1. How many stories will the building be when raised? 2. How high will the building be when raised? 3. Will the roof be flat, peak, or mansard? 4. What will be the thickness of wall of additional stories? story, inches; story, inches. 5. Give size and material of floor beams of additional stories; 1st tier, x Distance from centres on tier, inches; inches; inches; inches. 6. How will the building be occupied? IF TO BE EXTENDED ON ANY SIDE, GIVE THE FOLLOWING INFORMATION. 1. Size of extension, No. feet front, ; feet rear, ; feet deep, ; No. of stories in height, ; No. of feet in height,
IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION: 1. How many stories will the building be when raised? 2. How high will the building be when raised? 3. Will the roof be flat, peak, or mansard? 4. What will be the thickness of wall of additional stories? 5. Give size and material of floor beams of additional stories; 1. Size of extension, No. feet front, 1. Size of extension, No. feet front, 1. Size of extension, No. feet front, 1. No. of feet in height, 1. Size of extension, No. of feet in height,

Owner George Sheiss Address 136 Eash 14th St.
Architect Bruno W. Berger Address Room to Bible House
Mason Gustav Staiger Address 152 Second ave
CarpenterAddress
REPORT UPON APPLICATION.
BUREAU OF INSPECTION OF BUILDINGS,
New York, 189 2. To the Superintendent of Buildings:
I respectfully report that I have thoroughly examined and measured the building, walls, etc.,
named in the foregoing application, and found the foundation wall to be built of
inches thick,feet below curb, the upper wallbuilt ofinches thick,
feet deep. Work 62 feet in height, and that the mortar in said wall is
hard and good, and that all the walls arein good and safe condition.
What is the nature of the ground?
What kind of sand was used in the mortar?
How is or was the building occupied?
(The Inspector must here state what defects, if any, are in the walls, beams or other part of the building.)
The " state the thickness of each wall in each and every story.)
Jamtalin mace 20. Close
121/2013 121
Eastily made over my in made trater frame in mobil out
1 thin 1 this is
Inspector.
THE BUILDING LAW REQUIRES:
THE BUILDING LAW REQUIRES: 1st—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass.
THE BUILDING LAW REQUIRES: 1st—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass. 3d—All buildings over two stories or above 25 feet in height, except dwellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st
THE BUILDING LAW REQUIRES: 1st—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass. 3d—All buildings over two stories or above 25 feet in height, except dwellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted.
THE BUILDING LAW REQUIRES: 1st—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass. 3d—All buildings over two stories or above 25 feet in height, except dwellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted. 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first, and on dwellings more than four
THE BUILDING LAW REQUIRES: 1st—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass. 3d—All buildings over two stories or above 25 feet in height, except dwellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted. 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built
THE BUILDING LAW REQUIRES: 1st—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass. 3d—All buildings over two stories or above 25 feet in height, except dwellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted. 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first, and on dwellings more than four stories in height, occupied by three or more families above the first floor, and on office buildings, hotels
THE BUILDING LAW REQUIRES: 1st—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass. 3d—All buildings over two stories or above 25 feet in height, except dwellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted. 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first, and on dwellings more than four stories in height, occupied by three or more families above the first floor, and on office buildings, hotels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows: BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE. BRACKETS must not be less than ½ 1½ inches wrought iron, placed edgewise, or 1¼ inch angle iron ½ inch thick, well braced, and not more than three feet apart, and the braces to brackets must be not less than ½ 1½ inches wrought iron, and must extend two-thirds of the width of the respective brackets or balconies.
THE BUILDING LAW REQUIRES: 1st—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass. 3d—All buildings over two stories or above 25 feet in height, except dwellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted. 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first, and on dwellings more than four stories in height, occupied by three or more families above the first floor, and on office buildings, hotels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows: BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE. BRACKETS must not be less than ½ 1½ inches wrought iron, placed edgewise, or 1¼ inch angle iron ½ inch thick, well braced, and not more than three feet apart, and the braces to brackets must be not less than ½ 1½ inches wrought iron, and must extend two-thirds of the width of the respective brackets or balconies.
THE BUILDING LAW REQUIRES: 1st—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass. 3d—All buildings over two stories or above 25 feet in height, except dwellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted. 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first, and on dwellings more than four stories in height, occupied by three or more families above the first floor, and on office buildings, hotels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows: BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE. BRACKETS must not be less than ½ 1½ inches wrought iron, placed edgewise, or 1¼ inch angle iron ½ inch thick, well braced, and not more than three feet apart, and the braces to brackets must be not less than ½ 1½ inches wrought iron, and must extend two-thirds of the width of the respective brackets or balconies.
THE BUILDING LAW REQUIRES: 1st—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass. 3d—All buildings over two stories or above 25 feet in height, except dwellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted. 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first, and on dwellings more than four stories in height, occupied by three or more families above the first floor, and on office buildings, hotels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows: BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE. BRACKETS must not be less than 1½ x 1½ inches wrought iron, placed edgewise, or 1½ inch angle iron ½ inch thick, well braced, and not more than three feet apart, and the braces to brackets must be not less than ½ inch square wrought iron, and must extend two-thirds of the width of the respective brackets or balconies. In all cases the brackets must go through the wall, and be turned down three inches. Brackets or New Bullings must be set as the walls are being built. When brackets are to be put on old houses, the part going through the wall shall not be less than one inch diameter, with screw nuts and washers not less than if we inches square and ½ inch thick. TOR RAILS—The top rail of balcony must be 1½ inch x ½ inch wrought iron or 1½ inch angle iron ¼ inch thick, well backed into the wall. In frame buildings the top rails must so through the studding and be secured on the inside by washers and nuts as above. Filaling-in Balas—The tilling-in bars must be not less than ½ inch rough tiron of 1½ inch angle iron ¼ inch thick, well taked dinto the wall. In frame buildings the top rails must go t
Ist—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass. 3d—All buildings over two stories or above 25 feet in height, except dwellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted. 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first, and on dwellings more than four stories in height, occupied by three or more families above the first floor, and on office buildings, hotels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows: BRACKETS must not be less than ½ x ½ inches wrought iron, placed edgewise, or ½ inch angle iron ½ inch thick, well braced, and not more than three feet apart, and the braces to brackets must be not less than ½ inch square wrought iron, and must extend two-chirds of the width of the respective brackets or balconies. BRACKETS ON New Buildings, hotels and the braces to brackets must be to less than ½ inch equare wrought iron, and must extend two-chirds of the width of the respective brackets or balconies. BRACKETS ON New Buildings and washers not less than 10 l
Ist—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass. 3d—All buildings over two stories or above 25 feet in height, except dwellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted. 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first, and on dwellings more than four stories in height, occupied by three or more families above the first floor, and on office buildings, lottels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows: BRACKETS MUST NOT BE LESS THAN THREE FEET WIDE. BRACKETS ON NEW BUILDINGS must be set than ½ inch square wrought iron, and must extend two-thirds of the width of the respective brackets or balconies. In all cases the brackets must go through the wall, and be turned down three inches. BRACKETS ON NEW BUILDINGS must be set as the walls are being built. When brackets are to be put on old houses, the part going through the wall shall not walls, and be secured by units and 4 inch square wrought iron, or 1½ inch angle iron 1½ inch thick, and in all cases must go through the walls. TOP RAILS.—The top rail of belony must be 13½ inch x ½ inch x ½ inch wrought iron or 1½ inch angle iron 1½ inch thick, and in all cases must go through the wall. Shall have been allowed and the secured by units and 4 inch square wrought iron or 1½ inch angle iron 1½ inch made inches from centres, and well riveted to the top and bottom rails. STAILS.—The Balling-in bars must be not less than 1½ inch rough it would be connected at angles by the use of cast iron. Borrook Rails—The filling-in bars must be not less than 1½ inch rough it or or 1½ inch angle iron 1½ inch and inches or strings. Steps ma
Ist—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass. 3d—All buildings over two stories or above 25 feet in height, except dwellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted. 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first floor, and on office buildings more than four stories in height, occupied by three or more families above the first floor, and on office buildings, hotels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows: BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE. Brackers must not be less than 15 x 13/2 inches wrought fron, placed edgewise, or 13/2 inch angle iron 14 inch thick, well braced, and not more than three feet spart, and the braces to brackets must be not less than 3/2 inch square wrought iron, and must extend two-thirds of the width of the respective brackets or beloonies. In all cases the brackets must be not less than 3/2 inch square wrought iron, and must extend two-thirds of the width of the respective brackets or beloonies. Brackers on New Buildings and be turned down three inches. Brackers on New Buildings are seen as the walls are being built. When brackets are to be put on old houses, the part going through the wall shall not be less than one inch diameter, with serve wutta and washers not less than 14 with the case square and 1/4 inch thick, and in all cases must go through the wall shall not be seen than 15 inches with a wall of the control of the study of
Ist—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass. 3d—All buildings over two stories or above 25 feet in height, except dwellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted. 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first, and on dwellings more than four stories in height, occupied by three or more families above the first floor, and on office buildings, hotels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows: BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE. BRACKETS must not be less than 14 x 134 inches wrought from, and must extend two-chirds of the width of the respective brackets or balconies. In all cases the brackets must be not less than 34 inch square wrought from, and must extend two-chirds of the width of the respective brackets or balconies. Top Rans.—The profile of belong must be ask as the walls are being built. When brackets are lost put on 4 inch thick, and in all cases must go through the walls, and be secured by nuts and 4 inch square washers, at least 36 inch thick, and no top rail shall be connected at angles by the use of cast from. Borrow Rans.—The profile of belong must be 143 inch x 45 inch wrought from or 155 inch angle from 44 inch thick, and in all cases must go through the walls had be secured by nuts and 4 inch square washers, at least 36 inch thick, and no top rail shall be connected at angles by the use of cast from. Borrow Rans.—The prail of belong must be 143 inch x 45 inch wrought from 0 155 inch angle from 44 inch thick, well benefit and 1 inches wide, and constructed of 4x 345 inch wrought iron 4 inch thick, well benefit and inches from ce
Ist—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass. 3d—All buildings over two stories or above 25 feet in height, except duellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted. 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first, and on dwellings more than four stories in height, occupied by three or more families above the first floor, and on office buildings, hotels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows: BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE. BRACKETS must not be less than 1/4 x1/4 inches wrought from, placed edgewise, or 1/4 inch angle iron 1/4 inch thick, well braced, and not more than three feet apart, and the braces to brackets must be not less than 8/2 inch equare wrought from, and must extend two-thirds of the width of the respective brackets or balconies. In all cases the brackets must be not less than 8/2 inch equare wrought from, and must extend two-thirds of the width of the respective brackets or balconies. Brackets are to make the brackets must be not less than 8/2 inch equare wrought from 1/4 inch thick, well braced, and not more than three feet spent, and the bracket on the sum step through the wall, and be secured by muts and 4 inch square washers, at least 9/3 inch hungarian did inch thick. Brackets on New Buttanyes must be set as the walls are being built. When branches are to put on old houses, the part going through the wall and be secured on the less than 1/2 inch wyought from 1/4 inch kick, well leaded into the wall. In frame builtings the top and the secure of the same will be applied to the wall. In frame builtings the top and the secure
Ist—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass. 3d—All buildings over two stories or above 25 feet in height, except dwellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted. 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first, and on dwellings more than four stories in height, occupied by three or more families above the first, and on office buildings, hotels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows: BRACKETS must not be less than 15 135 inche square wrought iron, and must extend two-thirds of the width of the respective brackets or baconies. BRACKETS on New Brundros must be set than 35 inch square wrought iron, and must extend two-thirds of the width of the respective brackets or baconies. BRACKETS on New Brundros must be set washes not less than it we inches square and 15 inch hick, well braced, and not more than three feet spart, and the braces to brackets must be not less than 15 inch we will one that the will shall not be less than 15 inch we will be shall not be less than 15 inch we will one that the will shall not be less than 15 inch we will one that the will shall not be less than 15 inch we will one that the will shall not be less than 15 inch we will one to 115 inch angle iron 15 inch will not the wall shall not be less than 15 inch we will one to 115 inch angle iron 15 inch will not he wall. In time buildings the top wall shall not be set to 15 inch angle iron 15 inch will not the wall of the wall shall not be set than 15 inch we will not 15 inch angle iron 15 inch will not the wall. In time buildings the top trail of belong must be set 15 inch 15 inch will no
Ist—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass. 3d—All buildings over two stories or above 25 feet in height, except dwellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted. 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first, and on dwellings more than four stories in height, occupied by three or more families above the first floor, and on office buildings, hotels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows: BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE. BRACKETS must not be less than 1\(\frac{1}{2}\) x 1\(\frac{1}{2}\) inches wrought fron, placed efgewise, or 1\(\frac{1}{2}\) inch angle from 4 inch flick, well braced, and not more than three feet apart, and the braces to brackets must be not less than 3\(\frac{1}{2}\) inch square wrought fron, and must extend two-chirds of the width of the respective brackets or balconies. In all cases the brackets must be not less than 4\(\frac{1}{2}\) inch square wrought fron, and must extend two-chirds of the width of the respective brackets or balconies. Tor Raits.—The tori inf or belong must be 1\(\frac{1}{2}\) inch square wrought fron, and must extend two-chirds of the width of the respective brackets or balconies. Tor Raits.—The tori inf of belong must be 1\(\frac{1}{2}\) inch in a plei inch in the control of belong the wall shall not be less than one inch diameter, with serve must and washers not less than five inches square and \(\frac{1}{2}\) inch thick, and in all cases must go through the wall shalls and be secured by must and 4 inch square wrought iron, inch thick, and in all cases must go through the wall shalls and be se
1st—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass. 3d—All buildings over two stories or above 25 feet in height, except dwellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted. 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first floor, and on dwellings more than four stories in height, occupied by three or more families above the first floor, and on office buildings, hotels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows: BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE. BRACERTS must not be less than 15 the set than 35 inches winds the brace to brackets must be not less than 35 inches winds the brace to brackets must be not less than 35 inches winds the brace to brackets must be not less than 35 inches winds. BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE. BRACERTS must not be less than 15 inches winds the brackets are to be put on old houses, the part going through the belies than one inch diameter, with serew miles than 35 inches winds. Too Rates—The top mil of below; must have a company the brackets are to be put on old houses, the part going through the miles of the put
1st—All stone walls must be properly bonded. 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass. 3d—All buildings over two stories or above 25 feet in height, except durellings, school houses, and churches, on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted. 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first foor, and on office buildings, lotels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows: Balconies Must not be less than 15 135 inches wrought iron, placed edgewise, or 135 inch angle iron 14 inch thick, well braced, and not more than three feet apart, and the braces to brackets must be not less than 35 inches wides in the brace of brackets must be not less than 35 inches wides in the brace of brackets must be not less than 35 inches wides in the brackets are to be put on old houses, the part going through the wall hall not be be secured by mits and it is not become the chee square and jee by the use of cast from. Brackets on New Branches must be at as the wall are better in the chee square and plet by the use of cast from. Brackets on New Branches and 4 inch square wrought in the chee square and plet by the use of cast from the wall, and be secured by mits and better in the chee square and in the square with the student of the wall hall not be be secured to a bracket or rail of balcony must be 134 inch x 16 inch wrought iron. 34 inch thick, and in all cases must be to the wall, and be secured to a bracket or extra cast and will have a star with a star of the wall of the wall and the secured to a bracket or extra cross bar at the bottom. All status must have a 34 inch hand rail of wrought from, seed on those with of strings, or 95 inch round ton, doubte rungs,

1800

	4	What will be the base, stone or concrete?			
		and how laid,If concrete, give thickness,			
	5.	What will be the sizes of piers? What will be the sizes of the base of piers?			
		What will be the thickness of upper walls? 1st story, inches; 2d story inches;			
		3d story, inches; 4th story, inches; 5th story, inches;			
		6th story, inches; 7th story, inches; from thence to top, inches;			
		and of what materials to be constructed,			
	7.	State whether independent or party-walls			
		With what material will walls be coped?			
		What will be the materials of front? If of stone, what kind?			
		Give thickness of front ashlar Give thickness of backing			
	10.	Will the roof be flat, peaked or mansard?			
		What will be the materials of roofing?			
		Give size and material of floor beams, 1st tier, ; 2d tier,			
		x ; 3d tier, x ; 4th tier, x			
		5th tier,; 7th tier,; 7th tier,;			
		; roof tier, x State distance from centres on 1st tier,			
		inches; 2d tier,inches; 5th tier,inches; 5th tier,			
		inches; 6th tier, inches; 7th tier, inches; roof tier, inches			
	13.	If floors are to be supported by columns and girders, give the following information: Size and material			
		of girders under 1st floor,			
		Size and material of columns under first floor,			
		under each of the upper floors,			
	14	If the front, rear or side walls are to be supported, in whole or in part, by iron girders or lintels, give			
	11.				
		definite particulars,			
	75				
	LU.	If girders are to be supported by brick piers and columns, state the size of piers and columns.			
	1 6.	How will the extension be connected with present or main building?			
	16.	How will the extension be connected with present or main building?			
		How will the extension be connected with present or main building?			
		How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy			
	17.	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor.			
	17. 18.	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. 3. 1. Bergar			
	17. 18.	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. The Berger F ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE			
	17. 18.	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. 3. 7. Bergar F ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED:			
It is form	17. 18. I	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. 3. 1. Bengar F ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED: Building Will BE OCCUPIED:			
It is form	17. 18. I	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. 3. 1. Bengar F ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED: Building Will BE OCCUPIED:			
It is form	17. 18. I	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. 3. 1. Bengar F ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED: Building Will BE OCCUPIED:			
It is form	17. 18. I	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. 3. 1. Bengar F ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED: Building Will BE OCCUPIED:			
It is form	17. 18. I	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. 3. 7. Bergar F ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED:			
It is for to take or new star iron gu to be and be and	17. 18. I volume of the control of	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. 3. 1. Bengar F ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED: und to remove the partitions in the 1st 2st stong and the stangar hading from 1 to 3st stong to build be from 1 to 2st stong and from 2 to 3st stong. I have form 1 to 2st stong and from 2 to 3st stong. I have no partition in 2 stong to meet an a removing from front to man are center of building number 2 stong floor beauto. Stong identity with bridle notes.			
It is for to take or new star iron gu to be and be and	17. 18. I volume of the control of	How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. B. Berger F ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED: Building Will BE OCCUPIED: Med to remain the partitions in the partitions in the part stong and the standard hading from! 1 to 3 to briefly the floor beauty and from 2 to 3 tong 2 put up new partitions in 2 stong 2 must an a remaining from front to pray in center of building render 2 thought on the stong floor beauty and the will have 12 to must be made in the stong floor beauty and from the proof of the stong floor beauty floor. THE FRONT, REAR, OR SIDE WALLS, OR ANY PORTION THEREOF. ARE TO BE			
It is form to take or new star iron gu to be and be and	17. 18. I offer in continue of the continue	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. B. H. Benger F ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED: Building Will BE OCCUPIED: The partitions in the 1th 2 stony and to much many frame, same to be 3x12 planed to apart on cutters. To build we from 1th 2 stony and from 2 to 3 stony. I put up new partitions in 2 stony, a much an a summary from front to near we center of brailding, muche 1 stony floor beauto, stony floor beauto, the private floor beauto, stony floor beauto, the private stony floor beauto, the first beauto, with briefly provided irons. THE FRONT, REAR, OR SIDE WALLS, OR ANY PORTION THEREOF, ARE TO BE TAKEN OUT AND REBUILT, GIVE DEFINITE PARTCULARS, AND STATE IN WHAT MANNER.			
It is form to take or new star iron gu to be and be and	17. 18. I offer in each in e	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. B. H. Benger F ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED: Building Will BE OCCUPIED: The partitions in the 1th 2 stony and to much many frame, same to be 3x12 planed to apart on cutters. To build we from 1th 2 stony and from 2 to 3 stony. I put up new partitions in 2 stony, a much an a summary from front to near we center of brailding, muche 1 stony floor beauto, stony floor beauto, the private floor beauto, stony floor beauto, the private stony floor beauto, the first beauto, with briefly provided irons. THE FRONT, REAR, OR SIDE WALLS, OR ANY PORTION THEREOF, ARE TO BE TAKEN OUT AND REBUILT, GIVE DEFINITE PARTCULARS, AND STATE IN WHAT MANNER.			
It is form to take or new star iron gu to be and be and	17. 18. I offer in each in e	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. B. H. Benger F ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED: Building Will BE OCCUPIED: The partitions in the 1th 2 stony and to much many frame, same to be 3x12 planed to apart on cutters. To build we from 1th 2 stony and from 2 to 3 stony. I put up new partitions in 2 stony, a much an a summary from front to near we center of brailding, muche 1 stony floor beauto, stony floor beauto, the private floor beauto, stony floor beauto, the private stony floor beauto, the first beauto, with briefly provided irons. THE FRONT, REAR, OR SIDE WALLS, OR ANY PORTION THEREOF, ARE TO BE TAKEN OUT AND REBUILT, GIVE DEFINITE PARTCULARS, AND STATE IN WHAT MANNER.			
It is form to take or new star iron gu to be and be and	17. 18. I offer in each in e	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. B. H. Benger F ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED: Building Will BE OCCUPIED: The partitions in the 1th 2 stony and to much many frame, same to be 3x12 planed to apart on cutters. To build we from 1th 2 stony and from 2 to 3 stony. I put up new partitions in 2 stony, a much an a summary from front to near we center of brailding, muche 1 stony floor beauto, stony floor beauto, the private floor beauto, stony floor beauto, the private stony floor beauto, the first beauto, with briefly provided irons. THE FRONT, REAR, OR SIDE WALLS, OR ANY PORTION THEREOF, ARE TO BE TAKEN OUT AND REBUILT, GIVE DEFINITE PARTCULARS, AND STATE IN WHAT MANNER.			
It is form to take or new star iron gu to be and be and	17. 18. I offer in each in e	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. B. H. Benger F ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED: Building Will BE OCCUPIED: The partitions in the 1th 2 stony and to much many frame, same to be 3x12 planed to apart on cutters. To build we from 1th 2 stony and from 2 to 3 stony. I put up new partitions in 2 stony, a much an a summary from front to near we center of brailding, muche 1 stony floor beauto, stony floor beauto, the private floor beauto, stony floor beauto, the private stony floor beauto, the first beauto, with briefly provided irons. THE FRONT, REAR, OR SIDE WALLS, OR ANY PORTION THEREOF, ARE TO BE TAKEN OUT AND REBUILT, GIVE DEFINITE PARTCULARS, AND STATE IN WHAT MANNER.			
It is form to take or new star iron gu to be and be and	17. 18. I offer in each in e	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. B. H. Benger F ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED: Building Will BE OCCUPIED: The partitions in the 1th 2 stony and to much many frame, same to be 3x12 planed to apart on cutters. To build we from 1th 2 stony and from 2 to 3 stony. I put up new partitions in 2 stony, a much an a summary from front to near we center of brailding, muche 1 stony floor beauto, stony floor beauto, the private floor beauto, stony floor beauto, the private stony floor beauto, the first beauto, with briefly provided irons. THE FRONT, REAR, OR SIDE WALLS, OR ANY PORTION THEREOF, ARE TO BE TAKEN OUT AND REBUILT, GIVE DEFINITE PARTCULARS, AND STATE IN WHAT MANNER.			
It is form to take of new star iron gu to be and be and	17. 18. I offer in each in e	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. B. H. Benger F ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED: Building Will BE OCCUPIED: The partitions in the 1th 2 stony and to much many frame, same to be 3x12 planed to apart on cutters. To build we from 1th 2 stony and from 2 to 3 stony. I put up new partitions in 2 stony, a much an a summary from front to near we center of brailding, muche 1 stony floor beauto, stony floor beauto, the private floor beauto, stony floor beauto, the private stony floor beauto, the first beauto, with briefly provided irons. THE FRONT, REAR, OR SIDE WALLS, OR ANY PORTION THEREOF, ARE TO BE TAKEN OUT AND REBUILT, GIVE DEFINITE PARTCULARS, AND STATE IN WHAT MANNER.			
The 12 the in show	17. 18. I offee victorial for the state of the state o	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. 3. A. Berger F ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED: Building Will be occupied? If so occupied the standard from 1 the 30 clong the 1 through the fractions in the 1 through the standard from 2 through the standard from the			
The 12 the in show	17. 18. I offee victorial for the state of the state o	How will the extension be connected with present or main building? How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor. State who will superintend the alterations. 3. 1. Berger F ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED: med to remove the partitions in the 1th 2th story and the standard from 1th 3th 3th 5th 5th 5th 5th 5th 5th 5th 5th 5th 5			

IF TO BE EXTENDED ON ANY SIDE GIVE THE FOLLOWING INFORMATION.

Whish or

FIRE DEPARTMENT CATY OF NEW YORK. BUREAU OF INSPECTION OF BUILDINGS.

City and County	Plan No. Building
of New York ss.	Danabag
a fly	
I Tronge The	USS residing at 136 Gash 14th S
in the City of Mero	York State of New York &
	he Executor of the Estate of
iler	
A of the premises known and designated a	s 109 East 19th Sheet "
in the City of New York; and that the w	ork proposed to be done upon the said premises, in accordanc
with the accompanying plans and specific	ations, is authorized by MZ and that
Bruno W Berger	Colit
	on for a permit for the proposed work inbehal
with their several addresses, are in any ma	y that no other person or persons than those hereinafter named anner interested in the said work, as owners, executors, adminis
trators or other legal representatives.	and the same work, as owners, executors, adminis
trators or other legal representatives.	dininis caccitors, adminis
trators or other legal representatives.	and the same word, as owners, executors, adminis
trators or other legal representatives.	adminis
trators or other legal representatives.	owners, executors, adminis
trators or other legal representatives.	
trators or other legal representatives.	a Ca A
Subscribed and sworn to before me, this 15	i Genger Heir
trators or other legal representatives.	i Genger Heir
Subscribed and syorn to before me, this 15 day of February A. D. 189	i Genger Heir
Subscribed and sworn to before me, this 15	i Genger Heir
Subscribed and syorn to before me, this 15 day of February A. D. 189	i Genger Heir

DEPARTMENT OF BUILDINGS

	BOROUGH	OF Wanhatta	n , CITY	OF NEW Y	ORK
JHATTAN Municipal Bldg, Manhattan	BROOKLYN Municipal Bldg., Brooklyn	Bronx	BRONX County Bldg., course & E. 161st St. Bronx	QUEE 21-10 49th A L. I. Ci	Avenue, Boro Hall,
	plication must be ty n plans and section		in triplicate. All p	proposed work u	nder this application must be
			1937		
		No. 1702			ON No193
SPRINKLER A	APPLICATION	No. LLUS	193 BUIL	DING NOTIO	CE No193
LOCATION	109 East	9th. St		Block	555 Lot 40
				Ward	Vol
Number of Building	ouilding: 30	. AND B. CONVE Number of Stories. Ft. front 30	FICATIONS RTED MULTIPLE 4 Ft. rear as ClassB Mul	DEPADO	Vol. Vol. Vol. PECEIVED MENT OF 45 JILDINGS MANHATTAN
Present occupancy_			an of Stor Objecting		
How to be occupied			Same		
	INDICATE I	BELOW NUMBER	OF PROPOSED S	SPRINKLER HE	
	HALLS LAN	DINGS SOFFITS	CLOSETS UN	NDER STAIRS	COOKING
Cellar					APAN .
`asement					524
1st story					5.4 5
2nd story	4	1			—
3rd story	5	1			200
4th story	5	1	O CANADA		
5th story	57	1			D
6th story	10	3	7.	2 Comme	
NOT THE RESERVE OF		t. or the tenement hou Water Supply, Gas as		Yes M.D. tificate stating the	V.
Size of tap		2			
Size of Main		21			
Material of sprinkle	r piping		black wrough	t irom	
Material of pipe fitti	ings		cast i	ron	
Method of protecting	g sprinkler piping ag	ainst frost action	halls h	ALLE STATE OF BUILDING LONG AND ALLE STATE	
Area sprayed by each	h sprinkler head		less 100	sq.ft.	
Any structural chan	ges?	No. If so, given	ve number of altera	ation application o	r building notice above
		RE	MARKS		A STORES TO STORE

Request permission to install two additional sprinklers in excess of the allowed 20 heads due to the very small area covered by each head, also the excessive water pressure which shows on inspection 29 lbs. The building is only 23'0x30'0in area.

DEPARTMENT OF BUILDINGS

	DU	KŲ	JUI	OI.
1/4				

Wanhattan , CITY OF NEW YORK

MANHATTAN Municipal Bldg., Manhattan

BROOKLYN Municipal Bldg., Brooklyn

BRONX Bronx County Bldg., Grand Concourse & E. 161st St., Bronx

QUEENS 21-10 49th Avenue, L.M. City

RICHMOND Boro Hall St. George, S. I.

NOTICE-This Application must be TYPEWRITTEN and filed in triplicate

FOR CLASS A and B CONVERTED MULTIPLE DWELLINGS PLECEIVED

AFFIDAVIT

DEC 2 2 1937

SPRINKLER APP	LICATION No	19337	AIT APPI	DEPARTMENT BOROUGH OF	OF BUILDINGS
PERMIT No.	170)2_193	B. N.	No.	manggillan
LOCATION	No.109 East	9th StBLOCK	555	LOT	40
		WARD		VOL	ACTURE HOTELY
The State of		New Y	ork City I	Dec 21, 1937	193

To THE COMMISSIONER OF BUILDINGS:

Application is hereby made for approval of the plans and specifications herewith submitted, and made a part hereof, for the SPRINKLER SYSTEMS of the building herein described,—with the understanding that if no work is performed hereunder within one year from the time of issuance, this approval shall expire by limitation as provided by law; and the applicant agrees to comply with all the rules and regulations of the Department of Buildings for the Borough of and with every other provision of law relating to this subject in effect at this date.

Work under this approval will not be commenced until a permit has been secured, and satisfactory evidence that compensation insurance has been obtained in accordance with the provisions of the Workmen's Compensation Law.

Examined and Recommended for Approval on	193/
	J. Malsh Exempses
APPROVED 193	Daniel Commen
	Commissioner of Buildings, Borough of

STATE AND CITY OF NEW YORK SS.: COUNTY OF NewYork

William J.Farrell

Typewrite Name of Applicant.

40 W.33rd. St

being duly sworn, deposes and says: That he resides at Number , in the Borough of

Man.

in the City of in the State of

N.Y. N.Y

, in the County of , that he is

N.Y. agent for

owner in fee of all that certain lot, piece or parcel of land, shown on the diagram annexed hereto and made a part Man. City of New York, aforesaid, and known and 109 East 9th. St hereof, situate, lying and being in the Borough of designated as Number

and hereinafter more particularly described; that the work proposed to be done upon the said premises, in accordance with the accompanying detailed statement in writing of the specifications and plans of such proposed work-including all amendments to the same which may be filed hereafter-is duly authorized to be performed by MOttos Schulman or Lease

and that

William J. Farrell is

duly authorized by the aforesaid owner to make application for the approval of such detailed statement of specifications and plans (and amendments thereto) in his



Deponent further says that the full names and residences, street and number, of the owner or owners of the said land, and also of every person interested in said building, structure, premises, wall, platform, staging or flooring, either as owner, lessee, or in any representative capacity, are as follows: Afreds Other Schulman ____ No.. 246-3rd. Ave owner ... No... The said land and premises above referred to are situate at, bounded and described as follows, viz.: BEGINNING at a point on the north side of E.9th. St distant 100 west from the corner formed by the intersection of feet E.9th. St and 3rd.Ave west 30 feet; thence north 23 running thence feet: east 30 south 23 thence feet; thence feet to the point or place of beginning. Sworn to before me, this... AUTHORIZATION OF OWNER __DEPOSES AND SAYS: That____ Borough of ... State of..... that he is....owner of in the City of New York, all that certain piece or lot of land situated in the Borough of... and located on the..... ...side of.... on said street; that the multiple dwelling in which the installation is to be and known as No.... made___upon said premises will be in accordance with the annexed specifications and plans submitted herewith for the approval of the Department of buildings and that___ is duly authorized by said owner... to make application in said owner's behalf in compliance with Chapter 713 of the Laws of 1929 for the approval of such specifications and plans. Note:—This clause to be used only when the person executing this authorization is not the sole owner of the premises described herein. He further says that the full names and residences, street and number, of the owner or owners of the said land, and of every person having an interest in said premises and projected multiple dwelling either as owner. lessee, or otherwise, as required by Section 300 of the Multiple Dwelling Law, are as follows: (Address) (Relation to premises) (Name) (Address) (Name) (Relation to premises) WORKMEN'S COMPENSATION INSURANCE Contractor ... Policy Number

Conipany ..

Form 8-240M-701190(63)

ORIGINAL

THE CITY OF NEW YORK DEPARTMENT OF BUILDINGS

MANHATTAN Municipal Bldg., New York, N. Y. 10007 BROOKLYN Municipal Bldg., Brooklyn, N. Y. 11201 BRONX 1932 Arthur Avenue, Bronx, N. Y. 10457 QUEENS 120-55 Queens Blvd., Kew Gardens, N. Y. 11424 RICHMOND Boro Hall, St. George, N. Y. 10301

PLUMBING, MECHANICAL EQU	JIPMENT AND	TANK INSTALLATION
	SPRINKLE.	R: Re: 5ECT. 194 m. D. L
BLOCK 555 LOT40	MISC/	134
FEES REQUIRED FOR	F.P.	*ECETYED FEB 14 1966
N.B. ALT. No	SPR	CITY OF NEW YORK BOROUGH TO MANHATTAN
	DO NO	T WRITE IN THIS SPACE
Street No. and LOCATION 109 EAST 9TH STREET Owner 171 HOLDING CORP DESAW HERBERT WEINGAST, VICE PRES Architect. JOHN B RESCHEE Contractor COMPENSATION INSURANCE has been Workmen's Compensation Law as follows:	Address 10 Address 27 Address Address	9 East 9th Street, N Y 5 West 43rd Street, N Y 36
To The Borough Superintendent: Application is hereby made on behalf of the own submitted, and made a part hereof, for the erection, the understanding that if no work is performed hereund expire by limitation as provided by law; and the applicable thereto in effect at this date.	ner-lessee for approval alteration or installati- ler within one year fro	on of the building therein described,—with
Applicant (Sign Here) Multiple Manual	Address	276 WEST 4380 ST., N. Y. 36
Examined and Recommended APR 1 = 1966 APPROVED APPROVED 19		Boronyin Bushing
Initial fee payment— 2nd payment of fee to be collected before permit is in Verified by	ssued—Amount \$ Date	IVONE
ADDITIONAL FEES REQUIRED(Yes o	r Mal	UNT \$
Work Included Herein: Plumbing? Sprinkler?	K. Standpipe? I	Gasoline Tank Installation Fuel Oil? or Fuel Oil (Bulk)?
Is this a new or old building? QLD. Give character of construction BRICK Dimensions: Stories High. 5 Feet High. How occupied CLASS B, MD & STORE Is application made to remove a violation or order of a	No. of Families	Class: 3 30 Feet Deep. 24 Give No. Housing Div
How to be occupied CLASS B, MD HCD & STO Estimated Cost # 450.00 (Any variation in estimated cost shall be filed and reco Exemptions If exemption from payment of fee is claimed, state clear	rded as an amendment)
NOTICE—This application must be typewr this application must be shown on plans and sec ator pipes should be designated by numbers or may be considered as one stack, and so numbers be specified. When new fixtures are to be confines must be shown on the plan. Minor alterat in this form.	itten and filed in quition. All vertical lingle letters. A soil or vertical in all the contract of the contrac	adruplicate. All proposed work under nes of soil, waste, leader and refriger- waste line and its attendant vent line terations, NEW WORK ONLY should nes the location and diameter of said

Form 21 (Rev. 10/62)-143M-701190(63) 114



THE CITY OF NEW YORK

DEPARTMENT OF BUILDINGS

MANHATTAN BROOKLYN BRONX QUEENS RICHMOND Municipal Bldg., Municipal Bldg., 1932 Arthur Ave., 120-55 Queens Blvd., Boro Hall, New York, N. Y. 10007 Brooklyn, N. Y. 11201 Bronx, N. Y. 10457 Kew Gardens, N. Y. 11244 St. George, N. Y. 10301

NOTICE --- This Application must be TYPEWRITTEN and filed in TRIPLICATE

Minor Structures, Minor Alterations and Repairs, Elevator Repairs, Drop Curb, Fire Escapes, Miscellaneous

and the second s	BUILDING NOTICE
Block 555 Lot 40 DISTRICT (under building zone resolution)	RECEIVED
Use R7-2 Height Area	DEPARTMENT OF BUILDINGS
Is sidewalk shed or fence required. No	P. & FEB211966552
SIDE WALK SHED. No sidewalk shed or fence shall interfere with visibility or operation of any traffic light. The Department of Traffic shall be notified whenever such structure is to be erected within seventy five (75) feet of a traffic light. Failure to comply may be cause for revocation of this approval and any permit issued thereon.	CITY OF NEW YORK BOROUGH OF MANHATTAN DO NOT WRITE IN THIS SPACE
LOCATION 109 East 9th Street 1001-0" wes (Give Street Number)	t of 3rd Avenue Manhattan
THIS IS NOT A WORK PERMIT. A PERMIT MUST	BE OBTAINED BEFORE WORK IS STARTED
State proposed work in detail: Erect new stud partit.	ions for new sanitary facilities
Date of Construction 🖫 Before 1938 🗌 Af	
Indicate class of construction:	
☐ Class 1—Fireproof ☐ Class 2—Fire pro	tected
☐ Class 4—Wood frame ☐ Class 5—Metal	☐ Class 6—Heavy timber
Number of stories high	•
How occupied MD Class B	
Is application made to remove a violation? Yes Item 644	
How to be occupied Same	
Estimated Cost \$\$1,500.00 (includes plumbing)	
(Any variation in estimated cost shall be filed and recorded	as an amendment.)
Exemptions	
If exemption from payment fee is claimed, state clearly the ba	sis of claim
T. 101.10	
Initial fee payment—	
	56 (6)
2nd payment of fee to be collected before a permit is issued-	-Amount \$ 2-) - / 0 = / 0
Verified by	Date
17	ENTER OF MICHOLDIA
ADDITIONAL FEES REQUIRED (Yes or No)	AMOUNT \$
VERIFIED BY	DATE
1. The sum of the fees indicated on the first and second receipts shall represent the estimated cost shall be recorded as an amendment. If any question are no permit shall be issued unless adjusted to the spit-faction of the departure	ent the total fee. Any variation on contemplated work or change affecting see in connection with the estimated cost or with the adequacy of the fee,

Bribery is a Crime: A person who gives or offers a bribe to any employee of the City of New York, or an employee who takes or solicits a bribe, is guilty of a felony punishable by imprisonment for ten years or by a fine of \$4,000, or more, or both. Penal Law, Section 378 and 1826.

KEMARKS OR SKETCH:

Cut cui D	Total	Splay	
Length in Feet		-F/	Length in Feet
Deposit (\$), e Buildings, to insure the proper construct	either in cash or ion of the sidewal	certified check, payab k and curb.	le to the order of the Department of
Refer to ALT.	19		
Donald D. Fisher of ob Fisher & Donald D. Fisher, (Typewrite Name of Applican	Architects		
States that his office is	225 Laf	gyette Street	Borough of
Manhattan City of Ne described, and is duly authorized to with submitted, and made a part her understanding that if no work is perfor shall expire by limitation as provided be Code and all laws and regulations applied the work to be done is duly authorized.	make this applice of, for the work med hereunder way law; and the a cable to the erection	ation for approval of k to be done in the livithin one year from applicant agrees to com-	building therein described,—with the the time of issuance, this approval
			ers or lessees of said premises are:
Owner 171 Holding Corp.		Address 109 E.	9th Street, N.Y.C.
Pres. Eleanor Wein	gast V. Pres	. Herbert Weinga	est spenied 400%
Lessee		Address	
Dated Feb. 12, 1966.	(Sign her		Applicant S
	, j=		If Licensed Architect or Professional Engineer, affix seal.
AUTHORIZATION OF OWNER:	I hereby state th	at I have authorized t	he applicant to file this application for
Lase rager steers	a a	Signature of	Alcen Jet V. F
Falsification of any statement is an off by a fine of not more than five hundred	ense under Secti I dollars (\$500.00	on 982-9.0 of the Ad)) or imprisonment of	ministrative Code and is punishable not more than sixty (60) days or both.
5-	3-66	10011	1 0
For Approval on 3 13	6 3 19	Music	Pa. Jacobery
Approved1	9 V 5	1966	rough Superintendent
	1466-23	Data signed of	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Work commenced		Date Signed off	
			and that the work indicated has been
	e above report is	true in every respect	and that the work indicated has been