

IF THE BUILDING IS TO BE OCCUPIED AS A APARTMENT OR TENEMENT HOUSE, GIVE THE FOLLOWING PARTICULARS.

1. State how many families are to occupy each floor, and the whole number in the house; also, if any part is to be used as a store or for any other business purposes, state the fact, *4 on 2nd floor & 2 on 1st floor & 2 stores on 1st floor in all 18 families*
2. What will be the heights of ceilings? 1st story *11* feet; 2d story, *9.3* feet; 3d story, *9.3* feet; 4th story, *9.3* feet; 5th story, *9.3* feet; 6th story _____ feet; 7th story, _____ feet.
3. How are the hall partitions to be constructed and of what materials? *Ordinary Stud Partitions*

Owner, *Gonast Weil & Bernard Meyer* Address *305 East 57th St*
 Architect, *Geo B Pelham* Address *1481 B. way*
 Mason, } *John Van Dolsen* Address *Belmont 88th St & 10th Ave*
 Carpenter, } Address _____

IF A WALL OR PART OF A WALL ALREADY BUILT IS TO BE USED, FILL UP THE FOLLOWING.

The undersigned give notice that _____ intend to use the _____ wall of building _____

as party wall in the erection of the building hereinbefore described, and respectfully requests that the same be examined and a permit granted therefor. The foundation wall _____ built of _____ inches thick, _____ feet below curb; the upper wall _____ built of _____ inches thick; _____ feet deep, _____ feet in height.

(Sign here) _____

NOTE.—In making application for the erection of buildings the following drawings must be furnished: Plans of each and every story, front, rear and side elevations, and longitudinal and transverse erections. All plans must be drawn to a uniform scale and must be on tracing cloth, properly designated and colored.

THE BUILDING LAW REQUIRES :

- 1st—All stone walls must be properly bonded.
- 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass.
- 3d—All buildings over two stories or above 25 feet in height, *except dwellings, school houses, and churches*, on streets less than 30 feet wide, must have iron shutters on *every* window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted.
- 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first, and on dwellings more than four stories in height, occupied by three or more families above the first floor, and on office buildings hotels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows :

BRACKETS must not be less than $\frac{1}{2}$ x $1\frac{1}{2}$ inches wrought iron, placed edgewise, or $1\frac{1}{2}$ inch angle iron, well braced, and not more than three feet apart, and the braces to brackets must be not less than $\frac{1}{2}$ inch square wrought iron, and must extend two-thirds of the width of the respective brackets or balconies. In all cases the brackets must go through the wall, and be turned down three inches.

BRACKETS ON NEW BUILDINGS must be set as the walls are being built. When brackets are to be put on old houses, the part going through the wall shall not be less than one inch diameter, with screw nuts and washers not less than five inches square and $\frac{1}{2}$ inch thick.

TOP RAILS—The top rail of balcony must be $1\frac{1}{2}$ inch x $\frac{1}{2}$ inch wrought iron, and in all cases must go through the walls, and be secured by nuts and 4 inch square washers, at least $\frac{1}{2}$ inch thick, and no top rail shall be connected at angles by the use of cast iron.

BOTTOM RAILS—Bottom rails must be $1\frac{1}{2}$ inch x $\frac{1}{2}$ inch wrought iron, well leaded into the wall. In frame buildings the top rails must go through the studding and be secured on the inside by washers and nuts as above.

FILLING-IN-BARS—The filling-in bars must be not less than $\frac{1}{2}$ inch round or square wrought iron, placed not more than 6 inches from centres, and well riveted to the top and bottom rails.

STAIRS—The stairs in all cases must be not less than 18 inches wide, and constructed of $\frac{1}{2}$ x $3\frac{1}{2}$ inch wrought iron sides or strings. Steps may be of cast iron of the same width of strings, or $\frac{5}{8}$ inch round iron, double rungs, and well riveted to the strings. The stairs must be secured to a bracket on top and rest on and be secured to a bracket or extra cross bar at the bottom. All stairs must have a $\frac{1}{2}$ inch hand rail of wrought iron, well braced.

FLOORS—The flooring of balconies must be of wrought iron $1\frac{1}{2}$ x $\frac{3}{4}$ inch slats placed not over $1\frac{1}{2}$ inches apart, and secured to iron battens $1\frac{1}{2}$ x $\frac{3}{4}$ inch, not over three feet apart and riveted at the intersection. The openings for stairways in all balconies shall not be less than 20 inches wide and 36 inches long, and have no covers.

DROP LADDERS—Drop ladders from lower balconies where required shall not be less than 14 inches wide, and shall be made of $1\frac{1}{2}$ x $\frac{3}{4}$ inch sides and $\frac{5}{8}$ inch rungs of wrought iron. In no case shall a drop ladder be more than 12 feet in length. In no case shall the ends of balconies extend more than nine inches over the brackets.

SCUTTLE LADDERS—Ladders to scuttles shall be constructed in all cases the same as the stairs or step-ladders from balconies of fire escapes.

THE HEIGHT OF RAILING around balconies shall not be less than two feet nine inches.

No Fire Escape will be approved by this Bureau if not in accordance with above specifications.

- 5th—All walls must be coped with stone or terra cotta. If coped with stone, the stone must not be less than $2\frac{1}{2}$ inches thick; and if with terra cotta, the terra cotta must be made with proper lap joints.
- 6th—Roofs must be covered with fire-proof material.
- 7th—All cornices must be fire-proof.
- 8th—All FURNACE FLUES OF DWELLING HOUSES shall have at least eight inch walls on each side, No furnace flue shall be of less size than eight inches square, or four inches wide and sixteen inches long, inside measure. If preferred, the furnace flues may be made of cast iron or fire-clay pipe of proper size built in the walls, with an air space of not less than one inch between said pipes, and four inches of brick wall on the outside.
All flues not built for furnace or boiler flues must be altered to conform to the above requirements before they are used as such.
- 9th—No iron beam, lintel, or girder, intended to span an opening over eight feet, intended to support a wall, shall be used for that purpose, *until tested and approved as provided by law.*

LOT 44

BOROUGH OF Manhattan

CITY OF NEW YORK

DEPARTMENT OF BUILDINGS HOUSING & BUILDINGS

MANHATTAN Municipal Bldg., Manhattan

BROOKLYN Municipal Bldg., Brooklyn

BRONX Bronx County Bldg., Grand Concourse & E. 161st St. Bronx

QUEENS 21-10 49th Avenue

RICHMOND Boro Hall, St. George, S. I.

RECEIVED MAR 10 1938

NOTICE—This Application must be TYPEWRITTEN and filed in TRIPLE COPY.

Use for Specifications of "ALTERED" BUILDINGS

ALTERED BUILDINGS

PERMIT No. 19

BLOCK No. 393

LOT No. 44

APPLICATION No. 762 1938

WARD No.

VOL. No.

LOCATION 383 East 10th Street

DISTRICT (Under building zone resolution) USE Business HEIGHT 1 1/2 AREA B

SPECIFICATIONS

- (1) NUMBER OF BUILDINGS TO BE ALTERED one
Any other building on lot or permit granted for one? no
Is building on front or rear of lot? front
(2) ESTIMATED COST OF ALTERATION: \$ 300.00
(3) OCCUPANCY (in detail): Store, Multiple Dwelling Class A Tenement

Table with columns: STORY (include Cellar and basement), BEFORE ALTERATION (APTS., ROOMS, USE), AFTER ALTERATION (LIVE LOAD, NO. OF PERSONS, APTS., ROOMS, USE). Rows include Cellar, 1st Fl., 2nd Fl., 3rd Fl., 4th Fl., 5th Fl.

Handwritten notes: No C.O. to be issued with this application. See Com. to app 1/4. Large diagonal stamp: RECEIVED

If building is to be occupied other than dwelling with ordinary store on the first floor, give permit number under which it was erected or legally converted.

- (4) SIZE OF EXISTING BUILDING: At street level 25 feet front 50 feet deep; At typical floor level 25 feet front 50 feet deep; Height 5 stories 55 feet
(5) SIZE OF BUILDING AS ALTERED: At street level Same feet front Same feet deep; At typical floor level Same feet front Same feet deep; Height Same feet deep
(6) CHARACTER OF PRESENT BUILDING: Frame— Non-fireproof— Yes 2 Fireproof—

(7) STATE GENERALLY IN WHAT MANNER THE BUILDING WILL BE ALTERED:

Remove partition, erect new partition, remove store front, erect brick wall at front first story as shown.

If the building is to be raised in height or if the occupancy is changed so that the floor loads will be increased, the following information must be given as to the EXISTING BUILDING and the thickness of existing walls and size of footings must be clearly shown on the plans.

(8) FOUNDATIONS: Character of Soil (State one of the materials as described in Building Code, Section 231, Subdivision 2)

Material of Foundation Walls
Thickness of Walls
Depth Below Curb

(9) UPPER WALLS: Material

Kind of Mortar
Any Ashlar
Thickness of Walls

(10) PARTY WALLS: Any to be used?

Thickness of Walls

If building is to be enlarged or extended, the following information as to NEW WORK must be given:

(11) FOUNDATIONS: Character of Soil (State one of the materials as described in Building Code, Section 231, Subdivision 2)

Material of Foundation Walls
Thickness of Walls
Depth Below Curb

(12) UPPER WALLS: Material

Kind of Mortar
Any Ashlar
Thickness of Walls

(13) PARTY WALLS: Any to be used?

Thickness of Walls

(14) FIREPROOFING: Material and Thickness

For Columns
For Girders
For Beams

(15) INTERIOR FINISH: Material

Floor Surface
Trim, Sash, Doors, etc.
Plaster

(16) OUTSIDE WINDOW FRAMES AND SASH: Material

EXAMINED AND RECOMMENDED
FOR APPROVAL ON _____

193 _____

Examiner

APPROVED _____

193

Commissioner of Buildings, Borough of