			-	10.0	Miller
	Form 152-1929 ALT. APPLICATION (SPECI	FICATIONS-SHEET AD	EALL OF ALL		8Å-2060-29-1.S
			EAU OF BUIL	LDINGS	•
	BOI	REAUOF	BUIEDIN	GSK	· ·
	BOROLICH	DE MANUATTA	ed MAR 29 1930	NEW YORK	
	BOROUGH	OF MANHATTA	THE BORC	NEW IORK	
	NOTICE-This Applica		MANHATT	field in TRIPLICA	TE.
	"SPECIFICATIONS-SHEET A" (I "SPECIFICATIONS-SHEET B" (I	Form 152) must be	filed with EVER	V Alteration Appli	cation.
	in height or occupancy char one side.	nged so as to incre	ase floor loads, o	or if building is to	be enlarged o
		the second			4
	ALT. APPLICATION No.	625	1930		
	ALL APPLICATION No	)	108-20.2	BLOCK 399	LOT58
	LOCATION #157 East Srd	Street N/S	100 foot Pe	at at language	
	LOCATION 1101 Habit of		T00 1691 18		<u>A</u>
	DISTRICT (under building zone reso	lution) UseBud:	iness	leight 13 A	rea
	Examined 4-9	1030	Ø,	V	12
			Timu-	للمعمدة بملتزم بسرائي استانياتهم	Eraminer.
	(]as	s A, Multiple	dwalling T		-
$\mathcal{E}$			-	3	
	<u>5F1</u>	ECIFICATIO	NS-SHEEI	A	2.4
	(1) NUMBER OF BUILDINGS TO BE	ALTERED			
	Any other building on lot or p	ermit granted for or	ne? No	1	3.1
	(2) ESTIMATED COST OF ALTERATION	N: \$4000.00		2	12 -
	(3) Occupancy (in detail): Class	e a Kultinle	Dwelling	Tesamest	
		n families, 1			ŝ.
		(integral			2
	Of building as altered One	Store and Se	ven Familie	s, Tenement	
		1		8	
	(4) Size of Existing Building:	1		+	
њ.,	At street level At typical floor level	22.5	feet front feet front	50	feet de
	Height		stories	50 40	feet
	(5) SIEP OF BUILDING AS ALTERED:		a	-	2
	At street level At typical floor level	22.5 22.5	feet front feet front	50	feet dee feet dee
	Height	4	stories	50 40	feet
1 19	(6) CHARACTER OF CONSTRUCTION O			, 1-1/2, B	
		dinary Brick		[Frame, Ordinary or	
	(7) NUMBER OF OCCUPANTS (in each case of factories):	1			separately in th
		About 28 pe:	rsons (Dwell	ing)	
		I		3022	1
			<i>.</i>		
	(8). STRATE CONDUCT TO THE MA	NNER THE PLATER		m. Mba -C	
	(3) STATE GENERALLY IN WHAT MA first floor to be removed the upper well to be supp	and replaced	i with plate	glass store	wall, X front X
	I beams. One new toilet a	nd hoth to h	TETTA GO	runns, and th	wo 12" 31.
	to be placed in the basem in side wall third and for	ent, third an	id fourth fl	OOTE. Windows	to be at
	in side wall third and for which belongs to the some	urth ILCORS	on them outo	adjoining p	roperty
	proof end glazed with with	re glass, New	v lath and p	laster partit	tions to
	which belongs to the same proof and glazed with wi: be built as shown on the	re glass, New	v ratu and p	laster partit	E IIIE pr tions to

