6024B-03-25M(B)-Form 2-1908

Applicant must indicate the Building Lines clearly and distinctly on the Dra.

Borough President of the Borough of Manhattan, In The City of New York.

> EE BUREAU OF BUILDINGS FOR THE BOROUGH OF MANHATTAN, Office, No. 220 FOURTH AVENUE,

S. W. Corner 18th Street.

APPLICATION TO ALTER, REPAIR, ETC.

Application is hereby made to the Superintendent of Buildings of The City of New York for the Borough of Manhattan for the approval of the detailed statement of the specifications and plans herewith submitted for the alteration or repair of the building herein described. All provisions of the law shall be complied with in the alteration or repair of said building, whether specified herein or not.

> THE CITY OF NEW YORK, BOROUGH OF MANHATTAN, Sept 11"

· **	What is the exact location thereof? (State on what street or avenue; the side thereof, the number of fee
	from the nearest street or avenue, and the name thereof)
37 E	- 10 433 East 6 - Sheet
3.	How was the building occupied? as close and lucine.
	How is the building to be occupied? as at present.
4.	Is the building on front or rear of lot? from Is there any other building erected on lot o
	permit granted for one? Size x ; height How
	Give distance between same and
	proposed buildingfeet,
5.	Size of lot? 25 feet front; 25 feet rear; 90 feet deep.
6.	ize of building which it is proposed to alter or repair? 25 feet front; 25 feet rear
	feet rear
	feet deep. Number of stories in height?
7.	ighest point?55
7.	Depth of foundation walls below curb level? 10:0" Motorial of foundation and
7.	Depth of foundation walls below curb level? 10:0" Material of foundation walls Thickness of foundation walls? front 20 inches
7. S.	Depth of foundation walls below curb level? 10:0" Material of foundation walls? Thickness of foundation walls? front 20 inches ear 20 inches; side 20 inches; party 20 inches.
	Depth of foundation walls below curb level? 10:0" Material of foundation walls Thickness of foundation walls? front 20 inches
	Depth of foundation walls below curb level? Thickness of foundation walls? front 20 inches ar 20 inches; side 20 inches; party 20 inches. In ashlar, give kind and thickness. Thickness of upper walls?
S.	Depth of foundation walls below curb level? Thickness of foundation walls? front 20 inches ar 20 inches; side 20 inches; party 20 inches. Interial of upper walls? If ashlar, give kind and thickness thickness of upper walls: Basement: front inches; rear inches; side inches; party inches; part
).	Depth of foundation walls below curb level? Thickness of foundation walls? front 20 inches ar 20 inches; side 20 inches; party 20 inches. Interial of upper walls? Thickness of foundation walls? front 20 inches are 20 inches; party 20 inches. If ashlar, give kind and thickness thickness of upper walls: Description of the service o
S.	Depth of foundation walls below curb level? 10:0" Material of foundation walls? Thickness of foundation walls? front 20 inches party 20 inches. In a shlar, give kind and thickness Thickness of upper walls? Thickness of upper walls? If a shlar, give kind and thickness inches party inches party inches; st story: "Thickness of upper walls: "Thickness of upper walls? "Thickness of upper walls? "Thickness of upper walls: "Th
S.	Depth of foundation walls below curb level? 10:0" Material of foundation walls? Store: Thickness of foundation walls? front 20 inches are 20 inches; side 20 inches; party 20 inches. In ashlar, give kind and thickness. Thickness of upper walls? If ashlar, give kind and thickness. Thickness of upper walls? If ashlar, give kind and thickness. Thickness of upper walls? If ashlar, give kind and thickness. Thickness of upper walls? If ashlar, give kind and thickness. Thickness of upper walls? If ashlar, give kind and thickness. Thickness of upper walls? If ashlar, give kind and thickness. Thickness of upper walls? If ashlar, give kind and thickness. Thickness of upper walls? If ashlar, give kind and thickness. Thickness of upper walls? If ashlar, give kind and thickness. Thickness of upper walls? If ashlar, give kind and thickness. Thickness of upper walls? If ashlar, give kind and thickness.
<u>.</u>	Depth of foundation walls below curb level? 10:0" Material of foundation walls Store: Thickness of foundation walls? front 20 inches party 20 inches. In a shlar, give kind and thickness for thickness of upper walls? Discharge inches; rear inches; side inches; party inches. Sasement: front inches; rear inches; side inches; party inches. Sasement: front inches; rear inches; side inches; party inches. Sasement: front inches; rear inches; side inches; party inches. Sasement: front inches; rear inches; side inches; party inches. Sasement: front inches; rear inches; side inches; party inches. Sasement: front inches; rear inches; side inches; party inches. Sasement: front inches; rear inches; side inches; party inches.
<u>.</u>	Depth of foundation walls below curb level? Thickness of foundation walls? front 20 inches ar 20 inches; side 20 inches; party 20 inches. Itaterial of upper walls? Thickness of upper walls? If ashlar, give kind and thickness Thickness of upper walls: Basement: front inches; rear inches; side inches; party inches at story: Thickness of upper walls? Thickness of foundation walls? front inches. If ashlar, give kind and thickness Thickness of upper walls: Thickness of upper walls? Thickness of foundation walls? Thickness of fou

If the Front, Rear or Side Walls, or any portion thereof, are to be taken out and rebuilt, give definite particulars, and state in what manner: 47. It is proposed to cut windows apenings in front and rear If altered Internally, give definite particulars, and state how the building will be occupied: 48. It is proposed to build no. c partitions on the various 49. How much will the alteration cost? If the Building is to be occupied as a Flat, Apartment or Lodging House, give the following particulars: 50. Is any part of building to be used as a store or for any other business purpose, if so, state for what? 3d Floor 6th Floor 51. How many families will occupy each? Height of ceilings? 53. How basement to be occupied? How made water-tight ? Will cellar or basement ceiling be plastered ?______How ?____ **54.** How will cellar stairs be enclosed? How cellar to be occupied ? **56.** How made water-tight?....

57. Will shafts be open or covered with louvre skylights full size of shafts?

Size of each shaft?____

58.	3. Dimensions of water-closet windows?		
	Dimensions of windows for living rooms?		
5 9.	Of what materials will hall partitions be constructed?		
60.	Of what materials will hall floors be constructed?		
61.	. How will hall ceilings and soffits of stairs be plastered		
62.	d. Of what material will stairways be constructed?	der was the state of the state	
	Give sizes of stair well holes?		
63.	If any other building on lot, give size; front	; rear	; deep:
	stories high ; how occupied		
	of lot; material		
	How much space between it and proposed building !	· E	TO SERVICE MANAGEMENT OF THE SERVICE
64.	. How will floors and sides of water closets to the height	of 16 inches be made wa	terproof ?
65.			
	3d floor ; 4th floor ; 5	5th floor	; 6th floor
66.	. This building will safely sustain per superficial foot	upon the first floor	lbs.; upon 2d floor
	lbs.; upon 3d Hoorlbs.		
	lbs.; upon 6th floorlbs.		
	lbs.		
		W W	6 24 11
Owr	wner, Louis Geissles A	ddress. 4-39 Cas	6 Street.
Arc	rchitect, Charles Stegmaner	" 168 Las	191d Sheel
Sup	perintendent,		
Mas	ason,		
Com	arporter	"	

HOUSING &

DEPARTMENT OF BUILDINGS

BOROUGH	OF	Manhattan	,

CITY OF NEW YORK

MANHATTAN Municipal Bldg., Manhattan

PERMIT No.

APPLICATION No.

BROOKLYN Municipal Bldg., Brooklyn BRONX
Bronx County Bldg.,
Grand Concourse & E. 181st St.,
Bronx

QUEENS 21-19 49th Avenue, L. I. City RICHMOND Boro Hall, St. George, S. I.

NOTICE—This Application must be TYPEWRITTEN and filed in TRIPLICATE and ONE copy sworn to by Applicant.

BUILDING NOTICE

Application for Minor Structures, Minor Alterations and Repairs

WARD No.

ZONE	GI CONTRACTOR OF THE CONTRACTO
USE	
HEIGHT	Borough of Manhattan , Crry of New YorkMarch 3rd, 193
AREA	
To the Commissione	ER OF BUILDINGS:
part hereof, for the er work is performed he as provided by law; a Buildings for the Bor	hereby made for approval of the plans and specifications herewith submitted, and made rection or alteration of the building—therein described,—with the understanding that if recunder within one year from the time of issuance, this approval shall expire by limitation and the applicant agrees to comply with all the rules and regulations of the Department rough of Manhattan, all provisions of the Building Code of the City of New Yor provision of law relating to the erection or alteration of said building—in effect at this day. APPLICAN
SEPA	RATE PERMIT SHOWING PROOF OF
	KMEN'S COMPENSATION, MUST BE
PROC	CURED BEFORE COMMENCING WORK.
24	(HERE STATE DEFINITELY NATURE OF PROPOSED WORK)
I propose to	(HERE STATE DEFINITELY NATURE OF PROPOSED WORK) remove present wood stairs from first to second floor
500 OC 0	remove present wood stairs from first to second floor ce with new iron stairs same width.
500 OC 0	remove present wood stairs from first to second floor
500 OC 0	remove present wood stairs from first to second floor ce with new iron stairs same width.
500 OC 0	remove present wood stairs from first to second floor ce with new iron stairs same width.
5 To 10 10 10 10 10 10 10 10 10 10 10 10 10	remove present wood stairs from first to second floor ce with new iron stairs same width. spend headers throughout language and
5 To 10 10 10 10 10 10 10 10 10 10 10 10 10	remove present wood stairs from first to second floor ce with new iron stairs same width.
5 To 10 10 10 10 10 10 10 10 10 10 10 10 10	remove present wood stairs from first to second floor ce with new iron stairs same width. spend headers throughout language and
500 OC 0	remove present wood stairs from first to second floor ce with new iron stairs same width. spend headers throughout language and
500 OC 0	remove present wood stairs from first to second floor ce with new iron stairs same width. spend headers throughout language and
and repla //4/38 / Lio a	remove present wood stairs from first to second floor ce with new iron stairs same width. spend headers throughout language and
and repla /////38 ///// ///////////////////////	remove present wood stairs from first to second floor ce with new iron stairs same width. State das Fund in 109651 esp. 3-2717 polyments. Jumines standfunction of the second floor and constit.
and repla [14/38 phoa 5/16/38 Plan Is this a new or old	remove present wood stairs from first to second floor ce with new iron stairs same width. The first dis Fund in 18965/ esp: 3-2717 Show in the first wood stairs from first to second floor Character of construction. Brick non fireproof.
and repla //// 38 // Solution Is this a new or old If old building, give of	remove present wood stairs from first to second floor ce with new iron stairs same width. The formal of the first of the
Is this a new or old If old building, give of Number of stories hig How occupied Sam	remove present wood stairs from first to second floor ce with new iron stairs same width. The formal of the first of the
Is this a new or old If old building, give of Number of stories hig How occupied Sam	remove present wood stairs from first to second floor ce with new iron stairs same width. The first distributed in 109651 exp. 3-2737 State distributed in 109651 exp. 3-2737 Show in the first to second floor Construction Brick non fireproof Character of construction Brick non fireproof Character of violation? No