

555

~~Bureau of Buildings~~
FORM No. 2-1892.

Original 136

BUREAU OF BUILDINGS

Received APR 6 1892 2560

Plan No. 555

APPLICATION TO ALTER, REPAIR, ETC. 28

Application is hereby made to alter as per subjoined detailed statement of specification for Alterations, Additions or Repairs to buildings already erected, and I herewith submit Plans and Drawings of such proposed alterations; and I do hereby agree that the provisions of the Building Law will be complied with, whether the same are specified herein or not.

B 430

L 44

(Sign here) Adam Weber
P. Kutzger & Kobl.
Archts.

NEW YORK, April 6th 1892

1. State how many buildings to be altered. One
2. What is the street or avenue and the number thereof? Give diagram of property. No 111 St. Marks Place?
3. How much will the alteration cost? \$ 500⁰⁰/₁₀₀

GIVE THE FOLLOWING INFORMATION AS TO THE PRESENT BUILDING:

1. Size of lot on which it is located, No. of feet front, 25' 4"; feet rear, 25' 4"; feet deep, 100'
2. Size of building, No. of feet front, 25' 2"; feet rear, 25' 2"; feet deep, 52 No. of stories in height, Bar + 5 Stories; No. of feet in height from curb level to highest point of beams, 54
3. Material of building, Brick; material of front, Brick
4. Whether roof is peak, flat, or mansard, flat
5. Depth of foundation walls, 12 feet; thickness of foundation walls, 24; materials of foundation walls, Stone
6. Thickness of upper walls, 16 x 12 inches. Material of upper walls, Brick
7. Whether independent or party walls, party wall at Eastern side
8. How the building is or was occupied, 12 families

IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION:

1. How many stories will the building be when raised?
2. How high will the building be when raised?
3. Will the roof be flat, peak, or mansard?
4. What will be the thickness of wall of additional stories? story, inches; story, inches.
5. Give size and material of floor beams of additional stories; 1st tier, x 2d tier, x Distance from centres on tier, inches; tier inches.
6. How will the building be occupied?

IF TO BE EXTENDED ON ANY SIDE, GIVE THE FOLLOWING INFORMATION.

1. Size of extension, No. feet front,; feet rear,; feet deep,; No. of stories in height,; No. of feet in height,
2. What will be the material of foundation walls of extension? What will be the depth? feet. What will be the thickness? inches.
3. Will foundation be laid on earth, sand, rock, timber or piles?

111 St. Marks Place
4/6/92

IF TO BE EXTENDED ON ANY SIDE GIVE THE FOLLOWING INFORMATION.

4. What will be the base, stone or concrete?..... If base stones, give size and thickness and how laid,..... If concrete, give thickness,.....
5. What will be the sizes of piers?..... What will be the sizes of the base of piers?.....
6. What will be the thickness of upper walls? 1st story,..... inches ; 2d story..... inches ; 3d story,..... inches ; 4th story,..... inches ; 5th story,..... inches ; 6th story,..... inches ; 7th story,..... inches ; from thence to top,..... inches ; and of what materials to be constructed,.....
7. State whether independent or party-walls..... If party-walls give thickness thereof.....
8. With what material will walls be coped?.....
9. What will be the materials of front?..... If of stone, what kind?..... Give thickness of front ashlar..... Give thickness of backing.....
10. Will the roof be flat, peaked or mansard?.....
11. What will be the materials of roofing?.....
12. Give size and material of floor beams, 1st tier,.....,..... x..... ; 2d tier,..... x..... ; 3d tier,.....,..... x..... ; 4th tier,.....,..... x..... 5th tier,.....,..... x..... ; 6th tier,.....,..... x..... ; 7th tier,.....,..... x..... ; roof tier,.....,..... x..... State distance from centres on 1st tier,..... inches ; 2d tier,..... inches ; 3d tier,..... inches ; 4th tier,..... inches ; 5th tier,..... inches ; 6th tier,..... inches ; 7th tier,..... inches ; roof tier,..... inches
13. If floors are to be supported by columns and girders, give the following information : Size and material of girders under 1st floor,.....,..... x..... under each of the upper floors,..... Size and material of columns under first floor,..... under each of the upper floors,.....
14. If the front, rear or side walls are to be supported, in whole or in part, by iron girders or lintels, give definite particulars,.....
15. If girders are to be supported by brick piers and columns, state the size of piers and columns.....
16. How will the extension be connected with present or main building?.....
17. How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor.....
18. State who will superintend the alterations.....
19. If buildings are to be removed, state the number.....

IF ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED :

.....
.....
.....
.....

IF THE FRONT, REAR, OR SIDE WALLS, OR ANY PORTION THEREOF, ARE TO BE TAKEN OUT AND REBUILT, GIVE DEFINITE PARTICULARS, AND STATE IN WHAT MANNER :

Present front wall to be taken down to 1st story and rebuilt same with 12" brick wall in cheap sand mortar.

Owner Adam Weber Address 203 Second Avenue
 Architect Kurtz & Kohl Address Cor. 3rd Ave & 7th Street
 Mason Bliss Regelman Address 546 E. 13 Street
 Carpenter _____ Address _____

REPORT UPON APPLICATION.

BUREAU OF INSPECTION OF BUILDINGS,
 NEW YORK, April 11 1892

To the Superintendent of Buildings:

I respectfully report that I have thoroughly examined and measured the building, walls, etc., named in the foregoing application, and found the foundation wall.....to be built of Stone 24 inches thick, 10 feet below curb, the upper wall.....built of Brick 16, 12 inches thick, 52 feet deep. 54 feet in height, and that the mortar in said wall is hard and good, and that all the walls are _____ in good and safe condition.

What is the nature of the ground? Good

What kind of sand was used in the mortar? "

How is or was the building occupied? Dwelling

(The Inspector must here state what defects, if any, are in the walls, beams or other part of the building.)

The " " state the thickness of each wall in each and every story.)

Foundation walls	stone	24"
Basement	brick	16
1 story	"	12
2 "	"	12
3 "	"	12
4 "	"	12
5 "	"	"

John P. Reilly Inspector.

THE BUILDING LAW REQUIRES:

- All stone walls must be properly bonded.
- All skylights having a superficial area of more than 9 square feet must be of iron and glass.
- All buildings over two stories or above 25 feet in height, *except dwellings, school houses, and churches,* streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted.
- Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first, and on dwellings more than four stories in height, occupied by three or more families above the first floor, and on office buildings, hotels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows:

BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE.

BRACKETS must not be less than 1/2 x 1 3/4 inches wrought iron, placed edgewise, or 1 3/4 inch angle iron 1/4 inch thick, well braced, and not more than three feet apart, and the braces to brackets must be not less than 3/4 inch square wrought iron, and must extend two-thirds of the width of the respective brackets or balconies. In all cases the brackets must go through the wall, and be turned down three inches.

BRACKETS ON NEW BUILDINGS must be set as the walls are being built. When brackets are to be put on old houses, the part going through the wall shall not be less than one inch diameter, with screw nuts and washers not less than five inches square and 1/2 inch thick.

TOP RAILS.—The top rail of balcony must be 1 3/4 inch x 1 1/2 inch wrought iron or 1 1/2 inch angle iron 1/4 inch thick, and in all cases must go through the walls, and be secured by nuts and 4 inch square washers, at least 3/8 inch thick, and no top rail shall be connected at angles by the use of cast iron.

BOTTOM RAILS.—Bottom rails must be 1 1/4 inch x 3/8 inch wrought iron or 1 1/2 inch angle iron 1/4 inch thick, well leaded into the wall. In frame buildings the top rails must go through the studding and be secured on the inside by washers and nuts as above.

FILLING-IN BARS.—The filling-in bars must be not less than 1/2 inch round or square wrought iron, placed not more than 6 inches from centres, and well riveted to the top and bottom rails.

STAIRS.—The stairs in all cases must be not less than 18 inches wide, and constructed of 1/4 x 3 1/2 inch wrought iron sides or strings. Steps may be of cast iron of the same width of strings, or 5/8 inch round iron, double rungs, and well riveted to the strings. The stairs must be secured to a bracket on top and rest on and be secured to a bracket or extra cross bar at the bottom. All stairs must have a 3/4 inch hand rail of wrought iron, well braced.

FLOORS.—The flooring of balconies must be of wrought iron 1 1/4 x 3/8 inch slats placed not over 1 1/4 inches apart, and secured to iron battens 1 1/2 x 3/8 inch, not over three feet apart and riveted at the intersection. The openings for stairways in all balconies shall not be less than 20 inches wide and 30 inches long, and have no covers.

DROP LADDERS.—Drop ladders from lower balconies where required shall not be less than 14 inches wide, and shall be made of 1 1/2 x 3/8 inch sides and 5/8 inch rungs of wrought iron. In no case shall a drop ladder be more than 12 feet in length. In no case shall the ends of balconies extend more than nine inches over the brackets.

SCUTTLE LADDERS.—Ladders to scuttles shall be constructed in all cases the same as the stairs or step-ladders from balconies of fire escapes.

THE HEIGHT OF RAILING around balconies shall not be less than two feet nine inches.

~~No~~ No Fire Escape will be approved by this Bureau if not in accordance with above specifications.

- 5th—All walls must be coped with stone or terra cotta. If coped with stone, the stone must not be less than 2 1/2 inches thick; and if with terra cotta, the terra cotta must be made with proper lap joints.
- 6th—Roofs must be covered with fire-proof material.
- 7th—All cornices must be fire-proof.
- 8th—All FURNACE FLUES OF DWELLING HOUSES shall have at least eight inch walls on each side. No furnace flues shall be of less size than eight inches square, or four inches wide and sixteen inches long, inside measure. If preferred, the furnace flues may be made of cast iron or fire-clay pipe of proper size built in the walls, with an air space of not less than one inch between said pipes, and four inches of brick wall on the outside.
 All flues not built for furnace or boiler flues must be altered to conform to the above requirements before they are used as such.
- 9th—No iron beam, lintel, or girder, intended to span an opening over eight feet, intended to support a wall, shall be used for that purpose, *until tested and approved* as provided by law.

Applicant must indicate the Building Line or Lines clearly and distinctly on the Drawings.

B 436
L 41

Office of the Borough President of the Borough of Manhattan,
In The City of New York.

THE BUREAU OF BUILDINGS FOR THE BOROUGH OF MANHATTAN,
Office, No. 220 FOURTH AVENUE,
S. W. Corner 18th Street.

Plan No. 328

APPLICATION TO ALTER, REPAIR, ETC.

Application is hereby made to the Superintendent of Buildings of The City of New York for the Borough of Manhattan for the approval of the detailed statement of the specifications and plans herewith submitted for the alteration or repair of the building herein described. All provisions of the law shall be complied with in the alteration or repair of said building, whether specified herein or not.

Adam Weber
(Sign here) per. *[Signature]* Architects.

THE CITY OF NEW YORK

BOROUGH OF MANHATTAN, February 7th, 1905.

LOCATION AND DESCRIPTION OF PRESENT BUILDING.

- State how many buildings to be altered One
- What is the exact location thereof? (State on what street or avenue; the side thereof, the number of feet from the nearest street or avenue, and the name thereof) Northerly side of St. Marks place 225' west of Avenue A. 111 St. Marks Place.
- How was the building occupied? Tenement
How is the building to be occupied? Tenement
- Is the building on front or rear of lot? front Is there any other building erected on lot or permit granted for one? _____ Size _____ x _____; height _____ How occupied? _____ Give distance between same and proposed building _____ feet.
- Size of lot? 25 feet front; 25 feet rear; 93'10" feet deep.
- Size of building which it is proposed to alter or repair? 25 feet front; 25 feet rear; 52'8-1/2" feet deep. Number of stories in height? 5 Height from curb level to highest point? 59'0"
- Depth of foundation walls below curb level? 10'0" Material of foundation walls? _____ Thickness of foundation walls? front 1'8" inches; rear 1'8" inches; side 1'8" inches; party 1'8" inches.
- Material of upper walls? Brick If ashlar, give kind and thickness _____
- Thickness of upper walls:
Basement: front 16 inches; rear 16 inches; side 16 inches; party 16 inches.
1st story: " 12 " " 12 " " 12 " " 12 "
2d story: " 12 " " 12 " " 12 " " 12 "
3d story: " 12 " " 12 " " 12 " " 12 "
4th story: " 12 " " 12 " " 12 " " 12 "
5th story: " 12 " " 12 " " 12 " " 12 "
6th story: " _____ " " _____ " " _____ " " _____ "
- Is roof flat, peak or mansard? Flat.

11. Size of present extension, if any? _____ feet front; _____ feet deep; _____ feet high.
12. Thickness and material of foundation walls? _____
13. Material of upper walls? _____ If ashlar, give kind and thickness _____
14. Thickness of upper walls:
 Basement: front _____ inches; rear _____ inches; side _____ inches; party _____ inches.
 1st story: " _____ " _____ " _____ " _____ " _____ " _____ "
 2d story: " _____ " _____ " _____ " _____ " _____ " _____ "
 3d story: " _____ " _____ " _____ " _____ " _____ " _____ "
 4th story: " _____ " _____ " _____ " _____ " _____ " _____ "
15. Is present building provided with a fire escape? Yes

If to be extended on any side, give the following information:

16. Is extension to be on side, front or rear? _____
17. Size of proposed extension, feet front _____; feet rear _____; feet deep _____; number of stories in height? _____ number of feet in height? _____
18. Material of foundation walls? _____; depth _____ feet; material of base course _____; thickness of base course _____; thickness of foundation walls, front _____ inches; side _____ inches; rear _____ inches; party _____ inches.
19. Will foundation be on rock, sand, earth or piles? _____
20. What will be the size of piers in cellar? _____; distance on centres? _____; size of base of piers? _____; thickness of cap stones? _____; of bond stones? _____
21. Material of upper walls? _____; material of front? _____
22. Thickness, exclusive of ashlar, of upper walls:
 1st story: front _____ inches; rear _____ inches; side _____ inches; party _____ inches.
 2d story: " _____ " _____ " _____ " _____ " _____ " _____ "
 3d story: " _____ " _____ " _____ " _____ " _____ " _____ "
 4th story: " _____ " _____ " _____ " _____ " _____ " _____ "
 5th story: " _____ " _____ " _____ " _____ " _____ " _____ "
 6th story: " _____ " _____ " _____ " _____ " _____ " _____ "
23. With what will walls be coped? _____
24. Will roof be flat, peak, or mansard? _____; material _____
25. Give size and material of floor and roof beams _____
 1st tier, material _____; size _____; distance on centres _____
 2d tier, " _____ " _____ " _____ " _____ "
 3d tier, " _____ " _____ " _____ " _____ "
 4th tier, " _____ " _____ " _____ " _____ "
 5th tier, " _____ " _____ " _____ " _____ "
 Roof tier, " _____ " _____ " _____ " _____ "
- Give thickness of headers _____ of trimmers _____
26. Give material of girders _____ of columns _____
 Under 1st tier, size of girders _____; size of columns _____
 " 2d " " " _____; " " _____
 " 3d " " " _____; " " _____
 " 4th " " " _____; " " _____
 " 5th " " " _____; " " _____
 " Roof tier, " " _____; " " _____

If the Front, Rear or Side Walls, or any portion thereof, are to be taken out and rebuilt, give definite particulars, and state in what manner :

47. On the basement, 2nd, 3rd, 4th, and 5th, stories a window to be cut into center piers of rear wall as shown on plan.

If altered Internally, give definite particulars, and state how the building will be occupied :

48. We will entirely remove from the yard the present school sink including the masonry of the vault, the iron trough and all other parts, properly disinfected the site, and will provide one watercloset for every two families in the said house.

Watercloset compartments will be 2'4" wide in the clear.

Watercloset compartments will have watertight floors made of slate and will have a slate base 6" all around said compartment.

Said door will be provided to the watercloset compartment.

Vestibule will be provided before entering watercloset compartment.

Partitions will be built of studs, lath and plaster 4".

49. How much will the alteration cost? \$ 625.00

If the Building is to be occupied as a Flat, Apartment or Lodging House, give the following particulars :

50. Is any part of building to be used as a store or for any other business purpose, if so, state for what?

The building is already occupied as a tenement house and occupancy will not be changed in any way whatsoever.

51. How many families will occupy each?

52. Height of ceilings?

Cellar	Base-ment	1st Floor	2d Floor	3d Floor	4th Floor	5th Floor	6th Floor

53. How basement to be occupied?

How made water-tight?

54. Will cellar or basement ceiling be plastered? How?

55. How will cellar stairs be enclosed?

56. How cellar to be occupied?

How made water-tight?

57. Will shafts be open or covered with louvre skylights full size of shafts?

Size of each shaft?

58. Dimensions of water-closet _____
 Dimensions of windows for living rooms? _____
59. Of what materials will hall partitions be constructed? _____

60. Of what materials will hall floors be constructed? _____

61. How will hall ceilings and soffits of stairs be plastered? _____
62. Of what material will stairways be constructed? _____
 Give sizes of stair well holes? _____
63. If any other building on lot, give size; front _____; rear _____; deep _____;
 stories high _____; how occupied _____; on front or rear
 of lot _____; material _____
 How much space between it and proposed building? _____
64. How will floors and sides of water closets to the height of 16 inches be made waterproof? _____

65. Number and location of water closets: Cellar _____; 1st floor _____; 2d floor _____;
 3d floor _____; 4th floor _____; 5th floor _____; 6th floor _____
66. This building will safely sustain per superficial foot upon the first floor _____ lbs.; upon 2d floor
 _____ lbs.; upon 3d floor _____ lbs.; upon 4th floor _____ lbs.; upon 5th floor
 _____ lbs.; upon 6th floor _____ lbs.; upon 7th floor _____ lbs.; upon 8th floor
 _____ lbs.

Owner, Adam Weber Address, 203 2nd, Avenue.

Architect, Bruno W. Berger & Son " 121 Bible House.

Superintendent, Owner " _____

Mason, _____ " _____

Carpenter, _____ " _____

Applicant must indicate the Building Line or Lines clearly and distinctly on the Drawings.

B 436
L 41

Office of the Borough President of the Borough of Manhattan,
In The City of New York.

THE BUREAU OF BUILDINGS FOR THE BOROUGH OF MANHATTAN,
Office, No. 220 FOURTH AVENUE,
S. W. Corner 18th Street.

Plan No. 3001

APPLICATION TO ALTER, REPAIR, ETC.

Application is hereby made to the Superintendent of Buildings of The City of New York, for the Borough of Manhattan, for the approval of the detailed statement of the specifications and plans herewith submitted, for the alteration or repairs of the building herein described. All provisions of the Law shall be complied with in the alteration or repair of said building, whether specified herein or not.

(Sign here) Harry Platt
The City of New York, Borough of Manhattan, Nov 17 1906

LOCATION AND DESCRIPTION OF PRESENT BUILDING.

- State how many buildings to be altered One
- What is the exact location thereof? (State on what street or avenue, the side thereof, the number of feet from the nearest street or avenue, and the name thereof) 111 St Marks place
North side 275 West Ave A.
- How was the building occupied? Tenement
How is the building to be occupied? Tenement
- Is the building on front or rear of lot? front Is there any other building erected on lot or permit granted for one? No Size _____ x _____; height _____ How occupied? _____ Give distance between same and proposed building _____ feet.
- Size of lot? 25 feet front; 25 feet rear; 91 feet deep.
- Size of building which it is proposed to alter or repair? 25 feet front; 25 feet rear; 52 feet deep. Number of stories in height? 5 Height from curb level to highest point? 50
- Depth of foundation walls below curb level? 8' Material of foundation walls? rubble Thickness of foundation walls? front 16 inches rear 16 inches; side 16 inches; party _____ inches.
- Material of upper walls? _____ If ashlar, give kind and thickness _____
- Thickness of upper walls:
Basement: front 16 inches; rear 16 inches; side 16 inches; party _____ inches.
1st story: " 12 " " 12 " " 12 " " " " "
2d story: " 12 " " 12 " " 12 " " " " "
3d story: " 12 " " 12 " " 12 " " " " "
4th story: " 12 " " 12 " " 12 " " " " "
5th story: " 12 " " 12 " " 12 " " " " "
6th story: " _____ " " _____ " " _____ " " _____ "
- Is roof flat, peak or mansard? flat

No Plumbing

11. Size of present extension, if any? _____ feet front; _____ feet deep; _____ feet high.

12. Thickness and material of foundation walls? _____

13. Material of upper walls? _____ If ashlar, give kind and thickness _____

14. Thickness of upper walls :

Basement: front _____ inches; rear _____ inches; side _____ inches; party _____ inches.

1st story: " _____ " _____ " _____ " _____ " _____ " _____ " _____ "

2d story: " _____ " _____ " _____ " _____ " _____ " _____ " _____ "

3d story: " _____ " _____ " _____ " _____ " _____ " _____ " _____ "

4th story: " _____ " _____ " _____ " _____ " _____ " _____ " _____ "

15. Is present building provided with a fire escape? *yes* _____

If to be extended on any side, give the following information :

16. Is extension to be on side, front or rear? _____

17. Size of proposed extension, feet front _____; feet rear _____; feet deep _____; number of stories in height? _____ number of feet in height? _____

18. Material of foundation walls? _____; depth _____ feet; material of base course _____; thickness of base course _____; thickness of foundation walls, front _____ inches; side _____ inches; rear _____ inches; party _____ inches.

19. Will foundation be on rock, sand, earth or piles? _____

20. What will be the size of piers in cellar? _____; distance on centres? _____; size of base of piers? _____: thickness of cap stones? _____; of bond stones? _____.

21. Material of upper walls? _____; material of front? _____

22. Thickness, exclusive of ashlar, of upper walls :

1st story: front _____ inches; rear _____ inches; side _____ inches; party _____ inches.

2d story: " _____ " _____ " _____ " _____ " _____ " _____ " _____ "

3d story: " _____ " _____ " _____ " _____ " _____ " _____ " _____ "

4th story: " _____ " _____ " _____ " _____ " _____ " _____ " _____ "

5th story: " _____ " _____ " _____ " _____ " _____ " _____ " _____ "

6th story: " _____ " _____ " _____ " _____ " _____ " _____ " _____ "

23. With what will walls be coped? _____

24. Will roof be flat, peak, or mansard? _____; material _____

25. Give size and material of floor and roof beams _____

1st tier, material _____; size _____; distance on centres _____

2d tier, " _____ " _____ " _____ " _____ " _____ " _____ " _____ "

3d tier, " _____ " _____ " _____ " _____ " _____ " _____ " _____ "

4th tier, " _____ " _____ " _____ " _____ " _____ " _____ " _____ "

5th tier, " _____ " _____ " _____ " _____ " _____ " _____ " _____ "

Roof tier, " _____ " _____ " _____ " _____ " _____ " _____ " _____ "

Give thickness of headers _____ of trimmers _____

26. Give material of girders _____ of columns _____

Under 1st tier, size of girders _____; size of columns _____

" 2d " " " _____; " " _____

" 3d " " " _____; " " _____

" 4th " " " _____; " " _____

" 5th " " " _____; " " _____

" Roof tier, " " " _____; " " _____

If the Front, Rear or Side Walls, or any portion thereof, are to be taken out and rebuilt, give definite particulars, and state in what manner :

47. _____

If altered Internally, give definite particulars, and state how the building will be occupied :

48. *It is proposed to put in partitions
 windows in cross partitions*

49. How much will the alteration cost? *\$200.*

If the Building is to be occupied as a Flat, Apartment or Lodging House, give the following particulars :

50. Is any part of building to be used as a store or for any other business purpose, if so, state for what ?

	Cellar	Base-ment	1st Floor	2d Floor	3d Floor	4th Floor	5th Floor	6th Floor
51. How many families will occupy each ?								
52. Height of ceilings?								

53. How basement to be occupied? _____
 How made water-tight? _____

54. Will cellar or basement ceiling be plastered? _____ How? _____

55. How will cellar stairs be enclosed? _____

56. How will cellar be occupied? _____
 How made water-tight? _____

57. Will shafts be opened or covered with louvre skylights full size of shafts? _____

 Size of each shaft? _____

58. Dimensions of water closet windows? _____
 Dimensions of windows for living rooms? _____
59. Of what materials will hall partitions be constructed? _____

60. Of what materials will hall floors be constructed? _____

61. How will hall ceilings and soffits of stairs be plastered? _____
62. Of what material will stairways be constructed? _____
 Give sizes of stair well holes? _____
63. If any other building on lot, give size; front _____; rear _____; deep _____;
 stories high _____; how occupied _____; on front or rear
 of lot _____; material _____
 How much space between it and proposed building? _____
64. How will floors and sides of water closets to the height of 16 inches be made waterproof? _____

65. Number and location of water closets: Cellar _____; 1st floor _____; 2d floor _____;
 3d floor _____; 4th floor _____; 5th floor _____; 6th floor _____;
66. This building will safely sustain per superficial foot upon the first floor _____ lbs.; upon 2d floor
 _____ lbs.; upon 3d floor _____ lbs.; upon 4th floor _____ lbs.; upon 5th floor
 _____ lbs.; upon 6th floor _____ lbs.; upon 7th floor _____ lbs.; upon 8th floor
 _____ lbs.

Owner, Adam Weber Address, 203-2nd Ave
 Architect, Harry Flat " 230 Grand St
 Superintendent, _____ " _____
 Mason, _____ " _____
 Carpenter, _____ " _____

DEPARTMENT OF HOUSING AND BUILDINGS
BOROUGH OF Manhattan, CITY OF NEW YORK

MANHATTAN
Municipal Bldg.,
Manhattan

BROOKLYN
Municipal Bldg.,
Brooklyn

BRONX
Bronx County Bldg.,
Grand Conc. & E. 161st St.

QUEENS
21-10 49th Avenue,
L. I. City

RICHMOND
Boro Hall,
St. George, S. I.

NOTICE—This Application must be TYPEWRITTEN and filed in QUADRUPPLICATE ✓

ALTERED BUILDING

PERMIT NO. 19 BLOCK 436 LOT 41

Application No. 981 19 SEC. OR WARD VOL.

N.B. ALT. LOCATION No 111 St Marks Place

DISTRICT (under building zone resolution) Use Bus Height 1-1/2 Area B

EXAMINED AND RECOMMENDED

FOR APPROVAL ON Apr 20 19 39

James C. Clarke
Examiner

APPROVED 19

Borough Superintendent

SPECIFICATIONS

- (1) NUMBER OF BUILDINGS TO BE ALTERED one
Any other building on lot or permit granted for one? NO
Is building on front or rear of lot? front
- (2) ESTIMATED COST OF ALTERATION: \$ 1560. (Old Law Tenement)
- (3) PROPOSED OCCUPANCY: Stores and tenement (Class A Multiple Dwelling)

STORY (include Cellar and basement)	BEFORE ALTERATION			AFTER ALTERATION						
	APTS.	ROOMS	USE	LIVE LOAD	NO. OF PERSONS			APTS.	ROOMS	USE
					MALE	FEMALE	TOTAL			
Cellar			Storage							Storage
Bas't			Stores							Stores
1. Story	2		Apartments				2			Apartments
2. "	2		"				2			"
3. "	2		"				2			"
4. "	2		"				2			"
5. "	2		"				2			"

ORIGINAL

- (4) SIZE OF EXISTING BUILDING:
At typical floor level 25 feet front 55 feet deep 25 feet rear
At street level 25 feet front 55 feet deep 25 feet rear
Height¹ Bas't & 5 stories 56 feet
- (5) SIZE OF BUILDING AS ALTERED:
At street level feet front feet deep feet rear
At typical floor level same feet front same feet deep feet rear
Height¹ feet stories same feet

If volume of building is to be increased, give the following information:

- (6) AREA² OF BUILDING AS ALTERED: At street level Total floor area² sq. ft.
- (7) TOTAL HEIGHT³ Cubic Contents⁴ cu. ft.

1. The term "height" of a structure shall mean the vertical distance from the curb level to the highest point of the roof beams in the case of flat roofs or to a point at the average height of the gable in the case of roofs having a pitch of more than one foot in four and one-half, except that in the case of structure where the grade of the street has not been legally established or where the structure does not adjoin the street, the average level of all the ground adjoining such structures shall be used instead of the curb level.
2. In computing this area, measurement shall be taken to the outside surfaces of exterior walls at each floor. Courts, yards, etc., shall be excluded. The areas of cellars and basements shall not be included.
3. Total height shall be measured from 6 inches below the lowest finished floor to the outside of the roof, and in case of sloping roofs, to the average height.
4. The cubical contents is the actual space enclosed within the outer surfaces of the outside walls and between the outer surface of the roof and six inches below the surface of the lowest floors. This includes the cube of dormers, penthouses, vaults, pits, enclosed porches, and other enclosed appendages. Outside steps, terraces, footings, courts, yards, light shafts and buildings detached from the main structure are not to be included. (Detached structures are to be separately computed.)

(8) CHARACTER OF PRESENT BUILDING:

Frame—		Fire-Protected—
Non-fireproof—	nonfireproof	Metal—
Fireproof—		Heavy Timber—

(9) STATE GENERALLY IN WHAT MANNER THE BUILDING WILL BE ALTERED:

New stud and plaster partitions to be erected on all floors above basement to form new water closet compartments, as per plans.
New water closet compartments to be ventilated by metal ducts extending thru roof etc as per requirements

If the building is to be raised in height or if the occupancy is changed so that the floor loads will be increased, the following information must be given as to the EXISTING BUILDING and the thickness of existing walls and size of footings must be clearly shown on the plans.

(10) NATURE OF SOIL UPON WHICH FOOTINGS WILL REST IN TERMS OF SECTION 7.5.2, BUILDING CODE:

(11) FOOTINGS: Material

(12) FOUNDATION WALLS: Material

(13) UPPER WALLS: Material

Kind of Mortar

Any Ashlar

Thickness of Walls

(14) PARTY WALLS: Any to be used?

Thickness of Walls

If building is to be enlarged or extended, the following information as to NEW WORK must be given:

(15) NATURE OF SOIL UPON WHICH FOOTINGS WILL REST IN TERMS OF SECTION 7.5.2, BUILDING CODE:

(16) FOOTINGS: Material

(17) FOUNDATION WALLS: Material

(18) UPPER WALLS: Material

Kind of Mortar

Any Ashlar

Thickness of Walls

(19) PARTY WALLS: Any to be used?

Thickness of Walls

(20) FIREPROOFING: Material and Thickness

For Columns

For Girders

For Beams

(21) INTERIOR FINISH: Material

Floor Surface

Trim, Sash, Doors, etc.

Plaster

(22) OUTSIDE WINDOW FRAMES AND SASH: Material

(23) ANY ELECTRICAL WORK TO BE DONE?

REMARKS

Inspector

DEPARTMENT OF HOUSING AND BUILDINGS
BOROUGH OF Manhattan, CITY OF NEW YORK

MANHATTAN
Municipal Bldg.,
Manhattan

BROOKLYN
Municipal Bldg.,
Brooklyn

BRONX
Byronx County Bldg.,
Grand Conc. & E. 161st St.

QUEENS
21-10 49th Avenue,
L. I. City

RICHMOND
Boro Hall
St. George, S. I.

NOTICE—This Application must be TYPEWRITTEN and filed in TRIPLICATE, and one copy sworn to by Applicant. If Elevator or Plumbing Applications are filed herewith, one affidavit is sufficient for all.

AFFIDAVIT
FORM A

APPLICATION No. 981 1039 BLOCK 456
PERMIT NO. _____ 19____ LOT 41
LOCATION 111 St Marks Place

FEES REQUIRED FOR _____

To THE BOROUGH SUPERINTENDENT:

Application is hereby made for approval of the plans and specifications herewith submitted and to be made a part hereof for the structure herein described, with the understanding that:

If this application shall be disapproved in part and if no further action is taken thereon within one year after notice of partial disapproval, it shall be automatically withdrawn.

Any permit issued under which no work is commenced within one year from the time of issuance shall expire by limitation. (Adm. Code C-26-177.0).

Work will be supervised by Licensed Architect, Professional Engineer or by a Superintendent of Construction who has had ten years' experience supervising building construction and who has been properly qualified. (Adm. Code C-26-187.0).

Work under this approval will not be commenced until a permit has been obtained, application for which will be filed with the Borough Superintendent, accompanied by satisfactory evidence that compensation insurance has been obtained in accordance with the provisions of the Workmen's Compensation Law. (Adm. Code C-26-161.0).

Work will be carried out in compliance with all the provisions of the Administrative Code of the City of New York and with the provisions of other laws and rules in effect on this date relating to the erection of said structure.

EXAMINED AND RECOMMENDED

FOR APPROVAL ON April 20 19 39

[Signature]
Examiner

APPROVED _____ 19____

Borough Superintendent *[Signature]*

STATE AND CITY OF NEW YORK }
COUNTY OF New York } ss.:

Frank Straub

Typewrite Name

being duly sworn, deposes and says: That he resides at 7 East 42nd Street
in the City of New York in the Borough of New York
in the State of New York

that he is making this application for the approval of plans and specifications herewith submitted and made a part hereof, for the building therein described. Deponent further says that he has personally supervised the preparation of the Architectural and Structural
(Architectural, Structural or Mechanical)

plans and that to the best of his knowledge and belief, the structure, if built in accordance with such plans, will conform to the Administrative Code; the Rules and Regulations of the Board of Standards and Appeals; The Charter; The Multiple Dwelling Law; The Labor Law; The General City Law; The Building Zone Resolution or any other provisions of law applicable thereto, except as hereinafter otherwise noted.

Deponent further says that he is the Architect for the owner in fee of all that certain lot, piece or parcel of land, shown on the diagram annexed hereto and made a part hereof, situate, lying and being in the Borough of Manhattan City of New York, aforesaid, and known and designated as Number 111 St Marks Place

and hereinafter more particularly described; that the work proposed to be done upon the said premises, in accordance with the accompanying detailed statement in writing of the specifications and plans of such proposed work, including all amendments to the same which may be filed hereafter—and also all Elevator and Plumbing work (if any) proposed to be done upon the same premises and specified in separate applications filed herewith and all subsequent amendments thereto—is duly authorized by Marie Safir

and that Frank Straub is owner (Name of Owner or Lessee who has Owner's consent) duly authorized by the aforesaid owner to make application for the approval of such detailed statements of specifications and plans (and amendments thereto) in her behalf.

Deponent further says that the full names and residences, street and number, of the owner or owners of the said land, and also of every person interested in said building or proposed building, structure or proposed structure premises, wall, platform, staging or flooring, either as owner, lessee, or in any representative capacity, are as follow

NAMES AND ADDRESSES

Owner Marie Safir 111 St Marks Place

Lessee

Architect Frank Straub 7 East 42nd Street

Superintendent owner

The said land and premises above referred to are situated, bounded and described as follows, viz.: BEGINNING at a point on the north side of St Marks Place

distant 225 feet west from the corner formed by the intersection of Avenue A and St Marks Place running thence west 25 feet; thence north 93'10 feet; east 25 feet; thence south 93'10 feet

to the point or place of beginning,—being designated on the map as Block No. 436 Lot No. 41

(SIGN HERE) Frank Straub APPLICANT

Sworn to before me, this 27 day of March, 1937

Affix Seal of Registered Architect or Professional Engineer Here

Notary Public or Commissioner of Deeds

NOTE.—If building is a Multiple Dwelling, the following authorization is required: Commission expires March 30, 1940

AUTHORIZATION OF OWNER

Marie Safir Deposits and says: That resides at 111 St Marks Place Borough Manhattan City of New York State of New York; that he is the Owner of all that certain piece or lot of land situated in the Borough of Manhattan in the City of New York, and located on the north side of St. Marks Place and known as No. 111 on said street; that the multiple dwelling proposed to be altered upon said premises will be constructed in accordance with the annexed specifications and plans submitted herewith for the approval of the Department of Housing and Buildings; that the work will be supervised by Licensed Architect, Professional Engineer or a Superintendent of Construction who has had ten years' experience supervising building construction and who has been properly qualified; and that Frank Straub is duly authorized by said owner.

Marie Safir to make application in said owner's behalf for the approval of such specifications and plans in compliance with Chapter 713 of the Laws of 1929.

NOTE.—This clause to be used only when the person executing this authorization is not the sole owner of the premises described herein.

He further says that the full names and residences, street and number, of the owner or owners of the said land, and of every person having an interest in said premises and projected multiple dwelling either as owner, lessee, or otherwise, as required by Section 300 of the Multiple Dwelling Law, are as follows:

Table with 3 columns: Name and Relationship to premises, No., Address. Includes signature of Marie Safir.

DEPARTMENT OF HOUSING AND BUILDINGS

BOROUGH OF Manhattan, CITY OF NEW YORK

MANHATTAN
Municipal Bldg.,
Manhattan

BROOKLYN
Municipal Bldg.,
Brooklyn

BRONX
Bronx County Bldg.,
Grand Conc. & E. 161st St.,

QUEENS
21-10 49th Avenue,
L. I. City

RICHMOND
Boro Hall
St. George, S. I.

NOTICE—This Amendment must be TYPEWRITTEN and filed in TRIPPLICATE

AMENDMENT

Alteration APPLICATION No. 981, 1939 PERMIT No. 19
(N.B., Alt., Elev., Etc.)

LOCATION 111 St Marks Place

BLOCK LOT SEC VOL

April 24, 39, 19

TO THE BOROUGH SUPERINTENDENT:

Application is hereby made for approval of the following AMENDMENT to the specifications and plans filed with the above numbered application, with the stipulation that this amendment is to become a part of the aforesaid original application and subject to all the conditions, agreements and statements therein contained.

(Signed) [Signature] Applicant
7 East 42nd Street Address

Present wood stairs from first story to roof will be replaced by new steel stairs; All headers and trimmers around stair openings will be reinforced by placing of lally columns in cellar and basement and new wood posts in all upper floors, in hall partitions, all as shown on new plan filed this day

NOTE.—The applicant must not use the back of this sheet. If more space is needed, additional sheets must be used. No item must be continued over to another sheet; but each item must be complete on the sheet on which it appears. Only those items that appear above the endorsements at the bottom of the page can be considered.

EXAMINED AND RECOMMENDED FOR APPROVAL ON May 3, 1939 [Signature] Examiner.

APPROVED [Signature] 19 Borough Superintendent.

DEPARTMENT OF HOUSING AND BUILDINGS

BOROUGH OF Manhattan, CITY OF NEW YORK

MANHATTAN Municipal Bldg., Manhattan

BROOKLYN Municipal Bldg., Brooklyn

BRONX Bronx County Bldg., Grand Conc. & E. 161st St.

QUEENS 21-10 49th Avenue, L. I. City

RICHMOND Boro Hall St. George, S. I.

NOTICE—This Amendment must be TYPEWRITTEN and filed in TRIPLICATE

AMENDMENT

DEPARTMENT OF HOUSING & BUILDINGS RECEIVED MAY 24 1939 CITY OF NEW YORK BOROUGH OF MANHATTAN

Alteration APPLICATION No. 981, 19 39 (N. B., Alt., Elev., Etc.)

LOCATION 111 St Marks Place

BLOCK LOT

May 23, 1939, 19

To THE BOROUGH SUPERINTENDENT:

Application is hereby made for approval of the following AMENDMENT to the specifications and plans filed with the above numbered application, with the stipulation that this amendment is to become a part of the aforesaid original application and subject to all the conditions, agreements and statements therein contained.

(Signed) Frank Howard Applicant 7 East 42nd Street Address

It is proposed to omit the new 4" Lally Columns and Concrete footings in basement and first story now shown on approved plans, as there is now a 12" brickwall in centre of basement, running from front to rear walls of building. wood posts will be installed in 1st story, 4" x 6", as above, same will rest on a 4" x 10" beam set on edge about 4ft long, covering at least 3 floor beams same, over basement

NOTE.—The applicant must not use the back of this sheet. If more space is needed, additional sheets must be used. No item must be continued over to another sheet; but each item must be complete on the sheet on which it appears. Only those items that appear above the endorsements at the bottom of the page can be considered.

EXAMINED AND RECOMMENDED FOR APPROVAL ON June 19 39

James C. Clarke Examiner. [Signature]

APPROVED, 19

Borough Superintendent. [Signature]