

Plan No. 70

APPLICATION FOR ERECTION OF BUILDINGS. 1

Application hereby made to the Superintendent of Buildings of the City of New York, for the erection of the building herein described. All provisions of the Building Law shall be complied with in the erection of said building, whether specified herein or not.

NEW YORK, March 4th 1898

(Sign here)

John L. Buttner
George William Cook

1. State how many buildings to be erected. one
2. How occupied? If for dwelling, state the number of families. Permanent 22 fam. + 2 stores
3. What is the street or avenue and the number thereof? Give diagram of property. No. 336 East 5th Street
4. Size of lot. No. of feet front, 25'0"; No. of feet rear, 25'0"; No. of feet deep, 96'0"
5. Size of building. No. of feet front, 25'0"; No. of feet rear, 25'0"; No. of feet deep, 82'10"
No. of stories in height, 6; No. of feet in height from curb level to highest point of roof beams, 70'0" to top of cornice
6. What will each building cost exclusive of the lot? \$ 27,000.00
7. What will be the depth of foundation walls from curb level or surface of ground? 10 feet
8. Will foundation be laid on earth, sand, rock, timber or piles? earth
9. What will be the base, stone or concrete? stone If base stones, give size and thickness and how laid. 9x36x2" laid edge to edge If concrete, give thickness.
10. What will be the sizes of piers? 2/35x28" 2/24x28"
11. What will be the sizes of the base of piers? one foot larger on all sides
12. What will be the thickness of foundation walls? 24" Of what material constructed? Rubble stone laid in cement mortar
13. What will be the thickness of upper walls? Basement, _____ inches; 1st story, 16 inches; 2d story, 16 inches; 3d story, 12 inches; 4th story, 12 inches; 5th story, 12 inches; 6th story, 12 inches; 7th story, ✓ inches, and from thence to top, 8 inches. Of what materials to be constructed? Hard burnt brick
14. State whether independent or party walls. Independent
15. With what material will walls be coped? Blue stone or Earthenware
16. What will be the materials of front? Brick If of stone, what kind? ✓
Give thickness of ashler. ✓ Give thickness of backing in each story. ✓
17. Will the roof be flat, peaked or mansard? Flat
18. What will be the materials of roofing? Tin 4" HK arches
19. Give size and materials of floor beams. 1st tier, 8" 54 lbs p.y. steel; 2d tier, 3x10" Spruce; 3d tier, 3x10" Spruce; 4th tier, 3x10" Spruce; 5th tier, 3x10" Spruce; 6th tier, 3x10" Spruce; 7th tier, _____; 8th tier, _____; roof tier, 3x9" Spruce
State distances from centres. 1st tier, 4'4" inches; 2d tier, 16 inches; 3d tier, 16 inches; 4th tier, 16 inches; 5th tier, 16 inches; 6th tier, 16 inches; 7th tier, ✓ inches; 8th tier, ✓ inches; roof tier, 20 inches.
20. If floors are to be supported by columns and girders, give the following information: Size and material of girders under 1st floor, 8" HK walls under each of the upper floors, _____
Size and materials of columns under 1st floor, 8" brick walls under each of the upper floors, _____
21. This building will safely sustain per superficial foot upon 1st floor 150 + 70 lbs; upon 2d floor 70 lbs; upon 3d floor 70 lbs; upon 4th floor 70 lbs; upon 5th floor 70 lbs.
22. If the front, rear or side walls are to be supported, in whole or in part, by iron girders or lintels, give definite particulars. Front wall above 1st sty. carried on 3/9" 63 lbs. per yard steel beams
23. If girders are to be supported by brick piers and columns, state the sizes of piers and columns. Front wall girder carried on 2/12x16" & 2/8x16" cast iron columns 3/4" metal with cap and sole plates complete
24. State by whom the construction of the building is to be superintended. Contractor
W. A. Mel 2/19/98

If the Building is to be occupied as an Apartment or Tenement House, give the following particulars.

1. State how many families are to occupy each floor, and the whole number in the house; also, if any part is to be used as a store or for any other business purposes, state the fact. *Apartment, 4 fam.*

on each floor + 2 fam on first 42 stores total number of fam. 22

2. What will be the heights of ceilings? 1st story, *11'8"* feet; 2d story, *10'0"* feet; 3d story, *9'8"* feet; 4th story, *9'8"* feet; 5th story, *9'8"* feet; 6th story, *9'8"* feet; 7th story, _____ feet.

3. How are the hall partitions to be constructed and of what materials? *8 1/2" brick walls to first story entrance hallway 4" No. 6. Blocks + 4" angle iron*

4. How many buildings are to be taken down? *one*

Owner *Jos. L. Butterfield* Address *233 Lenox Avenue*
 Architect *G. Fred Tullam* Address *503 Fifth Avenue*
 Mason _____ Address _____
 Carpenter _____ Address _____

If a Wall or part of a Wall already built is to be used, fill up the following.

The undersigned gives notice that _____ intend to use the _____ wall of building _____ as party wall in the erection of the building hereinbefore described, and respectfully requests that the same be examined and a permit granted therefor. The foundation wall _____ built of _____ inches thick, _____ feet below curb; the upper wall _____ built of _____ inches thick, _____ feet deep, _____ feet in height.

(Sign here) _____

NOTE—In making application for the erection of buildings, the following drawings must be furnished: Plans of each and every story, front, rear and side elevations, and longitudinal and transverse sections. All plans must be drawn to a uniform scale, and must be on tracing cloth, properly designated and colored.

THE BUILDING LAW REQUIRES:

- 1st—That all stone walls shall be properly bonded and laid in cement mortar.
- 2d—That all skylights having a superficial area of more than nine square feet, placed in any building, shall have the sashes and frames thereof constructed of iron and glass.
- 3d—That every building which is more than two stories in height above the curb level, except dwelling-houses, hotels, school-houses and churches, shall have doors, blinds or shutters made of iron, hung to iron hanging frames or to iron eyes built into the wall, on every window and opening above the first story thereof, excepting on the front openings of buildings fronting on streets which are more than thirty feet in width. Or the said doors, blinds or shutters may be constructed of pine or other soft wood of two thicknesses of matched boards at right angles with each other, and securely covered with tin, on both sides and edges, with folded lapped joints, the nails for fastening the same being driven inside the lap; the hinges and bolt, or latches shall be secured or fastened to the door or shutter after the same has been covered with the tin, and such doors or shutters shall be hung upon an iron frame, independent of the woodwork of the windows and doors, or two iron hinges securely fastened in the masonry; or such frames, if of wood, shall be covered with tin in the same manner as the doors and shutters.
- 4th—That outside fire escapes shall be placed on every dwelling-house occupied by or built to be occupied by three or more families above the first story, and every building already erected, or that may hereafter be erected, more than three stories in height, occupied and used as a hotel or lodging-house, and every boarding-house, having more than fifteen sleeping-rooms above the basement story, and every factory, mill, manufacturing or workshop, hospital, asylum or institution for the care or treatment of individuals, and every building in whole or in part occupied or used as a school or place of instruction or assembly, and every office building five stories or more in height, all to be constructed as follows:

BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE.

- BRACKETS** must not be less than 1 1/2 x 1 3/4 inches wrought iron, placed edgewise, or 1 3/4 inch angle iron 1/4 inch thick, well braced, and not more than three feet apart, and the braces to brackets must be not less than 3/4 inch square wrought iron, and must extend two-thirds of the width of the respective brackets or balconies. In all cases the brackets must go through the wall, and be turned down three inches.
- BRACKETS ON NEW BUILDINGS** must be set as the walls are being built. When brackets are to be put on old houses, the part going through the wall shall not be less than one inch diameter, with screw nuts and washers not less than five inches square and 1/2 inch thick.
- TOP RAILS.**—The top rail of balcony must be 1 3/4 inch x 1 1/2 inch wrought iron or 1 1/2 inch angle iron 1/4 inch thick, and in all cases must go through the walls, and be secured by nuts and 4 inch square washers, at least 3/8 inch thick, and no top rail shall be connected at angles by the use of cast iron.
- BOTTOM RAILS.**—Bottom rails must be 1 1/4 inch x 3/4 inch wrought iron or 1 1/4 inch angle iron 1/4 inch thick, well leaded into the wall. In frame buildings the top rails must go through the studding and be secured on the inside by washers and nuts as above.
- FILLING-IN BARS.**—The filling-in bars must be not less than 1/2 inch round or square wrought iron, placed not more than 6 inches from centres, and well riveted to the top and bottom rails.
- STAIRS.**—The stairs in all cases must be not less than 18 inches wide, and constructed of 1 1/2 x 3 1/2 inch wrought iron sides or strings. Steps may be of cast iron of the same width of strings, or 3/8 inch round iron, double rungs, and well riveted to the strings. The stairs must be secured to a bracket on top and rest on and be secured to a bracket or extra cross bar at the bottom. All stairs must have a 3/4 inch hand rail of wrought iron, well braced.
- FLOORS.**—The flooring of balconies must be of wrought iron 1 1/2 x 3/4 inch slats placed not over 1 3/4 inches apart, and secured to iron battens 1 1/2 x 3/8 inch, not over three feet apart and riveted at the intersection. The openings for stairways in all balconies shall not be less than 20 inches wide and 30 inches long, and have no covers.
- DROP LADDERS.**—Drop ladders from lower balconies where required shall not be less than 14 inches wide, and shall be made of 1 1/2 x 3/4 inch sides and 5/8 inch rungs of wrought iron. In no case shall a drop ladder be more than 12 feet in length. In no case shall the ends of balconies extend more than nine inches over the brackets.
- SCUTTLE LADDERS.**—Ladders to scuttles shall be constructed in all cases the same as the stairs or step-ladders from balconies of fire escapes.
- THE HEIGHT OF RAILING** around balconies shall not be less than two feet nine inches.

No Fire Escape will be approved by the Superintendent of Buildings if not in accordance with above specifications.

In constructing all balcony fire-escapes, the manufacturer thereof shall securely fasten thereto, in a conspicuous place, a cast-iron plate having suitable raised letters on the same, to read as follows: Notice! Any person placing any incumbrance on this balcony is liable to a penalty of ten dollars and imprisonment for ten days.

- 5th—That all exterior and division or party walls over fifteen feet high, excepting where such walls are to be finished with cornices, gutters or crown mouldings, shall have parapet walls carried two feet above the roof, and shall be coped with stone, well-burnt terra-cotta or cast iron.
- 6th—That every building and the tops and sides of every dormer-window thereon shall be covered and roofed with slate, tin, copper or iron, or such other quality of fire-proof roofing as the superintendent of buildings, under his certificate, may authorize.
- 7th—That all exterior cornices shall be fire proof.
- 8th—That the stone or brick work of all smoke flues, and the chimney shafts of all furnaces, boilers, bakers' ovens, large cooking ranges and laundry stoves, and all flues used for a similar purpose, shall be at least eight inches in thickness. If there is a cast-iron or burnt clay pipe built inside of the same, with one-inch air space all around it, then the stone or brick work inclosing such pipes shall not be less than four inches in thickness.
- 9th—That before any iron or steel beam, lintel or girder intended to span an opening over ten feet in length in any building, shall be used for supporting a wall, it shall be inspected, tested and approved as provided by law.

Applicant must indicate the Building Line or Lines clearly and distinctly on the Drawings

446
Office of the Borough President of the Borough of Manhattan,
26

2

Office of the Borough President of the Borough of Manhattan,

In The City of New York.

THE BUREAU OF BUILDINGS FOR THE BOROUGH OF MANHATTAN,
Office, No. 220 FOURTH AVENUE,
S. W. Corner 18th Street.

1424

Plan No. 1800

APPLICATION TO ALTER, REPAIR, ETC.

Application is hereby made to the Superintendent of Buildings of The City of New York, for the Borough of Manhattan, for the approval of the detailed statement of the specifications and plans herewith submitted for the alteration or repairs of the building herein described. All provisions of the Law shall be complied with in the alteration or repair of said building, whether specified herein or not.

(Sign here)

Lawrence A. Stewart
THE CITY OF NEW YORK, BOROUGH OF MANHATTAN, May 17 1910

LOCATION AND DESCRIPTION OF PRESENT BUILDING.

- State how many buildings to be altered one
- What is the exact location thereof? (State on what street or avenue, the side thereof, the number of feet from the nearest street or avenue, and the name thereof) South Side of 2nd Fifth St 200:0 East of First Ave No 386
- How was the building occupied? Store & Tenement
How is the building to be occupied? Store & Tenement
- Is the building on front or rear of lot? front Is there any other building erected on lot or permit granted for one? No Size _____ x _____; height _____ How occupied? _____ Give distance between same and proposed building _____ feet.
- Size of lot? 25:0 feet front; 25:0 feet rear; 100:0 feet deep.
- Size of building which it is proposed to alter or repair? 25:0 feet front; 25:0 feet rear; 80:0 feet deep. Number of stories in height? Six Height from curb level to highest point? 60:0
- Depth of foundation walls below curb level? 12:0 Material of foundation walls? Stone Thickness of foundation walls? front 20 inches; rear 20 inches; side 20 inches; party _____ inches.
- Material of upper walls? Brick If ashlar, give kind and thickness _____
- Thickness of upper walls:
Basement: front _____ inches; rear _____ inches; side _____ inches; party _____ inches.
1st story: " Columns " " 16 " " 16 " " " " "
2d story: " 16 " " 12 " " 12 " " " "
3d story: " 12 " " 12 " " 12 " " " "
4th story: " 12 " " 12 " " 12 " " " "
5th story: " 12 " " 12 " " 12 " " " "
6th story: " 12 " " 12 " " 12 " " " "
- Is roof flat, peak or mansard? flat

If the Front, Rear or Side Walls, or any portion thereof, are to be taken out and rebuilt, give definite particulars, and state in what manner :

47. _____

If altered internally, give definite particulars, and state how the building will be occupied :

48. *Erud a stud & plaster partition dividing the present store into two as shown in plan, present show window to remain*

49. How much will the alteration cost? 150⁰⁰

If the Building is to be occupied as a Flat, Apartment or Lodging House, give the following particulars :

50. Is any part of building to be used as a store or for any other business purpose, if so, state for what?

	Cellar	Base-ment	1st Floor	2d Floor	3d Floor	4th Floor	5th Floor	6th Floor
51. How many families will occupy each?	-	-	-	-	-	-	-	-
52. Height of ceilings?	-	-	-	-	-	-	-	-

53. How basement to be occupied? _____
 How made water-tight? _____

54. Will cellar or basement ceiling be plastered? _____ How? _____

55. How will cellar stairs be enclosed? _____

56. How will cellar be occupied? _____
 How made water-tight? _____

57. Will shafts be opened or covered with louvre skylights full size of shafts? _____

Size of each shaft? _____

**CITY OF NEW YORK
DEPARTMENT OF HOUSING AND BUILDINGS
ALTERED BUILDING**

NOTICE—This Application must be TYPEWRITTEN and filed in QUADRUPPLICATE

346

ALT. No. 346 19 53 BLOCK 446 LOT 26

LOCATION 336 East 5th Street, 150'-3" West of 1st Avenue Manhattan

House Number, Street, Distance from Nearest Corner and Borough

ZONING: USE DIST. Business Residence HEIGHT DIST. 1 1/2 AREA DIST. B

Initial fee payment—Amount \$ 5- 1st Receipt No. 50476

Date 3/24/53 Cashier [Signature]

2nd payment of fee to be collected before a permit is issued—Amount \$ 15 (20-5)

Verified by m. Sanders / Willis P.E. Date 12/9/53

2nd Receipt No. 55790 Date 12-9-53 Cashier [Signature]

EXAMINED AND RECOMMENDED FOR APPROVAL ON 3/23/53 MAR 24 1953
Willis P.E.
Manuel Hernandez
Examiner.

APPROVED 1953 19 1953 Borough Superintendent [Signature]

SPECIFICATIONS

- (1) Classification of Buildings to be Altered. (NOTE—See C26-238.0) **Non-Fireproof**
- (2) Any other buildings on lot or permit granted for one? **No**
Is building on front or rear of lot? **Front**
- (3) Use and Occupancy. **Stores and M.D. Cl. A**
(NOTE—If a multiple dwelling, authorization of owner must be filed)
A new C of O (~~will~~) (will not) be required.

Examined for stated work. No other factor considered.
nmw 3/20/53

STORY (Include cellar and basement)	EXISTING LEGAL USE			PROPOSED OCCUPANCY						
	APTS.	ROOMS	USE	LIVE LOAD	NO. OF PERSONS			APTS.	ROOMS	USE
					MALE	FEMALE	TOTAL			
Cellar										
1st	2	6	Stores & Apts.							
2nd	4	13	Apartments							
3rd	4	13	"							
4th	4	13	"							
5th	4	13	"							
6th	4	13	"							

NO CERTIFICATE OF OCCUPANCY TO BE ISSUED ON THIS APPLICATION EXAMINED FOR STATED WORK ONLY NO OTHER FACTOR CONSIDERED.

(4) State generally in what manner the Building will be altered:

Installing water closets and bath rooms, so that all apartments will have private toilet facilities.

No change in occupancy.

(5) Size of Existing Building:

At street level	25	feet front	96.2	feet deep	25	feet rear
At typical floor level	25	feet front	96.2	feet deep	25	feet rear
Height ¹	6	stories	55	feet		

(6) If volume of Building is to be changed, give the following information: No change

At street level		feet front		feet deep		feet rear
At typical floor level		feet front		feet deep		feet rear
Height ¹		stories		feet		

Area² of Building as Altered: At street level Total floor area² sq. ft.
 Total Height³ Additional Cubic Contents⁴ cu. ft.

(7) Estimated Cost of Alteration:⁵ ~~\$1,000.~~ \$5,000 ⁰⁰ *as M.S.*
Estimated Cost, exclusive of extension:

(8) Is Application made to remove violations? No If Yes, State Violation Numbers

(9) If building is to be enlarged or extended or floor loads increased, Soil Data shall be submitted in accordance with Sec. C26-376.0. For alterations of a minor nature, the Applicant certifies that he has investigated the nature of the soil and finds the following:

Character of soil Bearing capacity

(10) State what disposition will be made of waste and sewage Public Sewer
(Public sewer, Private sewer, Cesspool, etc.)

(11) Does this Application include Dropped Curb? No
(If Drop Curb Permit is obtained with this Application, DIAGRAM showing the relative position of drop curb and extent thereof must be included on plot diagram.⁶)

Drop Curb ft. @ \$ per ft. Splay ft. @ \$ per ft.
 Exact distance from nearest corner to Curb Cut: feet.
 Deposit: \$ Fee: \$ Total: \$
 Paid 19 Document No. Cashier

(12) Temporary Structures between Street Line and Curb: None
Will a Sidewalk Shed be required? Length feet.
Will any other miscellaneous temporary structures be required?
Fee Required Fee Paid 19 Document No. Cashier

1. The term "height" of a structure shall mean the vertical distance from the curb level to the highest point of the roof beams in the case of flat roofs or to a point at the average height of the gable in the case of roofs having a pitch of more than one foot in four and one-half, except that in the case of structures where the grade of the street has not been legally established or where the structure does not adjoin the street, the average level of all the ground adjoining such structures shall be used instead of the curb level.

2. In computing this area, measurement shall be taken to the outside surfaces of exterior walls at each floor. Courts, yards, etc., shall be excluded. The areas of cellars and basements shall not be included.

3. Total height shall be measured from 6 inches below the lowest finished floor to the outside of the roof, and in case of sloping roofs, to the average height.

4. The cubical contents is the actual space enclosed within the outer surfaces of the outside walls and between the outer surface of the roof and six inches below the surface of the lowest floors. This includes the cube of dormers, penthouses, vaults, pits, enclosed porches, and other enclosed appendages. Outside steps, terraces, footings, courts, yards, light shafts and buildings detached from the main structure are not to be included. (Detached structures are to be separately computed.)

5. "Estimated Cost" for computation purposes on alteration of existing buildings or structures shall be the cost of all contemplated construction, including plumbing work, elevator work, standpipe fire line work, automatic sprinkler, fuel oil, air conditioning, etc.

6. Space for plot diagram is located on Affidavit Form.

7. Uses should be related to pertinent legal terms, e.g., use terms like factory rather than loft, auto repairs rather than brake testing, etc.

ORIGINAL

DEPARTMENT OF HOUSING AND BUILDINGS

BOROUGH OF Manhattan, CITY OF NEW YORK

MANHATTAN Municipal Bldg., New York 7

BROOKLYN Municipal Bldg., Brooklyn 2

BRONX 1932 Arthur Ave., New York 57

QUEENS 120-55 Queens Blvd., Kew Gardens 15, L. I.

RICHMOND Boro Hall, St. George 1, S. I.

NOTICE—This Application must be TYPEWRITTEN and filed in TRIPLICATE, and ONE copy worn to by Applicant. A copy must be kept in plain view on the work at all times until completion.

PERMIT

PERMIT No. 2508 1953 N. B. ALT. ELEV. SIGN } Alt. Application No. 346 1953

LOCATION 336 East 5th Street BLOCK 446 LOT 26

FEES PAID FOR

NOTE—Trees in streets fronting on site are under jurisdiction of Department of Parks. They must be protected and written notification made to that Department at least 48 hours prior to commencement of work. New York City December 9th 1953

To the Borough Superintendent: Application is hereby made for a PERMIT to perform the Carpentry, Plastering work described in the above numbered application and the accompanying plans. If no work is performed within one year from the time of issuance, this permit shall expire by limitation as provided by law; and the applicant agrees to comply with all provisions of the Building Code of the City of New York and with the provisions of all other laws and rules relating to this subject. Compensation insurance has been secured in accordance with the requirements of the Workmen's Compensation Law as follows: State Ins. Fund #Y-217-139 Exp. 7-28-54

When the policy of a general contractor does not fully cover the work of any sub-contractor, such sub-contractor must file a certificate of workmen's compensation covering his particular work. No work is to be commenced by this sub-contractor until his certificate has been submitted and approved by this department.

No certificate of occupancy will be issued unless the construction work covered by this permit will be supervised by a Licensed Architect, or a Professional Engineer, or by a Superintendent of Construction, having at least ten years' experience, acceptable to the Borough Superintendent. An affidavit shall be filed indicating such supervision, as required by Section 2.1.3.7 of the Building Code.

Name and address of person designated for this supervision is as follows: Name Albert Fetner Address 49 East 12th Street, N.Y.C.

STATE AND CITY OF NEW YORK } ss.: Albert Fetner for M. Fetner & Co. COUNTY OF New York } Typewrite Name of Applicant

being duly sworn, deposes and says: That he resides at Number 49 East 12th Street in the Borough of Man. in the City of N.Y., in the County of N.Y. in the State of N.Y., that he is Agent for Contractor for the owner in fee of all that certain lot, piece or parcel of land, shown on the diagram annexed to the approved application and made a part thereof, situate, lying and being in the Borough of Manhattan, City of New York aforesaid, and known and designated as Number 336 East 5th Street and therein more particularly described; that the work proposed to be done upon the said premises, in accordance with the approved application and accompanying plans is duly authorized by B. Tomaszewski (Name of Owner or Lessee)

and that M. Fetner & Co. is duly authorized by the aforesaid Owner to make application for a permit to perform said work set forth in the approved application and accompanying plans, and all the statements herein contained are true to deponent's own knowledge.

(SIGN HERE) Albert Fetner Sworn to before me, this 9th day of December 1953 Notary Public or Commissioner of Deeds RUTH DORRMAN Commissioner of Deeds N. Y. City Kings County Clerk's No. 22 Commission Expires April 22, 1954

Satisfactory evidence having been submitted as indicated above that compensation insurance has been secured in accordance with the Workmen's Compensation Law, a permit is hereby issued for the performance of the work described in the above numbered application and the accompanying plans.

EXAMINED AND RECOMMENDED FOR APPROVAL ON DEC 9-1953 Approved DEC 9-1953 19 Borough Superintendent BOROUGH SUPERINTENDENT