

3449

APPLICATION FOR ERECTION OF BUILDINGS.

1

Application hereby made to the Superintendent of Buildings of the City of New York, for the approval of the detailed statement of the specifications and plans herewith submitted, for the erection of the building herein described. All provisions of the Building Law shall be complied with in the erection of said building, whether specified herein or not.

NEW YORK April 6th 1897

(Sign here) John L. Button, owner
Geo. P. & John Smith

1. State how many buildings to be erected. no
2. How occupied? If for dwelling, state the number of families. movement for 22 families & 1 store
3. What is the street or avenue and the number thereof? Give diagram of property. No. 73-75 Seventh St.

4. Size of lot. No. of feet front, 50'-0"; No. of feet rear, 50'-0"; No. of feet deep, 97'-6"
5. Size of building. No. of feet front, 27'-0"; No. of feet rear, 27'-0"; No. of feet deep, 83'-4"
No. of stories in height, 6; No. of feet in height from curb level to highest point of roof beams, 66'-0"

6. What will each building cost exclusive of the lot? \$ 27,000.00

7. What will be the depth of foundation walls from curb level or surface of ground? 10 feet

8. Will foundation be laid on earth, sand, rock, timber or piles? Earth

9. What will be the base, stone or concrete? stone If base stones, give size and thickness and how laid. 9x36 laid in cement If concrete, give thickness.

10. What will be the sizes of piers? 24x28, 28x28, 36x28

11. What will be the sizes of the base of piers? one foot larger on all sides

12. What will be the thickness of foundation walls? 24" Of what material constructed? Rubble stone laid in cement mortar

13. What will be the thickness of upper walls? Basement, 24 inches; 1st story, 16 inches; 2d story, 16 inches; 3d story, 14 inches; 4th story, 12 inches; 5th story, 12 inches; 6th story, 12 inches; 7th story, ✓ inches, and from thence to top, 8 inches. Of what materials to be constructed? Hard burnt brick

14. State whether independent or party walls. Both

15. With what material will walls be coped? Blue stone or Earthenware

16. What will be the materials of front? Brick If of stone, what kind? ✓
Give thickness of ashler. ✓ Give thickness of backing in each story. ✓

17. Will the roof be flat, peaked or mansard? Flat

18. What will be the materials of roofing? Tin 2 brick arches

19. Give size and materials of floor beams. 1st tier, 8" 54 lbs. p. steel; 2d tier, 3x10 Spruce; 3d tier, 3x10 Spruce; 4th tier, 3x10 Spruce; 5th tier, 3x10 Spruce; 6th tier, 3x10 Spruce; 7th tier, 3x9 Spruce; 8th tier, ✓; roof tier, 3x9 Spruce

State distances from centres. 1st tier, 4ft inches; 2d tier, 16 inches; 3d tier, 16 inches; 4th tier, 16 inches; 5th tier, 16 inches; 6th tier, 16 inches; 7th tier, ✓ inches; 8th tier, ✓ inches; roof tier, 20 inches.

20. If floors are to be supported by columns and girders, give the following information: Size and material of girders under 1st floor, 8" brick wall under each of the upper floors, 8" brick wall under each of the upper floors, _____ Size and materials of columns under 1st floor, _____ under each of the upper floors, _____

21. This building will safely sustain per superficial foot upon 1st floor _____ lbs.; upon 2d floor _____ lbs.; upon 3d floor _____ lbs.; upon 4th floor _____ lbs.; upon 5th floor _____ lbs.

22. If the front, rear or side walls are to be supported, in whole or in part, by iron girders or lintels, give definite particulars. Front wall above 1st story carried on 3-9" = 63 lbs per yard steel beams

23. If girders are to be supported by brick piers and columns, state the sizes of piers and columns. Under carrying front wall supported on 12x12" 16x16" & 20x20" cast iron columns 3/4" metal and with cap and sole plates complete

24. State by whom the construction of the building is to be superintended. Contractor

Dep 7/2/10

If the Building is to be occupied as an Apartment or Tenement House, give the following particulars.

1. State how many families are to occupy each floor, and the whole number in the house; also, if any part is to be used as a store or for any other business purposes, state the fact, *Permitted for families on each floor two on 1st floor total 22 families & 2 stores*
2. What will be the heights of ceilings? 1st story, *11'0"* feet; 2d story, *10'0"* feet; 3d story, *9'8"* feet; 4th story, *9'8"* feet; 5th story, *9'8"* feet; 6th story, *9'8"* feet; 7th story, *✓* feet.
3. How are the hall partitions to be constructed and of what materials? *8" x 12" brick walls & 2" x 8" b. blocks & angle iron frame to first story entrance hall*
4. How many buildings are to be taken down? *two*

Owner *J. L. Buttonweiser* Address *237 East 60th St.*
 Architect *G. F. Pellham* Address *1003 7th St.*
 Mason _____ Address _____
 Carpenter _____ Address _____

If a Wall or part of a Wall already built is to be used, fill up the following.

The undersigned gives notice that *he* intend to use the *plaster* *Castles* wall of building *No 75 Seventh St.*

as party wall in the erection of the building hereinbefore described, and respectfully requests that the same be examined and a permit granted therefor. The foundation wall *is* built of *Stone* *24* inches thick, *10* feet below curb; the upper wall *is* built of *Brick*, *12* inches thick, *at 46* feet deep, & *40* feet in height.

This wall is used by Bldg. 77 Seventh St. by beam right.

(Sign here)

G. F. Pellham Archt.

NOTE—In making application for the erection of buildings, the following drawings must be furnished: Plans of each and every story, front, rear and side elevations, and longitudinal and transverse sections. All plans must be drawn to a uniform scale, and must be on tracing cloth, properly designated and colored.

THE BUILDING LAW REQUIRES:

- 1st—That all stone walls shall be properly bonded and laid in cement mortar.
- 2d—That all skylights having a superficial area of more than nine square feet, placed in any building, shall have the sashes and frames thereof constructed of iron and glass.
- 3d—That every building which is more than two stories in height above the curb level, except dwelling-houses, hotels, school-houses and churches, shall have doors, blinds or shutters made of iron, hung to iron hanging frames or to iron eyes built into the wall, on every window and opening above the first story thereof, excepting on the front openings of buildings fronting on streets which are more than thirty feet in width. Or the said doors, blinds or shutters may be constructed of pine or other soft wood of two thicknesses of matched boards at right angles with each other, and securely covered with tin, on both sides and edges, with folded lapped joints, the nails for fastening the same being driven inside the lap; the hinges and bolt, or latches shall be secured or fastened to the door or shutter after the same has been covered with the tin, and such doors or shutters shall be hung upon an iron frame, independent of the woodwork of the windows and doors, or two iron hinges securely fastened in the masonry; or such frames, if of wood, shall be covered with tin in the same manner as the doors and shutters.
- 4th—That outside fire escapes shall be placed on every dwelling-house occupied by or built to be occupied by three or more families above the first story, and every building already erected, or that may hereafter be erected, more than three stories in height, occupied and used as a hotel or lodging house, and every boarding-house, having more than fifteen sleeping-rooms above the basement story, and every factory, mill, manufactory or workshop, hospital, asylum or institution for the care or treatment of individuals, and every building in whole or in part occupied or used as a school or place of instruction or assembly, and every office building five stories or more in height, all to be constructed as follows:

BALCONIES MUST NOT BE LESS THAN THREE FEET WIDE.

- BRACKETS** must not be less than $\frac{3}{4} \times 1\frac{3}{4}$ inches wrought iron, placed edgewise, or $1\frac{1}{4}$ inch angle iron $\frac{1}{4}$ inch thick, well braced, and not more than three feet apart, and the braces to brackets must be not less than $\frac{3}{4}$ inch square wrought iron, and must extend two-thirds of the width of the respective brackets or balconies. In all cases the brackets must go through the wall, and be turned down three inches.
- BRACKETS ON NEW BUILDINGS** must be set as the walls are being built. When brackets are to be put on old houses, the part going through the wall shall not be less than one inch diameter, with screw nuts and washers not less than five inches square and $\frac{1}{4}$ inch thick.
- TOP RAILS.**—The top rail of balcony must be $1\frac{1}{4}$ inch \times $\frac{3}{4}$ inch wrought iron or $1\frac{1}{4}$ inch angle iron $\frac{1}{4}$ inch thick, and in all cases must go through the walls, and be secured by nuts and 4 inch square washers, at least $\frac{3}{8}$ inch thick, and no top rail shall be connected at angles by the use of cast iron.
- BOTTOM RAILS.**—Bottom rails must be $1\frac{1}{4}$ inch \times $\frac{3}{4}$ inch wrought iron or $1\frac{1}{4}$ inch angle iron $\frac{1}{4}$ inch thick, well leaded into the wall. In frame buildings the top rails must go through the studding and be secured on the inside by washers and nuts as above.
- FILLING-IN BARS.**—The filling-in bars must be not less than $\frac{1}{2}$ inch round or square wrought iron, placed not more than 6 inches from centres, and well riveted to the top and bottom rails.
- STAIRS.**—The stairs in all cases must be not less than 18 inches wide, and constructed of $\frac{3}{4} \times 3\frac{1}{2}$ inch wrought iron sides or strings. Steps may be of cast iron of the same width of strings, or $\frac{5}{8}$ inch round iron, double rungs, and well riveted to the strings. The stairs must be secured to a bracket on top and rest on and be secured to a bracket or extra cross bar at the bottom. All stairs must have a $\frac{3}{4}$ inch hand rail of wrought iron, well braced.
- FLOORS.**—The flooring of balconies must be of wrought iron $1\frac{1}{4} \times \frac{3}{4}$ inch slats placed not over $1\frac{1}{4}$ inches apart, and secured to iron battens $1\frac{1}{2} \times \frac{5}{8}$ inch, not over three feet apart and riveted at the intersection. The openings for stairways in all balconies shall not be less than 20 inches wide and 30 inches long, and have no covers.
- DROP LADDERS.**—Drop ladders from lower balconies where required shall not be less than 14 inches wide, and shall be made of $1\frac{1}{2} \times \frac{5}{8}$ inch sides and $\frac{5}{8}$ inch rungs of wrought iron. In no case shall a drop ladder be more than 12 feet in length. In no case shall the ends of balconies extend more than nine inches over the brackets.
- SCUTTLE LADDERS.**—Ladders to scuttles shall be constructed in all cases the same as the stairs or step-ladders from balconies of fire escapes.
- THE HEIGHT OF RAILING** around balconies shall not be less than two feet nine inches.

No Fire Escape will be approved by the Superintendent of Buildings if not in accordance with above specifications.

In constructing all balcony fire-escapes, the manufacturer thereof shall securely fasten thereto, in a conspicuous place, a cast-iron plate having suitable raised letters on the same, to read as follows: Notice! Any person placing any incumbrance on this balcony is liable to a penalty of ten dollars and imprisonment for ten days.

- 5th—That all exterior and division or party walls over fifteen feet high, excepting where such walls are to be finished with cornices, gutters or crown mouldings, shall have parapet walls carried two feet above the roof, and shall be coped with stone, well-burnt terra-cotta or cast iron.
- 6th—That every building and the tops and sides of every dormer-window thereon shall be covered and roofed with slate, tin, copper or iron, or such other quality of fire-proof roofing as the superintendent of buildings, under his certificate, may authorize.
- 7th—That all exterior cornices shall be fire proof.
- 8th—That the stone or brick work of all smoke flues, and the chimney shafts of all furnaces, boilers, bakers' ovens, large cooking ranges and laundry stoves, and all flues used for a similar purpose, shall be at least eight inches in thickness. If there is a cast-iron or burnt clay pipe built inside of the same, with one-inch air space all around it, then the stone or brick work inclosing such pipes shall not be less than four inches in thickness.
- 9th—That before any iron or steel beam, lintel or girder intended to span an opening over ten feet in length in any building, shall be used for supporting a wall, it shall be inspected, tested and approved as provided by law.

Applicant must indicate the Building Line of Lines clearly and distinctly on the Drawings

B 449
L 44

2

Office of the Borough President of the Borough of Manhattan,
In The City of New York.

THE BUREAU OF BUILDINGS FOR THE BOROUGH OF MANHATTAN,
Office, No. 220 FOURTH AVENUE,
S. W. Corner 18th Street.

Plan No. 1512

APPLICATION TO ALTER, REPAIR, ETC.

Application is hereby made to the Superintendent of Buildings of The City of New York, for the Borough of Manhattan, for the approval of the detailed statement of the specifications and plans herewith submitted for the alteration or repairs of the building herein described. All provisions of the Law shall be complied with in the alteration or repair of said building, whether specified herein or not.

(Sign here)

Chas. B. Meyer

THE CITY OF NEW YORK, BOROUGH OF MANHATTAN June 23 1909

LOCATION AND DESCRIPTION OF PRESENT BUILDING.

1. State how many buildings to be altered One
2. What is the exact location thereof? (State on what street or avenue, the side thereof, the number of feet from the nearest street or avenue, and the name thereof) W. 5th St.
175'-0" west of 1st Ave.
#75 (E) 5th St.
3. How was the building occupied? Tenement
How is the building to be occupied? "
4. Is the building on front or rear of lot? Front Is there any other building erected on lot or permit granted for one? No Size _____ x _____; height _____ How occupied? _____ Give distance between same and proposed building _____ feet.
5. Size of lot? 25'-0" feet front; 25'-0" feet rear; 100'-0" feet deep.
6. Size of building which it is proposed to alter or repair? 25'-0" feet front; 25'-0" feet rear; 85'-9" feet deep. Number of stories in height? 6 stories + cellar Height from curb level to highest point? 62'-0"
7. Depth of foundation walls below curb level? 10'-0" Material of foundation walls? Stone & Brk. Thickness of foundation walls? front _____ inches; rear 24 inches; side 24 inches; party 24 inches.
8. Material of upper walls? Brick If ashlar, give kind and thickness none
9. Thickness of upper walls:
Basement: front _____ inches; rear _____ inches; side _____ inches; party _____ inches.
1st story: " " " " " " " " " "
2d story: " " " " " " " " " "
3d story: " " " " " " " " " "
4th story: " " " " " " " " " "
5th story: " " " " " " " " " "
6th story: " " " " " " " " " "
10. Is roof flat, peak or mansard? Flat

11. Size of present extension, if any? _____ feet front; _____ feet deep; _____ feet high.

12. Thickness and material of foundation walls? _____

13. Material of upper walls? _____ If ashlar, give kind and thickness _____

14. Thickness of upper walls :
Basement: front _____ inches; rear _____ inches; side _____ inches; party _____ inches.
1st story: " _____ " _____ " _____ " _____ " _____ " _____ "
2d story: " _____ " _____ " _____ " _____ " _____ " _____ "
3d story: " _____ " _____ " _____ " _____ " _____ " _____ "
4th story: " _____ " _____ " _____ " _____ " _____ " _____ "

15. Is present building provided with a fire escape? _____

If to be extended on any side, give the following information :

16. Is extension to be on side, front or rear? _____

17. Size of proposed extension, feet front _____; feet rear _____; feet deep _____; number of stories in height? _____ number of feet in height? _____

18. Material of foundation walls? _____; depth _____ feet; material of base course _____; thickness of base course _____; thickness of foundation walls, front _____ inches; side _____ inches; rear _____ inches; party _____ inches.

19. Will foundation be on rock, sand, earth or piles? _____

20. What will be the size of piers in cellar? _____; distance on centres? _____; size of base of piers? _____; thickness of cap stones? _____; of bond stones? _____

21. Material of upper walls? _____; material of front? _____

22. Thickness, exclusive of ashlar, of upper walls :
1st story: front _____ inches; rear _____ inches; side _____ inches; party _____ inches.
2d story: " _____ " _____ " _____ " _____ " _____ " _____ "
3d story: " _____ " _____ " _____ " _____ " _____ " _____ "
4th story: " _____ " _____ " _____ " _____ " _____ " _____ "
5th story: " _____ " _____ " _____ " _____ " _____ " _____ "
6th story: " _____ " _____ " _____ " _____ " _____ " _____ "

23. With what will walls be coped? _____

24. Will roof be flat, peak, or mansard? _____; material _____

25. Give size and material of floor and roof beams _____

1st tier, material _____; size _____; distance on centres _____
2d tier, " _____ " _____ " _____ " _____ "
3d tier, " _____ " _____ " _____ " _____ "
4th tier, " _____ " _____ " _____ " _____ "
5th tier, " _____ " _____ " _____ " _____ "
Roof tier, " _____ " _____ " _____ " _____ "

Give thickness of headers _____ of trimmers _____

26. Give material of girders _____ of columns _____

Under 1st tier, size of girders _____; size of columns _____
" 2d " " " _____; " " _____
" 3d " " " _____; " " _____
" 4th " " " _____; " " _____
" 5th " " " _____; " " _____
" Roof tier, " " " _____; " " _____

27. If front, rear or side is to be supported on columns or girders, give :

Girders, material _____ ; front _____ ; side _____ ; rear _____
size _____ " _____ " _____ " _____
Columns, material _____ " _____ " _____ " _____
size _____ " _____ " _____ " _____

28. If constructed of frame, give material _____ ; size of sill _____ ;
plate _____ ; enterties _____ ; posts _____ ; studs _____ ;
braces _____

29. If open on one side, give size of plate _____ posts _____

30. How will extension be occupied ? _____ If for
dwelling, give number of families on each floor _____

31. How will extension be connected with main building ? _____

32. Give size of skylights _____ ; material _____

33. Give material of cornices _____

34. Give material of light shafts _____ ; size _____

If to be increased in height, give the following information :

35. Will building be raised from foundation, or extended on top? Give particulars _____

36. How many stories high will building be when raised ? _____ ; feet high _____

37. Will the roof be flat, peak or mansard ? _____ ; material _____

38. Material of coping ? _____

39. Give material of new walls _____ thickness of _____ story _____ inches ;
_____ story _____ inches ; _____ story _____ inches ; _____ story
_____ inches ; _____ story _____ inches ; _____ story _____ inches ;
_____ story _____ inches.

40. Material of floor beams ? _____ Size _____ tier _____
centres _____ ; _____ tier _____ ; centres _____ ; _____ tier _____
centres _____ ; _____ tier _____ ; centres _____ ; _____ tier _____
centres _____

41. Material of girders ? _____ Size under 1st tier _____ ;
2d tier _____ ; 3d tier _____ ; 4th tier _____ ; 5th tier _____ ;
6th tier _____

42. Material of columns ? _____ Size under 1st tier _____ ; 2d tier _____ ;
3d tier _____ ; 4th tier _____ ; 5th tier _____ ; 6th tier _____

43. Size of piers in cellar _____ ; distance on centres _____ ; thickness of cap stones
to piers _____ ; bond stones _____

44. If constructed of frame, give material of frame _____ ; size of sills _____ ;
corner posts _____ ; middle posts _____ ; enterties _____ ; plates _____
braces _____ ; studs _____

45. How will building be occupied when altered ? _____
If for dwelling, state number of families on each floor ? _____

46. With what kind of fire escape will building be provided ? _____

If the Front, Rear or Side Walls, or any portion thereof, are to be taken out and rebuilt, give definite particulars, and state in what manner :

47. *It is proposed to construct bathroom compartment in cellar as shown on plans Construct new windows of size as shown on plans Construct all work shown colored Remove " " " dotted.*

If altered internally, give definite particulars, and state how the building will be occupied :

48. _____

49. How much will the alteration cost? *\$1500 00 / 100*

If the Building is to be occupied as a Flat, Apartment or Lodging House, give the following particulars :

50. Is any part of building to be used as a store or for any other business purpose, if so, state for what?

	Cellar	Base-ment	1st Floor	2d Floor	3d Floor	4th Floor	5th Floor	6th Floor
51. How many families will occupy each?	-	-						
52. Height of ceilings?	-	-						

53. How basement to be occupied?
 How made water-tight?

54. Will cellar or basement ceiling be plastered? _____ How? _____

55. How will cellar stairs be enclosed? _____

56. How will cellar be occupied?
 How made water-tight? _____

57. Will shafts be opened or covered with louvre skylights full size of shafts? _____

Size of each shaft? _____

58. Dimensions of water closet windows? _____
 Dimensions of windows for living rooms? _____
59. Of what materials will hall partitions be constructed? _____

60. Of what materials will hall floors be constructed? _____

61. How will hall ceilings and soffits of stairs be plastered? _____
62. Of what material will stairways be constructed? _____
 Give sizes of stair well holes? _____
63. If any other building on lot, give size ; front _____ ; rear _____ ; deep _____ ;
 stories high _____ ; how occupied _____ ; on front or rear
 of lot _____ ; material _____
 How much space between it and proposed building? _____
64. How will floors and sides of water closets to the height of 16 inches be made waterproof? _____

65. Number and location of water closets : Cellar _____ ; 1st floor _____ ; 2d floor _____ ;
 3d floor _____ ; 4th floor _____ ; 5th floor _____ ; 6th floor _____ ;
66. This building will safely sustain per superficial foot upon the 1st floor _____ lbs. ; upon 2d floor
 _____ lbs. ; upon 3d floor _____ lbs. ; upon 4th floor _____ lbs. ; upon 5th floor
 _____ lbs. ; upon 6th floor _____ lbs. ; upon 7th floor _____ lbs. ; upon 8th floor
 _____ lbs.

Owner, Henrietta Studensky Address, 377. 104th St.
 Architect, Chas. B. Meyers " Union Sq. N.
 Superintendent, Quandre " _____
 Mason, _____ " _____
 Carpenter, _____ " _____

BUREAU OF BUILDINGS

BOROUGH OF MANHATTAN, CITY OF NEW YORK

NOTICE—This Application must be TYPEWRITTEN and filed in TRIPLICATE.

“SPECIFICATIONS—SHEET A” [Form 152] must be filed with EVERY Alteration Application.

“SPECIFICATIONS—SHEET B” [Form 158] must be filed, in addition, in case the building is to be raised in height or occupancy changed so as to increase floor loads, or if building is to be enlarged on one side.

ALT. APPLICATION No. 5000 1916

LOCATION 75 Seventh Street, Manhattan.

Examined June 4 1916

A. J. Pappeberg
Examiner

SPECIFICATIONS—SHEET A

(1) NUMBER OF BUILDINGS TO BE ALTERED **one**
Any other building on lot or permit granted for one? **no**

(2) ESTIMATED COST OF ALTERATION: **\$ 10.00**

(3) OCCUPANCY (in detail):
Of present building **Stores and dwellings.**
Of building as altered **Stores and dwellings.**

(4) SIZE OF EXISTING BUILDING:

At street level	25	feet front	86	feet deep
At typical floor level		feet front		feet deep
Height	6	stories		feet

(5) SIZE OF BUILDING AS ALTERED:

At street level	25	feet front	86	feet deep
At typical floor level		feet front		feet deep
Height	6	stories		feet

(6) CHARACTER OF CONSTRUCTION OF PRESENT BUILDING: **Fireproof.**

[Frame, Ordinary or Fireproof]

(7) STATE GENERALLY IN WHAT MANNER THE BUILDING WILL BE ALTERED:

Two lath and plaster partitions (Cross) between two bath-rooms in rear of westerly store to be removed.

Two door openings from said two bath-rooms to hall to be closed up.

Two bath tubs will be removed.

New Wash-Basin to be installed in rear of store and wood dwarf partition 6' high.

BUREAU OF BUILDINGS

BOROUGH OF MANHATTAN, CITY OF NEW YORK

JAN 28 1930

NOTICE—This Application must be TYPEWRITTEN and filed in TRIPPLICATE.
"SPECIFICATIONS—SHEET A" (Form 152) must be filed with EVERY Alteration Application.
"SPECIFICATIONS—SHEET B" (Form 158) must be filed, in addition, in case the building is to be raised in height or occupancy changed so as to increase floor loads, or if building is to be enlarged on one side.

ALT. APPLICATION No. 192 BLOCK 445 LOT 44

LOCATION 75 West 131st Street

DISTRICT (under building zone resolution) Use Business Height 3 Area 3

Examined 192 Examiner.

SPECIFICATIONS—SHEET A

(1) NUMBER OF BUILDINGS TO BE ALTERED one
Any other building on lot or permit granted for one? no

(2) ESTIMATED COST OF ALTERATION: \$ 10,000.

(3) OCCUPANCY (in detail):
Of present building stores and tenement.

Of building as altered same.

(4) SIZE OF EXISTING BUILDING:				
At street level	<u>35</u>	feet front	<u>30</u>	feet deep
At typical floor level	<u>35</u>	feet front	<u>30</u>	feet deep
Height	<u>3</u>	stories	<u>35</u>	feet

(5) SIZE OF BUILDING AS ALTERED:				
At street level	<u>same</u>	feet front	<u>same.</u>	feet deep
At typical floor level	<u>same</u>	feet front	<u>same.</u>	feet deep
Height	<u>same</u>	stories	<u>same.</u>	feet

(6) CHARACTER OF CONSTRUCTION OF PRESENT BUILDING: ordinary brick
[Frame, Ordinary or Fireproof]

(7) NUMBER OF OCCUPANTS (in each story of building as altered, giving males and females separately in the case of factories):
no change in occupancy

(8) STATE GENERALLY IN WHAT MANNER THE BUILDING WILL BE ALTERED:

It is proposed to re-arrange rooms in each floor for two families in each of the 2nd to 6th floors and one family in first floor and store in front, install new bathrooms and remove some old partitions and construct new partitions as shown; also remove the main entrance in centre of building and construct new entrance at east side of building; install new metal flue for steam boiler as shown and construct incinerator and flue for same in place of old dumbwaiter, also construct new store front, all as called for on plans.

THE CITY OF NEW YORK DEPARTMENT OF BUILDINGS

ORIGINAL

MANHATTAN Municipal Bldg., New York 7

BROOKLYN Municipal Bldg., Brooklyn 1

BRONX 1932 Arthur Ave., New York 57

QUEENS 120-55 Queens Blvd., Kew Gardens 24, L. I.

RICHMOND Boro Hall, St. George 1, S. I.

NOTICE - This Application must be TYPEWRITTEN and filed in QUADRUPPLICATE.

REPLACEMENT OF OIL BURNING EQUIPMENT

66

F.P.

66

JAN 16 1961

CITY OF NEW YORK BOROUGH OF MANHATTAN

DO NOT WRITE IN THIS SPACE

BLOCK 449 LOT 44

LOCATION 75 E. 7 St.

BOROUGH Man.

Fee Computation \$ 15.00

JAN 13 1961 213402 SL 66 51 FID 15.00

FEE PAID

TO THE BOROUGH SUPERINTENDENT

Date Jan. 6, 1961

I hereby file notice of the replacement of oil burning equipment at the above premises which does not effect a change in any of the following: (1) The design of the combustion chamber. (2) The maximum capacity (gross BTU per hour input). (3) The method of atomization. (4) The grade of fuel oil.

The replacement consists of Burner only in Multiple Dwelling

and that I have not and will not make any other changes in the existing oil burning equipment.

If burner is replaced give the following information:

Old Burner Petro (NAME) is replaced by (MODEL NUMBER)

New Burner Heveoil (NAME) Am4DH (MODEL NUMBER) 948-40 (B.S.A. CALENDAR NUMBER)

(Note: If any equipment replaced requires a Board of Standards and Appeals approval, give name, model number and calendar number.)

Where a fuel oil storage tank is specified above as a replacement, the existing tank has a capacity of 275 gallons or less and is located above ground. The new tank is of the same capacity and will be installed in the same location.

The existing oil burning equipment installation is not included in the following: (IS) OR (IS NOT)

- 1. The fuel oil storage tank has a capacity greater than 275 gallons or
2. The fuel oil storage tank has a capacity of 275 gallons or less and is buried or delivers oil to a burner installed above the lowest floor of a business building; or the building is occupied as a multiple dwelling or a place of public assembly; or the building is located along the line of a subway.

I hereby certify the accuracy of the statements in this notification and that I have made or will make this replacement and to the best of my knowledge and belief it will or does conform with the Administrative Code, the Oil Burner Rules of the Board of Standards and Appeals and the rules of the Department of Air Pollution Control.

I have Workmen's Compensation Insurance as follows:

Pub. Svc. Mut. Ins. Co. 02 36058 1/1/62
INSURANCE COMPANY POLICY NO. EXPIRES

Barrow Oil Burner Corp. 100 Dobbin St., Bklyn.
NAME OF INSURED ADDRESS

Fred Feilenbaum 100 Dobbin St., Bklyn.
NAME OF LICENSED INSTALLER ADDRESS OF LICENSED INSTALLER

License No. 1456 CLASS B 2/28/61 EXPIRES
SIGNATURE OF LICENSED INSTALLER

Falsification of any statement is an offense under Section 982-9.0 of the Administrative Code and is punishable by a fine of not more than five hundred dollars (\$500.00) or imprisonment of not more than sixty (60) days or both.

Recommended for approval

JAN 20 1961
DATE OF RECEIPT

BOROUGH SUPERINTENDENT

RECEIVED BY CLERK

On I inspected the above premises and found the replacement described in this notification has been made in compliance with all applicable requirements.

Signed PLUMBING INSPECTOR

Vertical handwritten signature on the right margin.

OK. 1/11/61 mb