

IF THE BUILDING IS TO BE OCCUPIED AS AN APARTMENT OR TENEMENT HOUSE,
GIVE THE FOLLOWING PARTICULARS.

1. State how many families are to occupy each floor, and the whole number in the house; also, if any part is to be used as a store or for any other business purposes, state the fact. *one family partly on 3^d & 4th floors. the rest for meeting purposes.*
 2. What will be the heights of ceilings? 1st story, *9* feet; 2d story, *13* feet; 3d story, *11* feet; 4th story, *11* feet; 5th story, *10* feet; 6th story, *✓* feet; 7th story, *✓* feet.
 3. How are the hall partitions to be constructed and of what materials? *Wood*
- Owner *Corporation Odd Fellows Hall of* Address *President & Nidebrandt 229 E. 31st St*
 Architect *M. C. Rohue* Address *822 B. Way*
 Mason _____ Address _____
 Carpenter _____ Address _____

IF A WALL OR PART OF A WALL ALREADY BUILT IS TO BE USED, FILL UP
THE FOLLOWING.

The undersigned give notice that _____ intend to use the _____ wall of building _____ as party wall in the erection of the building hereinbefore described, and respectfully requests that the same be examined and a permit granted therefor. The foundation wall _____ built of _____ inches thick, _____ feet below curb; the upper wall _____ built of _____ inches thick, _____ feet deep, _____ feet in height.

(Sign here) _____

NOTE.—In making application for the erection of buildings the following drawings must be furnished: Plans of each and every story, front, rear and side elevations, and longitudinal and transverse sections. All plans must be drawn to a uniform scale and must be on tracing cloth, properly designated and colored.

THE BUILDING LAW REQUIRES:

- 1st—All stone walls must be properly bonded.
- 2d—All skylights having a superficial area of more than 9 square feet must be of iron and glass.
- 3d—All buildings over two stories or above 25 feet in height, *except dwellings, school houses, and churches,* on streets less than 30 feet wide, must have iron shutters on every window and opening above the 1st story. The front windows on streets over 30 feet wide are exempted.
- 4th—Outside fire escapes are required on all dwelling houses over two stories in height, occupied or built to be occupied by two or more families on any floor above the first, and on dwellings more than four stories in height, occupied by three or more families above the first floor, and on office buildings, hotels and lodging houses, factories, mills, workshops, hospitals, asylums and schools, all to be constructed as follows:

BRACKETS must not be less than $\frac{1}{2} \times 1\frac{3}{4}$ inches wrought iron, placed edgewise, or $1\frac{3}{4}$ inch angle iron $\frac{1}{4}$ inch thick, well braced, and not more than three feet part, and the braces to brackets must be not less than $\frac{3}{4}$ inch square wrought iron, and must extend two-thirds of the width of the respective brackets or balconies. In all cases the brackets must go through the wall, and be turned down three inches.

BRACKETS ON NEW BUILDINGS must be set as the walls are being built. When brackets are to be put on old houses, the part going through the wall shall not be less than one inch diameter, with screw nuts and washers not less than five inches square and $\frac{1}{4}$ inch thick.

TOP RAILS.—The top rail of balcony must be $1\frac{3}{4}$ inch \times $\frac{1}{2}$ inch wrought iron, or $1\frac{3}{4}$ inch angle iron $\frac{1}{4}$ inch thick, and in all cases must go through the walls, and be secured by nuts and 4 inch square washers, at least $\frac{3}{4}$ inch thick, and no top rail shall be connected at angles by the use of cast iron.

BOTTOM RAILS.—Bottom rails must be $1\frac{1}{4}$ inch \times $\frac{3}{4}$ inch wrought iron, or $1\frac{1}{4}$ inch angle iron $\frac{1}{4}$ inch thick, well leaded into the wall. In frame buildings the top rails must go through the studding and be secured on the inside by washers and nuts as above.

FILLING-IN BARS.—The filling-in bars must be not less than $\frac{1}{2}$ inch round or square wrought iron, placed not more than 6 inches from centres, and well riveted to the top and bottom rails.

STAIRS.—The stairs in all cases must be not less than 18 inches wide, and constructed of $\frac{1}{4} \times 3\frac{1}{2}$ inch wrought iron sides or strings. Steps may be of cast iron of the same width of strings, or $\frac{3}{4}$ inch round iron, double rungs, and well riveted to the strings. The stairs must be secured to a bracket on top and rest on and be secured to a bracket or extra cross bar at the bottom. All stairs must have a $\frac{3}{4}$ inch hand rail of wrought iron, well braced.

FLOORS.—The flooring of balconies must be of wrought iron $1\frac{1}{2} \times \frac{3}{4}$ inch slats placed not over $1\frac{1}{4}$ inches apart, and secured to iron battens $1\frac{1}{4} \times \frac{3}{8}$ inch, not over three feet apart and riveted at the intersection. The openings for stairways in all balconies shall not be less than 20 inches wide and 30 inches long, and have no covers.

DROP LADDERS.—Drop ladders from lower balconies where required shall not be less than 14 inches wide, and shall be made of $1\frac{1}{2} \times \frac{3}{8}$ inch sides and $\frac{5}{8}$ inch rungs of wrought iron. In no case shall a drop ladder be more than 12 feet in length. In no case shall the ends of balconies extend more than nine inches over the brackets.

SCUTTLE LADDERS.—Ladders to scuttles shall be constructed in all cases the same as the stairs or step-ladders from balconies of fire escapes.

THE HEIGHT OF RAILING around balconies shall not be less than two feet nine inches.

No Fire Escape will be approved by this Bureau if not in accordance with above specifications.

- 5th—All walls must be coped with stone or terra cotta. If coped with stone, the stone must not be less than $2\frac{1}{2}$ inches thick; and if with terra cotta, the terra cotta must be made with proper lap joints.
- 6th—Roofs must be covered with fire-proof material.
- 7th—All cornices must be fire-proof.
- 8th—All FURNACE FLUES OF DWELLING HOUSES shall have at least eight inch walls on each side. No furnace flues shall be of less size than eight inches square, or four inches wide and sixteen inches long, inside measure. If preferred, the furnace flues may be made of cast iron or fire-clay pipe of proper size built in the walls, with an air space of not less than one inch between said pipes, and four inches of brick wall on the outside.
All flues not built for furnace or boiler flues must be altered to conform to the above requirements before they are used as such.
- 9th—No iron beam, lintel, or girder, intended to span an opening over eight feet, intended to support a wall, shall be used for that purpose, *until tested and approved as provided by law.*

Plan No. *1756 N. B.* 1889

Received. DEC 3 1889

Report of Test of Iron Beams, Lintels and Girders.

New York, Dec. 2 1889

To the Superintendent of Buildings:

I respectfully report that the iron girders, beams, and lintels, described in the application for *New Building*, Plan No. *1756* 1889, were inspected by me with the following result:

Tested to	<i>3-20" Heavy</i>	Tons	<i>91</i>	, Deflected		inches.
"	<i>3-15"</i>	"	<i>78</i>	"		"
"		"		"		"

Permanent Set.

I hereby certify, by the foregoing inspection that the above *Beams are* sufficient to bear the weight to be imposed thereon, agreeably to the requirements of the foregoing application, and having approved of the same, I have placed the mark of the Department thereon.

Thomas Little
Inspector of Iron Work.

REMARKS.

The 20 inch beams as above described span an opening of 21 feet, load 76 1/2 tons. The 15 inch beams span an opening of 14 feet, load 38 1/2 tons
T. L.

B450

L40

1134

Original

DEPARTMENT OF BUILDINGS

1343

2

APPLICATION TO ALTER, REPAIR, ETC.

Application is hereby made to alter as per subjoined detailed statement of specification for Alterations, Additions or Repairs to buildings already erected, and we herewith submit Plans and Drawings of such proposed alterations; and we do hereby agree that the provisions of the Building Law will be complied with, whether the same are specified herein or not.

(Sign here)

Frohne & Kuhn Architects

NEW YORK, June 16, 1893

- 1. State how many buildings to be altered. one
2. What is the street or avenue and the number thereof? Give diagram of property. #69th Mark Place (East 8th Street)
3. How much will the alteration cost? \$ 600.

GIVE THE FOLLOWING INFORMATION AS TO THE PRESENT BUILDING:

- 1. Size of lot on which it is located, No. of feet front, 25; feet rear, 25; feet deep, 25-10
2. Size of building, No. of feet front, 25; feet rear, 25; feet deep, 22-1'; No. of stories in height, 5; No. of feet in height from curb level to highest point of beams, 5-9
3. Material of building, brick; material of front, brick
4. Whether roof is peak, flat, or mansard, flat
5. Depth of foundation walls, 10 feet; thickness of foundation walls, 2'-0" & 1'-8"; materials of foundation walls, brick
6. Thickness of upper walls, 16" & 12" inches. Material of upper walls, brick
7. Whether independent or party walls, independent walls on both sides
8. How the building is or was occupied, clubhouse

IF TO BE RAISED OR BUILT UPON, GIVE THE FOLLOWING INFORMATION:

- 1. How many stories will the building be when raised?
2. How high will the building be when raised?
3. Will the roof be flat, peak, or mansard?
4. What will be the thickness of wall of additional stories? story, inches;
5. Give size and material of floor beams of additional stories; 1st tier, 2d tier, Distance from centres on tier, inches; tier inches.
6. How will the building be occupied?

IF TO BE EXTENDED ON ANY SIDE, GIVE THE FOLLOWING INFORMATION.

- 1. Size of extension, No. feet front, feet rear, feet deep, No. of stories in height, No. of feet in height.
2. What will be the material of foundation walls of extension? What will be the depth? feet. What will be the thickness? inches.
3. Will foundation be laid on earth, sand, rock, timber or piles?

Handwritten scribbles at the bottom of the page.

IF TO BE EXTENDED ON ANY SIDE GIVE THE FOLLOWING INFORMATION.

4. What will be the base, stone or concrete? If base stones, give size and thickness and how laid, If concrete, give thickness,
5. What will be the sizes of piers? What will be the sizes of the base of piers?
6. What will be the thickness of upper walls? 1st story, inches; 2d story, inches; 3d story, inches; 4th story, inches; 5th story, inches; 6th story, inches; 7th story, inches; from thence to top, inches; and of what materials to be constructed,
7. State whether independent or party-walls. If party-walls give thickness thereof.
8. With what material will walls be coped?
9. What will be the materials of front? If of stone, what kind? Give thickness of front ashlar. Give thickness of backing.
10. Will the roof be flat, peaked or mansard?
11. What will be the materials of roofing?
12. Give size and material of floor beams, 1st tier, x; 2d tier, x; 3d tier, x; 4th tier, x; 5th tier, x; 6th tier, x; 7th tier, x; roof tier, x State distance from centres on 1st tier, inches; 2d tier, inches; 3d tier, inches; 4th tier, inches; 5th tier, inches; 6th tier, inches; 7th tier, inches; roof tier, inches
13. If floors are to be supported by columns and girders, give the following information: Size and material of girders under 1st floor, x under each of the upper floors, Size and material of columns under first floor, under each of the upper floors,
14. If the front, rear or side walls are to be supported, in whole or in part, by iron girders or lintels, give definite particulars,
15. If girders are to be supported by brick piers and columns, state the size of piers and columns.
16. How will the extension be connected with present or main building?
17. How will the extension be occupied? If for dwelling purposes, state how many families are to occupy each floor.
18. State who will superintend the alterations.
19. How many buildings are to be taken down?

IF ALTERED INTERNALLY, GIVE DEFINITE PARTICULARS AND STATE HOW THE BUILDING WILL BE OCCUPIED:

Some of the old partitions & water closets on first story to be taken out & replaced - see accompanying plans.

IF THE FRONT, REAR, OR SIDE WALLS, OR ANY PORTION THEREOF, ARE TO BE TAKEN OUT AND REBUILT, GIVE DEFINITE PARTICULARS, AND STATE IN WHAT MANNER:

New windows to be built on 1st, 2nd, 3rd, 4th, & 5th story (2 windows on easterly wall, 1 on westerly wall) of each story

ORIGINAL

DEPARTMENT OF HOUSING AND BUILDINGS
BOROUGH OF Manhattan, CITY OF NEW YORK

MANHATTAN
Municipal Bldg.,
New York 7

BROOKLYN
Municipal Bldg.,
Brooklyn 2

BRONX
1932 Arthur Ave.,
New York 57

QUEENS
120-55 Queens Blvd.,
Kew Gardens 15, L. I.

RICHMOND
Boro Hall,
St. George 1, S. I.

NOTICE—This Application must be TYPEWRITTEN and filed in TRIPLICATE, and ONE copy sworn to by Applicant. A copy must be kept in plain view on the work at all times until completion.

PERMIT Class "B" M. D.

PERMIT No. 2319 1950 N.B. } Alt.
194x ALT. } Application No. 537 19450
ELEV. }
SIGN }

LOCATION 69 St. Marks Place

BLOCK 450 LOT 40

FEES PAID FOR

NOTE—Trees in streets fronting on site are under jurisdiction of Department of Parks. They must be protected and written notification made to that Department at least 48 hours prior to commencement of work.

New York City Sept. 26th 19450

To the Borough Superintendent:

Application is hereby made for a PERMIT to perform the Entire work described in the above numbered application and the accompanying plans. If no work is performed within one year from the time of issuance, this permit shall expire by limitation as provided by law; and the applicant agrees to comply with all provisions of the Building Code of the City of New York and with the provisions of all other laws and rules relating to this subject. Compensation insurance has been secured in accordance with the requirements of the Workmen's Compensation Law as follows:

Lumber Mut. Cas. #US-72469 Exp. 5-13-51

When the policy of a general contractor does not fully cover the work of any sub-contractor, such sub-contractor must file a certificate of workmen's compensation covering his particular work. No work is to be commenced by this sub-contractor until his certificate has been submitted and approved by this department.

No certificate of occupancy will be issued unless the construction work covered by this permit will be supervised by a Licensed Architect, or a Professional Engineer, or by a Superintendent of Construction, having at least ten years' experience, acceptable to the Borough Superintendent. An affidavit shall be filed indicating such supervision, as required by Section 2.1.3.7 of the Building Code.

Name and address of person designated for this supervision is as follows:

Name William Glaser Address 103 Park Avenue, N.Y.C.

STATE AND CITY OF NEW YORK } ss. Leo Kravitz for Glaser Contracting Co. Inc.
COUNTY OF NEW YORK } Typewrite Name of Applicant

being duly sworn, deposes and says: That he resides at Number 103 Park Avenue in the Borough of Manhattan in the City of New York, in the County of New York in the State of New York, that he is Agent for Contractor for the owner in fee of all that certain lot, piece or parcel of land, shown on the diagram annexed to the approved application and made a part thereof, situate, lying and being in the Borough of Manhattan, City of New York aforesaid, and known and designated as Number 69 St. Marks Place and therein more particularly described; that the work proposed to be done upon the said premises, in accordance with the approved application and accompanying plans is duly authorized by Emergency Shelter Inc.

(Name of Owner or Lessee)

and that Glaser Contracting Co. Inc. is duly authorized by the aforesaid Owner to make application for a permit to perform said work set forth in the approved application and accompanying plans, and all the statements herein contained are true to deponent's own knowledge.

(SIGN HERE) Leo Kravitz

Sworn to before me, this 26th day of Sept. 19450

Ruth Dorrman Notary Public or Commissioner of Deeds
RUTH DORRMANN
Commissioner of Deeds, N. Y. City
New York County Clerk's No. 22
Commission Expires May 1, 1952

Satisfactory evidence having been submitted as indicated above that compensation insurance has been secured in accordance with the Workmen's Compensation Law, a permit is hereby issued for the performance of the work described in the above numbered application and the accompanying plans.

EXAMINED AND RECOMMENDED FOR APPROVAL ON 19450

Approved 13. 19450 Examiner
Borough Superintendent

DEPARTMENT OF HOUSING & BUILDINGS
CITY OF NEW YORK

DEPARTMENT OF HOUSING AND BUILDINGS
CITY OF NEW YORK

ALTERED BUILDING

NOTICE—This Application must be TYPEWRITTEN and filed in QUADRUPLICATE

ALT. No. 537 1950 BLOCK 450 LOT 40

LOCATION 69 St. Marks Pl. N.S. 175'-0" W. of First Ave. Manhattan
House Number, Street, Distance from Nearest Corner and Borough

ZONING: USE DIST. Res. HEIGHT DIST. 1 1/2 AREA DIST. B

Initial fee payment—Amount \$ 700.00 1st Receipt No.

Date 3/27/50 Cashier

2nd payment of fee to be collected before a permit is issued—Amount \$

Verified by Date

2nd Receipt No. Date Cashier


EXAMINED AND RECOMMENDED FOR APPROVAL ON 5/9/1950 George Wesselloff Examiner.

APPROVED MAY 17 1950 194 William A. Jarella Borough Superintendent.

See C.023108

SPECIFICATIONS

- (1) Classification of Buildings to be Altered. (NOTE—See C26-238.0) Class 3
- (2) Any other buildings on lot or permit granted for one? no
Is building on front or rear of lot? front
- (3) Use and Occupancy. EXISTING Class B. Mission House
(NOTE—If a multiple dwelling, authorization of owner must be filed)
A new C of O (will) (will not) be required. yes



STORY (Include cellar and basement)	EXISTING LEGAL USE			PROPOSED OCCUPANCY						
	APTS.	ROOMS	USE	LIVE LOAD	NO. OF PERSONS			APTS.	ROOMS	USE
					MALE	FEMALE	TOTAL			
Cellar			Bir. Rm. Stor. WashRm, Ldry	grd						Boiler Rm., Storage Washroom & Laundry
1st			Off., D.R. & Kitchen	40	40	40				Offices - Dining Rm., and Kitchen
2nd			Chapel & study	100	40	40				Chapel & Study
3rd	<u>ix</u>	<u>x2</u>	2 Dorm'ties	40	<u>35</u>	35				One Family and Dormitory
4th	<u>C. 40</u>		<u>2 Dorm'ties</u>	<u>40</u>	<u>35</u>	35				two dormitories
5th	<u>19</u>	<u>3</u>	<u>1 Cam. room</u>	<u>40</u>	<u>35</u>	35				3 Dormitories

DATE

"Human kindness cometh from the Heart"



The EMERGENCY SHELTER Inc.
69 ST. MARKS PLACE, NEW YORK 3, N. Y.
Telephone Spring 7-1234

SPRING BROOK—RETREAT FOR MEN AND BOYS
Middle Island, L. I. (open all year round)
1947 AUG 7 PM 2 33
"HELPING MEN TO HELP THEMSELVES"

PRESIDENT
CHARLES L. LAWRENCE
President Lawrence Engineering & Research Corporation
SECRETARY and TREASURER
JAMES J. MOORE
Asst. Vice President
Beech-Nut Packing Co.
DIRECTOR—CHAPLAIN
REV. WALTER D. BRITT

August 6, 1947

Department of Housing and Buildings,
Violation Section, Division of Buildings
Municipal Building,
New York, 7 N Y.

Gentlemen;

RE: Violation No. 79 - 1943
Premises - 69 St. Marks Place., Boro of Manhattan.

All alterations as recommended by Department of
Housing and Building having been completed (we
hereby request application for Certificate of
Occupancy.)

Very truly yours,
EMERGENCY SHELTER, INC.,
Walter D. Britt
Walter D. Britt,
Executive Director

WDB/deg

AUG 7 1947

BOARD OF TRUSTEES: Rev. Walter D. Britt, Charles L. Lawrence, James J. Moore, Leclanche Moen, Frederick Nehring, Mrs. Nellie G. Britt, Dr. L. Judson Westfall, Leon B. De Garmo.
MIDTOWN CIVIC ORG. REPRESENTATIVES ADVISORY BOARD: Lloyd Hooper, Gen. E. Leslie Kincaid, James W. Danahay, Joseph E. Kean, William H. Bird, V. C. Jenkins, Wm. D. Rawlins, George Shakley.
DOWNTOWN ADVISORY BOARD: Andrew Hazlehurst, William J. Jung.

"An American Institution to Alleviate Human Suffering"

is punishable by a fine of not more than five hundred dollars (\$500.00) or imprisonment of not more than sixty (60) days or both.

Satisfactory evidence having been submitted as indicated above that compensation insurance has been secured in accordance with the Workmen's Compensation Law, a permit is hereby issued for the performance of the work described in the above numbered application and the accompanying plans.

EXAMINED AND RECOMMENDED FOR APPROVAL ON 19.....

5

[Handwritten signature]

Examiner

Approved.....

THE CITY OF NEW YORK

DEPARTMENT OF BUILDINGS

RECEIVED JUN 15 1964

MANHATTAN
Municipal Bldg.
New York

BROOKLYN
Municipal Bldg.,
Brooklyn 1

BRONX
1932 Arthur Ave.,
New York 57

QUEENS
120-55 Queens Blvd.,
Kew Gardens 24, L. I.

CITY OF NEW YORK
RICHMOND
Boro Hall,
St. George 1, S. I.
MANHATTAN

NOTICE—This Application must be TYPEWRITTEN and filed in QUADRUPLICATE

ALTERED BUILDING

Alt. 1798/59

BLOCK 450 LOT 40

ZONING: USE DIST. Residential

HEIGHT DIST. 1 1/2

AREA DIST. B

DO NOT WRITE IN THIS SPACE

LOCATION 69 St. Mark's Place, 175' W. of Northwest Cor. 1st Ave. Man.

House Number, Street, Distance from Nearest Corner and Borough

EXAMINED AND RECOMMENDED

FOR APPROVAL ON19.....

Examiner.

APPROVED19.....

NOV 1 - 1962

Borough Superintendent.

Initial fee payment

2nd payment of fee to be collected before a permit is issued—Amount \$.....

Verified by..... Date.....

SPECIFICATIONS

- (1) Classification of Buildings to be Altered. (NOTE—See C26-238.0) **Class 3- Non Fireproof**
- (2) Any other buildings on lot or permit granted for one? **no**
Is building on front or rear of lot? **Entire Lot**
- (3) Use and Occupancy. **Class B Mission House**
(NOTE—If a multiple dwelling, authorization of owner must be filed)
A new C of O (will) **(will not)** be required.

STORY (Include cellar and basement)	EXISTING LEGAL USE			PROPOSED OCCUPANCY						
	Arts.	ROOMS	USE	LIVE LOAD	NO. OF PERSONS			Arts.	ROOMS	USE
					MALE	FEMALE	TOTAL			
Cellar			Boiler Rm. Storage Wash Rm. Laundry	on grade	70		70			Boiler Rm. Storage Dining Rooms Kitchen
1st			Offices Dining Rm Kitchen	100	48		48			Offices Waiting Area
2nd			Chapel Study	100	40		40			Chapel Study
3rd	1	2	1 Apt. 1 Dorm.		22		22	2	2	2 Bed Rms, 1 each 1 Dorm. (20)
4th		3	2 Dorms		22		22	2	2	2 Bed Rms, 1 each 1 Dorm. (20)
5th		3	3 Dorms.		20		20	2	2	2 Bed Rms, 2 each 1 Dorm. (16)
Building complies with Sec. 67 Multiple Dwelling Law. Fire alarm system approved by Fire Department 7/3/51. Watchman's Time Clock System approved by Fire Dept. 4/19/51. Entire building will be sprinklered under Misc. 1867/61.										

JAN 14 1965

SEE NEW SPEC. SHEET FILED

(4) State generally in what manner the Building will be altered:

Cellar - complete remodeling New dining Room, Kitchen, Exit Stair,
Vent system and Sewage Ejector.
1st-partition changes - new offices and waiting area
2nd - slight remodeling - no general changes
3rd- New Toilets, showers and laundry, 2 Bedrooms, 1 Dormitory
4th- New toilets, showers and storage, 2 Bedrooms, 1 Dormitory
5th - New Toilets, and showers, 2 Bedrooms, 1 Dormitory.

(5) Size of Existing Building:

At street level	24'8"	feet front	93'0"	feet deep	24'8"	feet rear
At typical floor level	24'8"	feet front	82'0"	feet deep	24'8"	feet rear
Height ¹	5	stories	50'	feet		

(6) If volume of Building is to be changed, give the following information:

At street level	feet front	feet deep	feet rear
At typical floor level	feet front	feet deep	feet rear
Height ¹	stories	feet	

Area ² of Building as Altered: At street level	Total floor area ²	sq. ft.
Total Height ³	Additional Cubic Contents ⁴	cu. ft.

(7) Estimated Cost of Alteration:⁵ **\$60,000.00**
Estimated Cost, exclusive of extension:

(8) Is Application made to remove violations? **no** If Yes, State Violation Numbers

(9) If building is to be enlarged or extended or floor loads increased, Soil Data shall be submitted in accordance with Sec. C26-376.0. For alterations of a minor nature, the Applicant certifies that he has investigated the nature of the soil and finds the following:

Character of soil	Bearing capacity
-------------------	------------------

(10) State what disposition will be made of waste and sewage
(Public sewer, Private sewer, Cesspool, etc.) **existing public sewer**

(11) Does this Application include Dropped Curb? **no**
(If Drop Curb Permit is obtained with this Application, DIAGRAM showing the relative position of drop curb and extent thereof must be included on plot diagram.⁶)

Drop Curb	ft. @ \$	per ft. Splay	ft. @ \$	per ft.
Exact distance from nearest corner to Curb Cut:			feet.	
Deposit: \$	Fee: \$	Total: \$		
Paid	19	Document No.		Cashier

(12) Temporary Structures between Street Line and Curb: **none**
Will a Sidewalk Shed be required? Length feet.
Will any other miscellaneous temporary structures be required?
Fee Required . Fee Paid 19 . Document No. . Cashier

- The term "height" of a structure shall mean the vertical distance from the curb level to the highest point of the roof beams in the case of flat roofs or to a point at the average height of the gable in the case of roofs having a pitch of more than one foot in four and one-half, except that in the case of structures where the grade of the street has not been legally established or where the structure does not adjoin the street, the average level of all the ground adjoining such structures shall be used instead of the curb level.
- In computing this area, measurement shall be taken to the outside surfaces of exterior walls at each floor. Courts, yards, etc., shall be excluded. The areas of cellars and basements shall not be included.
- Total height shall be measured from 6 inches below the lowest finished floor to the outside of the roof, and in case of sloping roofs, to the average height.
- The cubical contents is the actual space enclosed within the outer surfaces of the outside walls and between the outer surface of the roof and six inches below the surface of the lowest floors. This includes the cube of dormers, penthouses, vaults, pits, enclosed porches, and other enclosed appendages. Outside steps, terraces, footings, courts, yards, light shafts and buildings detached from the main structure are not to be included. (Detached structures are to be separately computed.)
- "Estimated Cost" for computation purposes on alteration of existing buildings or structures shall be the cost of all contemplated construction, including plumbing work, elevator work, standpipe fire line work, automatic sprinkler, fuel oil, air conditioning, etc.
- Space for plot diagram is located on Affidavit Form.
- Use should be related to pertinent legal terms, e.g., use terms like factory rather than lift, auto repairs rather than brake testing, etc.
- If fuel burning equipment is to be installed Smoke Control Equipment Form must accompany this application.

Bribery is a Crime: A person who gives or offers a bribe to any employee of the City of New York, or an employee who takes or solicits a bribe, is guilty of a felony punishable by imprisonment for ten years or by a fine of \$4,000, or more, or both. Penal Law, Section 378 and 1826.