

718

Original

July 17

B 452

# Department of Buildings,

IN THE CITY OF NEW YORK.

L 22

OFFICE OF THE SUPERINTENDENT, No. 2 FOURTH AVENUE.

11

## DETAILED STATEMENT OF SPECIFICATIONS FOR THE ERECTION OF BUILDINGS.

17th St. Man

1. State how many buildings to be erected, 1
2. How occupied; if for dwelling, state the number of families, two or more families on each floor
3. What is the Street or Avenue, and the number thereof, No 322 330 332 334 336. 11th St
4. On which side, North, South, East, or West, South
5. How many feet from the nearest street, 150 ft
6. Whether North, South, East, or West of said street, West
7. What is the nearest street, 1st Avenue
8. Size of lot, No. of feet front, 100; No. of feet rear, 100; No. of feet deep, 94' 10"
9. Size of building, No. of feet front, 45; No. of feet rear, 45; No. of feet deep, 42; each No. of stories in height, 5; No. of feet in height, from curb level to highest point, 32
10. What will each building cost (exclusive of the lot), \$ 12500.00
11. What will be the depth of foundation walls, from curb level or surface of ground, 5 ft feet.
12. Will foundation be laid on earth, rock, timber, or piles, Earth
13. What will be the base, stone or concrete, Stone; if base stones, give size, and how laid, 3' x 4' and 8" thick; if concrete, give thickness, 8"
14. What will be the sizes of piers, —
15. What will be the sizes of the base of piers, —
16. What will be the thickness of foundation walls, 24 in and of what materials constructed, Stone in cement mortar
17. What will be the thickness of upper walls in 1st story, 16 inches; 2d story, 12 inches; 3d story, 12 inches; from thence to top, 12 inches; and of what materials to be constructed, Brick in lime & clay sand mortar
18. Whether Independent or Party walls; if Party walls, give thickness thereof, 19 in under eaves and 16 in under beams inches.
19. With what material walls to be coped, Blue Stone
20. What will be the materials of front, Brick; if of stone, what kind, —; give thickness of front ashlar, 4", and thickness of backing thereof, 1" and front 1/2 in
21. Will the roof be Flat, Peak, or Mansard, Flat
22. What will be the materials of roofing, Iron
23. What will be the means of access to roof, bulkhead & stairs
24. What will be the materials of cornices, galv. iron

Return to...

25. If there are to be skylights in roof, give size of same, and of what materials constructed, full width of bulkhead, subspan of road

26. Is the building to be provided with iron shutters or blinds, no

27. Give size and material of floorbeams, 1st tier, 3x10" x \_\_\_\_\_; 2d tier, 3x10" x \_\_\_\_\_; 3d tier, 3x9" x \_\_\_\_\_; 4th tier, 3x9" x \_\_\_\_\_; 5th tier, 3x9" x \_\_\_\_\_; 6th tier, \_\_\_\_\_ x \_\_\_\_\_; roof tier, 3x9" all round x \_\_\_\_\_. State distance from centres on 1st tier, 16 inches; 2d tier, 16 inches; 3d tier, 16 inches; 4th tier, 16 inches; 5th tier, 16 inches; 6th tier, \_\_\_\_\_ inches; roof tier, 20 inches.

28. If floors are to be supported by columns and girders, give the following information: Size and material of girders on 1st floor, 8x9" I-beam x \_\_\_\_\_; 2d floor, \_\_\_\_\_ x \_\_\_\_\_; 3d floor, \_\_\_\_\_ x \_\_\_\_\_; 4th floor, \_\_\_\_\_ x \_\_\_\_\_; 5th floor, \_\_\_\_\_ x \_\_\_\_\_; 6th or roof girders, \_\_\_\_\_ x \_\_\_\_\_. Size and material of columns on 1st floor, 6" beam x \_\_\_\_\_; 2d floor, \_\_\_\_\_ x \_\_\_\_\_; 3d floor, \_\_\_\_\_ x \_\_\_\_\_; 4th floor, \_\_\_\_\_ x \_\_\_\_\_; 5th floor, \_\_\_\_\_ x \_\_\_\_\_; 6th or roof columns, \_\_\_\_\_ x \_\_\_\_\_.

29. What will be the distance of wooden girders, beams, or timbers, from all flues, 12"

30. If any hoistways, state how protected, \_\_\_\_\_

31. Will headers and trimmers be hung in stirrup-irons, \_\_\_\_\_

32. State if any hot air, steam, or other furnaces, \_\_\_\_\_

33. If the front, rear, or side walls are to be supported in whole or in part, by iron girders or lintels, give definite particulars, fronts resting on cast iron T lintels with 12" bottom plate & proper centering, all of 12" casing & a space of 8 feet between beams

34. If girders are to be supported by brick piers and columns, state the size of piers and columns, brick piers and eight 8x12" iron posts

35. Will a Fire-Escape be provided, yes

**IF THE BUILDING IS TO BE OCCUPIED AS A TENEMENT HOUSE, GIVE THE FOLLOWING PARTICULARS:**

36. State how many families are to occupy each floor, and the whole number in the house; also, if any part is to be used as a Store or for other business purposes, state the fact, if they be there the upper stories for dwelling, two or more families on each floor

37. What will be the heights of ceilings on 1st story, 11 feet; 2d story, 9.6 feet; 3d story, 9 feet; 4th story, 9 feet; 5th story, 8.6 feet; 6th story, \_\_\_\_\_ feet.

38. State if a fire-escape is to be provided, and what kind, Balconies in rear to connect every two stories on each floor above first. Also fire alarm in front as required by law

REPORT UPON APPLICATION.

New York, 187

To the Superintendent of Buildings:

I respectfully report, that I have examined the wall named in the above application, and find the foundation wall to be built of inches thick; the upper wall built of inches thick, feet deep, feet in height, and in a good and safe condition to be used as proposed.

of Buildings.

REMARKS:

REPORT OF INSPECTOR.

New York, March 1<sup>st</sup> 1873

To the Superintendent of Buildings:

Work was commenced on the within described building on the 19<sup>th</sup> day of August 1872 and completed on the 8 day of January 1873, and has been done in accordance with the plan and specification, except as noted below.

Inspector.

REMARKS:

Reported for fire alarm

[Handwritten signature]



39. If any wood houses, state where located, and of what materials, In cellar of wood

40. How is the building to be ventilated, Fixed transoms windows over doors also, movable blinds in sides of skylights

41. How are the hall partitions to be constructed and of what materials? of wood in 1<sup>st</sup> story filled with brick, all to be set as the building progresses from story

42. How are the stairways to be constructed and of what materials? of wood, all stairs built with a 2" brick wall & iron door hung at foot of stairs

43. How are the floors and ceilings of the cellar and first story to be constructed? Scraped & planed

44. If there is any building already erected on the front or rear of the lot, give size of the same, state how occupied, (if for a tenement, state by how many families,) and how many feet of space there will be between the building proposed to be erected, and the one already erected, \_\_\_\_\_

45. Will all materials and workmanship be in accordance with the requirements of the law? Yes

46. If any walls already built are to be used as party-walls, fill up the application below.

**APPLICATION TO USE PARTY-WALLS.**

The undersigned gives notice that \_\_\_\_\_ intends to use the \_\_\_\_\_ wall of building \_\_\_\_\_ as party-wall in the erection of the building described above, and respectfully requests that the same be examined and a permit granted therefor. The foundation wall \_\_\_\_\_ built of \_\_\_\_\_, \_\_\_\_\_ inches thick; the upper wall \_\_\_\_\_ built of \_\_\_\_\_, \_\_\_\_\_ inches thick, \_\_\_\_\_ feet in height, \_\_\_\_\_ feet deep, \_\_\_\_\_

(SIGN HERE,) \_\_\_\_\_

Owner Anthony Reichardt Address W. 6 Riverside St

Architect William J. ... Address 185 ...

Mason \_\_\_\_\_ Address \_\_\_\_\_

Carpenter \_\_\_\_\_ Address \_\_\_\_\_

ORIGINAL

Applicant must indicate the Building Line or Lines clearly and distinctly on the Drawings.

B 432  
L 22

Office of the Borough President of the Borough of Manhattan,  
In The City of New York.

THE BUREAU OF BUILDINGS FOR THE BOROUGH OF MANHATTAN,  
Office, No. 220 FOURTH AVENUE,  
S. W. Corner 18th Street.

Plan No. 803

APPLICATION TO ALTER, REPAIR, ETC.

Application is hereby made to the Superintendent of Buildings of The City of New York for the Borough of Manhattan for the approval of the detailed statement of the specifications and plans herewith submitted for the alteration or repair of the building herein described. All provisions of the law shall be complied with in the alteration or repair of said building, whether specified herein or not.

(Sign here) John H. Stumbel  
THE CITY OF NEW YORK,  
BOROUGH OF MANHATTAN, April 18 1905

LOCATION AND DESCRIPTION OF PRESENT BUILDING.

- State how many buildings to be altered One
- What is the exact location thereof? (State on what street or avenue; the side thereof, the number of feet from the nearest street or avenue, and the name thereof) 325 E 11th St Tenements
- How was the building occupied? Residential  
How is the building to be occupied? Residential
- Is the building on front or rear of lot? Front Is there any other building erected on lot or permit granted for one? None Size — x —; height — How occupied? — Give distance between same and proposed building — feet.
- Size of lot? 25 feet front; 25 feet rear; 100 feet deep.
- Size of building which it is proposed to alter or repair? 65 feet front; 25 feet rear; 75 feet deep. Number of stories in height? Five Height from curb level to highest point? 60'
- Depth of foundation walls below curb level? 10" Material of foundation walls? Stone Thickness of foundation walls? front 24 inches; rear 20 inches; side 20 inches; party 28 inches.
- Material of upper walls? Brick If ashlar, give kind and thickness —
- Thickness of upper walls:  
Basement: front 24 inches; rear 20 inches; side 20 inches; party 20 inches.  
1st story: " 12 " " 12 " " 12 " " 12 "  
2d story: " 12 " " 12 " " 12 " " 12 "  
3d story: " 12 " " 12 " " 12 " " 15 "  
4th story: " 12 " " 12 " " 15 " " 12 "  
5th story: " 12 " " 12 " " 12 " " 12 "  
6th story: " — " " — " " — " " — "
- Is roof flat, peak or mansard? —

11. Size of present extension, if any? ..... feet high; ..... feet deep; .....  
 12. Thickness and material of foundation walls? .....  
 13. Material of upper walls? ..... If ashlar, give kind and thickness .....  
 14. Thickness of upper walls:  
 Basement: front ..... inches; rear ..... inches; side ..... inches; party ..... inches.  
 1st story: " " " " " " " " " "  
 2d story: " " " " " " " " " "  
 3d story: " " " " " " " " " "  
 4th story: " " " " " " " " " "  
 15. Is present building provided with a fire escape? *Yes on*

If to be extended on any side, give the following information:

16. Is extension to be on side, front or rear? .....  
 17. Size of proposed extension, feet front .....; feet rear .....; feet deep .....; number of stories in height? ..... number of feet in height? .....  
 18. Material of foundation walls? .....; depth ..... feet; material of base course .....; thickness of base course .....; thickness of foundation walls, front ..... inches; side ..... inches; rear ..... inches; party ..... inches.  
 19. Will foundation be on rock, sand, earth or piles? .....  
 20. What will be the size of piers in cellar? .....; distance on centres? .....; size of base of piers? .....; thickness of cap stones? .....; of bond stones? .....  
 21. Material of upper walls? .....; material of front? .....  
 22. Thickness, exclusive of ashlar, of upper walls:  
 1st story: front ..... inches; rear ..... inches; side ..... inches; party ..... inches.  
 2d story: " " " " " " " " " "  
 3d story: " " " " " " " " " "  
 4th story: " " " " " " " " " "  
 5th story: " " " " " " " " " "  
 6th story: " " " " " " " " " "  
 23. With what will walls be coped? .....  
 24. Will roof be flat, peak, or mansard? .....; material .....  
 25. Give size and material of floor and roof beams  
 1st tier, material .....; size .....; distance on centres .....  
 2d tier, " " " " " " " " " "  
 3d tier, " " " " " " " " " "  
 4th tier, " " " " " " " " " "  
 5th tier, " " " " " " " " " "  
 Roof tier, " " " " " " " " " "  
 Give thickness of headers ..... of trimmers .....  
 26. Give material of girders ..... of columns .....  
 Under 1st tier, size of girders .....; size of columns .....  
 " 2d " " " " .....; " " .....  
 " 3d " " " " .....; " " .....  
 " 4th " " " " .....; " " .....  
 " 5th " " " " .....; " " .....  
 " Roof tier, " " " " .....; " " .....



27. If front, rear or side is to be supported on columns or girders, give  
 girders, material..... ; front..... ; side..... ; rear.....  
     size..... "..... "..... ".....  
 columns, material..... "..... "..... ".....  
     size..... "..... "..... ".....
28. If constructed of frame, give material..... ; size of sill..... ;  
 plate..... ; enterties..... ; posts..... ; studs..... ;  
 braces.....
29. If open on one side, give size of plate..... posts.....
30. How will extension be occupied?..... If for  
 dwelling, give number of families on each floor.....
31. How will extension be connected with main building?.....
32. Give size of skylights..... ; material.....
33. Give material of cornices.....
34. Give material of light shafts..... ; size.....

If to be increased in height, give the following information :

35. Will building be raised from foundation, or extended on top? Give particulars.....  
 .....  
 .....
36. How many stories high will building be when raised?..... ; feet high.....
37. Will the roof be flat, peak or mansard?....., material.....
38. Material of coping?.....
39. Give material of new walls..... thickness of..... story..... inches ;  
 ..... story..... inches ; ..... story..... inches ; ..... story.....  
 ..... inches ; ..... story..... inches ; ..... story..... inches ;  
 ..... story..... inches.
40. Material of floor beams?..... Size..... tier..... ;  
 centres..... ; ..... tier..... ; centres..... ; ..... tier..... ;  
 centres..... ; ..... tier..... ; centres..... ; ..... tier..... ;  
 centres.....
41. Material of girders?..... Size under 1st tier..... ;  
 2d tier..... ; 3d tier..... ; 4th tier..... ; 5th tier..... ;  
 6th tier.....
42. Material of columns?..... Size under 1st tier..... 2d tier.....  
 3d tier..... ; 4th tier..... ; 5th tier..... ; 6th tier.....
43. Size of piers in cellar..... ; distance on centres..... ; thickness of capstones  
 to piers..... ; bond stones.....
44. If constructed of frame, give material of frame..... ; size of sills..... ;  
 corner posts..... ; middle posts..... ; enterties..... ; plates..... ;  
 braces..... ; studs.....
45. How will building be occupied when altered?.....  
 If for dwelling, state number of families on each floor?.....  
 .....
46. With what kind of fire escape will building be provided?.....  
 .....

If the Front, Rear or Side Walls, or any portion thereof, are to be taken out and rebuilt, give definite particulars, and state in what manner :

47.

.....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....

If altered Internally, give definite particulars, and state how the building will be occupied :

48.

New front shaft constructed of 3" angle iron and 8" terra cotta blocks and plastered both sides. Iron frame work of shaft to be well anchored to the brick wall and the framing of wood beams or shaft to be dovetail joint in brick masonry. Shaft to be supported on first story by columns and piers as shown on plans

49.

How much will the alteration cost?

\$3000

If the Building is to be occupied as a Flat, Apartment or Lodging House, give the following particulars :

50.

Is any part of building to be used as a store or for any other business purpose, if so, state for what?

.....

	Cellar	Base-ment	1st Floor	2d Floor	3d Floor	4th Floor	5th Floor	6th Floor
51. How many families will occupy each?								
52. Height of ceilings?								

53.

How basement to be occupied?

How made water-tight?

54.

Will cellar or basement ceiling be plastered? How?

55.

How will cellar stairs be enclosed?

56.

How cellar to be occupied?

How made water-tight?

57.

Will shafts be open or covered with louvre skylights full size of shafts?

Size of each shaft?

.....



58. Dimensions of water-closet windows? \_\_\_\_\_  
 Dimensions of windows for living rooms? \_\_\_\_\_
59. Of what materials will hall partitions be constructed? \_\_\_\_\_  
 \_\_\_\_\_
60. Of what materials will hall floors be constructed? \_\_\_\_\_  
 \_\_\_\_\_
61. How will hall ceilings and soffits of stairs be plastered? \_\_\_\_\_
62. Of what material will stairways be constructed? \_\_\_\_\_  
 Give sizes of stair well holes? \_\_\_\_\_
63. If any other building on lot, give size; front \_\_\_\_\_; rear \_\_\_\_\_; deep \_\_\_\_\_;  
 stories high \_\_\_\_\_; how occupied \_\_\_\_\_; on front or rear  
 of lot \_\_\_\_\_; material \_\_\_\_\_  
 How much space between it and proposed building? \_\_\_\_\_
64. How will floors and sides of water closets to the height of 16 inches be made waterproof? \_\_\_\_\_  
 \_\_\_\_\_
65. Number and location of water closets: Cellar \_\_\_\_\_; 1st floor \_\_\_\_\_; 2d floor \_\_\_\_\_;  
 3d floor \_\_\_\_\_; 4th floor \_\_\_\_\_; 5th floor \_\_\_\_\_; 6th floor \_\_\_\_\_
66. This building will safely sustain per superficial foot upon the first floor \_\_\_\_\_ lbs.; upon 2d floor  
 \_\_\_\_\_ lbs.; upon 3d floor \_\_\_\_\_ lbs.; upon 4th floor \_\_\_\_\_ lbs.; upon 5th floor  
 \_\_\_\_\_ lbs.; upon 6th floor \_\_\_\_\_ lbs.; upon 7th floor \_\_\_\_\_ lbs.; upon 8th floor  
 \_\_\_\_\_ lbs.

Owner, Philip A. Messer Address, 565 7100 St  
 Architect, John H. Knudsen " 318 W 42 St  
 Superintendent, \_\_\_\_\_ " \_\_\_\_\_  
 Mason, \_\_\_\_\_ " \_\_\_\_\_  
 Carpenter, \_\_\_\_\_ " \_\_\_\_\_

If a Wall or Part of already built is to be used, following:

THE CITY OF NEW YORK,

BOROUGH OF MANHATTAN, 190

The undersigned gives notice that intend to use the wall of building

as party wall in the erection of the building hereinbefore described, and respectfully requests that the same be examined and a permit granted therefor. The foundation wall built of inches thick, feet below curb; the upper wall built of inches thick, feet deep, feet in height.

(Sign here)

REPORT UPON APPLICATION.

The Bureau of Buildings for The Borough of Manhattan.

THE CITY OF NEW YORK,

BOROUGH OF MANHATTAN, 190

To the Superintendent of Buildings for the Borough of Manhattan:

I respectfully report that I have thoroughly examined and measured the wall, etc., named in the foregoing application, and found the foundation wall to be built of inches thick, feet below curb, the upper wall built of inches thick, feet deep, feet in height, and that the mortar in said wall is hard and good, and that the building in a good and safe condition to be altered as proposed. The wall built as party wall and in a good and safe condition to be used as proposed. Building occupied as follows: basement, 1st floor, 2d floor, 3d floor, 4th floor, 5th floor, 6th floor, 7th floor, 8th floor, 9th floor, 10th floor

What is the nature of the ground

What kind of sand was used in the mortar?

If building is VACANT, state how the same was occupied?

Is the PRESENT building to be connected with any ADJOINING building? If so, state dimensions and material of adjoining building, viz: Material; feet front; feet rear; feet deep; feet in height; number of stories; how occupied?

(The Inspector must here state what defects, if any, are in the walls.)

(The Inspector must state the thickness of wall in each and every story.)

Inspector.

912  
19-05

DEPARTMENT OF BUILDINGS OF THE CITY OF NEW YORK  
FOR THE BOROUGH OF MANHATTAN

RECEIVED APR 13 1905  
FOR THE BOROUGH OF MANHATTAN

PLAN No. 809 of 1905

State and City of New York,  
County of N.Y.

John H. Stumber

being duly sworn, deposes and says: That he resides at Number 318 W. 42 St

in the Borough of Manhattan

in The City of New York, in the County of New York

in the State of New York; that he is architect for

Philip A. Tresser

owner in fee of all that certain lot, piece or parcel of land, shown on the diagram annexed hereto and made a part hereof, situate, lying and being in the Borough of Manhattan

in The City of New York, aforesaid, and known and designated as Number 328 E. 11 St

and hereinafter more particularly described;

that the work proposed to be done upon the said premises, in accordance with the accompanying detailed statement in writing of the specifications and plans of such proposed work, is duly authorized to be performed by

Philip A. Tresser

and that John H. Stumber

duly authorized by Philip A. Tresser

to make application for the approval of such detailed statement of specifications and plans in his behalf.

Deponent further says that the full names and residences, street and number, of the owner or owners of the said land, and also of every person interested in said building or proposed building, structure, or proposed structure, premises, wall, platform, staging or flooring, either as owner, lessee, or in any representative capacity, are as follows:

Philip A. Tresser No. 565 W. 160 St

as Owner

No

as

No

as

No

as

No

as



The said land and premises above referred to, are situate at, bounded and described as follows, viz.:

BEGINNING at a point on the South side of 11 St  
....., distant 225 feet  
West  
..... from the corner formed by the intersection of  
1 Ave and 11 St  
running thence West 25 feet;  
thence South 100 feet;  
thence East 25 feet;  
thence North 100 feet  
to the point or place of beginning.

Sworn to before me, this 18  
day of April 1905

John H. Kumberg

E. J. Carroll

Commissioner of Deeds  
City of New York

Notary Public, ..... County.

In The City of New York.

THE BUREAU OF BUILDINGS FOR THE BOROUGH OF MANHATTAN

Office, No. 220 FOURTH AVENUE,

S. W. Corner 18th Street.

PLAN No. 809 } NEW BUILDINGS } 190 5  
ALTERATIONS }

Location 328 East 11th St

BOROUGH OF MANHATTAN.

In all cases Inspectors will furnish the following information without regard to the information given in the application and plans on file in the Bureau.

- Foundation walls. Depth below curb level \_\_\_\_\_ material \_\_\_\_\_  
thickness, front \_\_\_\_\_ inches; rear \_\_\_\_\_ inches; side \_\_\_\_\_ inches; party \_\_\_\_\_ inches.
- Upper walls. Material \_\_\_\_\_; thickness as follows:  
Basement: front \_\_\_\_\_ inches; rear \_\_\_\_\_ inches; side \_\_\_\_\_ inches; party \_\_\_\_\_ inches.  
1st story: " " " " " " " " " "  
2d story: " " " " " " " " " "  
3d story: " " " " " " " " " "  
4th story: " " " " " " " " " "  
5th story: " " " " " " " " " "  
6th story: " " " " " " " " " "
- Nature of ground \_\_\_\_\_
- Quality of sand used in mortar \_\_\_\_\_
- What walls are built as party walls? \_\_\_\_\_
- What fire escapes are provided? \_\_\_\_\_
- Is building fireproof? \_\_\_\_\_
- If building is vacant, state how the same was occupied Stores & Tenement
- Is the present building to be connected with any adjoining building?  
If so, state dimensions and material of adjoining building, viz:—  
Material \_\_\_\_\_; feet front \_\_\_\_\_, feet rear \_\_\_\_\_  
feet deep \_\_\_\_\_; feet in height \_\_\_\_\_; number of stories \_\_\_\_\_  
how occupied \_\_\_\_\_
- How is present building occupied? Basement Storage; 1st floor Stores & 1 fam  
2d floor 4 fam; 3d floor 4 fam; 4th floor 4 fam; 5th floor 4 fam  
6th " \_\_\_\_\_; 7th " \_\_\_\_\_; 8th " \_\_\_\_\_; 9th " \_\_\_\_\_
- Height of building—feet 59; stories 5
- Size of building—feet front 25; feet rear 25; feet deep 75
- Size of lot— " " 25; " " 25; " " 100
- Are fireproof shutters provided? \_\_\_\_\_ What kind? \_\_\_\_\_

Dated, April 20<sup>th</sup> 1905

W. J. McKeon Inspector.

# ORIGINAL BUREAU OF BUILDINGS

## BOROUGH OF MANHATTAN, CITY OF NEW YORK

NOTICE—This Application must be TYPEWRITTEN and filed in TRIPLICATE, and ONE copy sworn to by Applicant. A copy must be kept in plain view on the work at all times until completion.

PERMIT No. 352 **192** } Application No. 362 **192** 7.  
No Bx }  
ALT. }  
P & D }  
ELEV }  
SIGN }

LOCATION 328 East 11th. Street BLOCK 452 LOT 22  
New York City March 22nd. 192 7.

To the Superintendent of Buildings:

Application is hereby made for a PERMIT to perform the entire

work described in the above numbered application and the accompanying plans. If no work is performed within one year from the time of issuance this permit shall expire by limitation as provided by law; and the applicant agrees to comply with all provisions of the Building Code of the City of New York and with the provisions of all other laws and rules relating to this subject. Compensation insurance has been secured in accordance with the requirements of the Workmen's Compensation Law as follows:

Applicant doing work alone and employing no help.

STATE, COUNTY AND }  
CITY OF NEW YORK } ss. Giuseppe Angelillo

Typewrite Name of Applicant

being duly sworn, deposes and says: That he resides at Number 98-2nd. Place  
in the Borough of Brooklyn in the City of New York, in the County of Kings  
in the State of New York, that he is contractor for the

owner in fee of all that certain lot, piece or parcel of land, shown on the diagram annexed to the approved application and made a part thereof, situate, lying and being in the Borough of Manhattan, City of New York aforesaid, and known and designated as Number 328 East 11th. Street

and therein more particularly described; that the work proposed to be done upon the said premises, in accordance with the approved application and accompanying plans is duly authorized by Vincenzo Caprio  
(Name of Owner or Lessee)

and that Giuseppe Angelillo is duly authorized by the aforesaid owner to make application for a permit to perform said work set forth in the approved application and accompanying plans, and all the statements herein contained are true to deponent's own knowledge.

Sworn to before me, this 22nd. (SIGN HERE) Giuseppe Angelillo  
day of March 192 7  
J. J. [Signature]  
COMMISSIONER OF DEEDS

Satisfactory evidence having been submitted as indicated above that compensation insurance has been secured in accordance with the Workmen's Compensation Law, a permit is hereby issued for the performance of the entire work described in the above numbered application and the accompanying plans.

EXAMINED AND RECOMMENDED FOR APPROVAL ON MAR 22 1927


[Signature]  
Examiner

Approved MAR 22 1927 **1927**  
[Signature]  
Superintendent of Buildings, Borough of Manhattan



# BUREAU OF BUILDINGS

## BOROUGH OF MANHATTAN, CITY OF NEW YORK



NOTICE—This Application must be TYPEWRITTEN and filed in TRIPLICATE.  
 "SPECIFICATIONS—SHEET A" (Form 152) must be filed with EVERY Alteration Application.  
 "SPECIFICATIONS—SHEET B" (Form 158) must be filed, in addition, in case the building is to be raised in height or occupancy changed so as to increase floor loads, or if building is to be enlarged on one side.

**ALT.** APPLICATION No. 362 1927  
 192 BLOCK 452 LOT 22

LOCATION No. 328 East 11th Street

DISTRICT (under building zone resolution) Use Business Height 1-1/2 Area B

Examined Mar. 9/27 192 M. J. Gardner Examiner.

### SPECIFICATIONS—SHEET A

- (1) NUMBER OF BUILDINGS TO BE ALTERED one  
 Any other building on lot or permit granted for one? no
- (2) ESTIMATED COST OF ALTERATION: \$500,00
- (3) OCCUPANCY (in detail):  
 Of present building Stores and tenement

Of building as altered Stores and tenement

(4) SIZE OF EXISTING BUILDING:

At street level	25	feet front	72	feet deep
At typical floor level	25	feet front	72	feet deep
Height	5	stories	50	feet

(5) SIZE OF BUILDING AS ALTERED:

At street level	25	feet front	72	feet deep
At typical floor level	25	feet front	72	feet deep
Height	5	stories	50	feet

(6) CHARACTER OF CONSTRUCTION OF PRESENT BUILDING: Ordinary [Frame, Ordinary or Fireproof]

(7) NUMBER OF OCCUPANTS (in each story of building as altered, giving males and females separately in the case of factories):

No change in occupancy

(8) STATE GENERALLY IN WHAT MANNER THE BUILDING WILL BE ALTERED:

Cut new door opening between kitchen and livingroom.  
Remove studpartition between bathroom and water closet compartment  
and stud up floor opening from water closet to hall, on 3rd story,  
as per plans.